

Nonmetallic QO® and Metal-Enclosed HOMELINE® Hot Tub/Pool/Spa Package

Selecting an outdoor load center for a hot tub, pool or spa has never been easier.



Nonmetallic QO enclosure



HOMELINE steel enclosure

Square D offers hot tub/pool/spa electrical protection in either metallic or nonmetallic versions with the QO® Hot Tub/Pool/Spa Pack and the new HOMELINE® Hot Tub/Pool/Spa Pack. The QO pack includes a QO Nonmetallic Load Center and an installed 50A Ground Fault Circuit Interrupter. The HOMELINE pack includes a 50A HOMELINE Outdoor Metallic Load Center and an installed HOM250GFI. Along with many other features and benefits, the QO250GFI and the HOM250GFI 2-Pole Ground Fault Circuit Breaker protects single pole and two pole loads against ground and overcurrent faults. The load center and GFCI breaker provide protection for outdoor circuits such as hot tubs, fountains, swimming pools or spas.

QO Hot Tub/Pool/Spa Pack Features:

- Non-corrosive, compact rainproof enclosure will not rust
- 50A QO 2-Pole QWIK-GARD® Ground Fault Circuit Breaker (QO250GFI) installed in load center (QO2-4L60NRNM) protects 120 V and 240 V loads against ground and overcurrent faults
- Exclusive VISI-TRIP® Indicator on QO GFCI easily identifies tripped circuit breaker
- Side-hinged door for easy access, can be padlocked
- Molded interior trim
- Main lug load center designed for applications up to 60 amperes 120/240 VAC, 1 Ø 3 wire with ground
- 10,000 amperes short-circuit current interrupting rating
- Warranty: 10 years on enclosure, lifetime of the device on the GFCI
- UL Listed

HOMELINE Hot Tub/Pool/Spa Pack Features:

- 50A HOMELINE 2-Pole QWIK-GARD Ground Fault Circuit Breaker (HOM250GFI) installed in a 50A outdoor load center (HOM2-4L50R) protects 120 V and 240 V loads against ground and overcurrent faults
- Painted, zinc-coated steel outdoor enclosure
- Top-hinged door can be padlocked
- Main lug load center designed for applications up to 50 amperes 120/240 VAC, 1 Ø 3 wire with ground
- 10,000 amperes short-circuit current interrupting rating
- Easy-to-remove steel interior trim
- Warranty: 10 years on enclosure, lifetime of the device on the GFCI when used in a residential installation
- UL Listed

Catalog Number	UPC Code	Dimensions	Weight
QOE250GFIM	7-85901-38950-7	3.9" H x 6.5" W x 9.8" D	2.7 lbs.
HOM250SPA	7-85901-23054-0	9.5" H x 5.4" W x 4.4" D	6 lbs.

For more information, contact your Square D distributor today, or call 1-888-SQUARED (1-888-778-2733).

