



U1232-RRL-KK-K1

4 Terminal Ringless Large Hub Open Adapt To Small Hub Open Horn Bypass 2 Position
Single Connector 6-350kcmil 150 Ampere



SPECIFICATIONS

| | |
|---------------------------|--|
| Brand Name | Milbank |
| Type | Ringless Meter Socket |
| Application | Meter Socket |
| Standard | UL Listed;Type 3R |
| Voltage Rating | 300 Volts Alternating Current |
| Amperage Rating | 150 Continuous Ampere |
| Phase | 1 Phase |
| Frequency Rating | 60 Hertz |
| Size | 5.125L x 26.5W x 14H |
| Number of Main Breakers | 0 |
| Main Breaker Size | No Main Breaker |
| Cable Entry | Overhead or Underground |
| Terminal | Single Mechanical |
| Insulation | Glass Polyester |
| Mounting | Surface Mount |
| Material | G90 Galvanized Steel with Powder Coat Finish |
| Number of Jaws | 4 Terminal |
| Bypass Provision | Horn Bypass |
| Number of Meter Positions | 2 Positions |
| Equipment Ground | Triplex Ground |
| Hub/Closing Plate | Large Hub Opening Adapted to Small Hub Opening |
| Line Side Wire Range | 6 AWG - 350 kcmil |
| Load Side Wire Range | 6 AWG - 350 kcmil |
| Number Of Receptacles | 0 |
| Height | 14 IN |
| Length | 5.125 IN |
| Width | 26.5 IN |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply

with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.