


Submittal

Variable Speed Air Handlers with Epoxy Coated Coil 1.5 – 2 Ton

5TAMXB02AV21DA



The Diagnostics Mobile App is available by scanning a QR code located inside this unit or by searching for the Link Diagnostics App in your App Store.


Note: "Graphics in this document are for representation only. Actual model may differ in appearance."

Note: For use with BAYEA series heaters ONLY.

Note: This unit can be used in Link Communicating mode or 24 volt mode.

Note: Need to use Diagnostics App to configure blower delays and accessories etc., in 24 volt mode.

Outline Drawing



Model Number	A	B	C	D	E	F	H	FLOW CONTROL	GAS LINE BRAZE	LIQ LINE BRAZE
5TAMXB02AV21DA	49.9	39.6	14.5	17.5	14.5	7.3	24.4	EEV	3/4	3/8

Product Specifications

MODEL	5TAMXB02AV21DA
Family Description	R-454B Variable Speed Air Handler with Epoxy Coated Coil
Description	R-454B Variable Speed Air Handler with Epoxy Coated Coil, Epoxy Coated All-Aluminum Plate Fin Coil, 4-Way Poise, Link Communicating or 24V System Control, 208-230/1/60, 18K - 24K BTUH Capacity
Application Configuration	4-Way
RATED CAPACITY RANGE (BTUH)	18K - 24K
SYSTEM CONTROL TYPE	Link Communicating or 24V
POWER CONN. - V/PH/HZ	208-230/1/60
Max Breaker Size, Without Electric Heater (Amps)	15
Max Breaker Size, With Electric Heater (Amps) ^(a) ^(b)	60
Name Plate	See the name plate
COIL TYPE	Epoxy Coated All-Aluminum Plate Fin
Refrigerant Type	R-454B
Refrigerant Control	EEV
Refrigerant Line Connection - Gas (in.)	3/4
Refrigerant Line Connection - Liquid (in.)	3/8
BLOWER TYPE	Direct Drive Centrifugal
Configuration	Blow Through
Dimensions (Diameter x Width (in.))	11 x 8
Motor Type	Variable Speed
Nominal CFM ^(c)	800
Speed (RPM)	1050
Volts/Ph/Hz	208-230/1/60
Full Load Amps	3.9
FILTER RACK (YES, NO)	Yes
Dimensions (Length x Width (in.))	16 x 20 x 1
DUCT CONNECTIONS	L x W
Supply (in.)	14.5 x 14.35
Return (in.)	14.5 x 17.15
DRAIN CONN. SIZE (IN.)	3/4 NPT
DIMENSIONS	H x W x D
Uncrated (in.)	49-7/8 x 17-1/2 x 21-3/4
Crated (in.)	51-3/8 x 20-1/2 x 25-3/4
WEIGHT - SHIPPING/NET (LBS.)	126/120

(a) Maximum overcurrent protection is dependent on which electric heater is installed. See Installation, Operation, and Maintenance manual or unit name plate.

(b) For CFM versus external static pressure (in. w.c.), refer to Installation, Operation, and Maintenance manual.

(c) If installing system outside of the United States, accessory electric heaters may not be installed.

Heater Attribute Data

Note: Heater size will be announced when using the resistor that is being provided with the BAYEA heater. Heater can also be configured in the UX360 User Interface or Diagnostics Mobile App.

5TAMXB02AV21DA											
Heater Model No.	No. of Circuits	240 Volt					208 Volt				
		Capacity		Heater Amps per Circuit	Minimum Circuit Ampacity	Maximum Overload Protection	Capacity		Heater Amps per Circuit	Minimum Circuit Ampacity	Maximum Overload Protection
		kW	BTUH				kW	BTUH			
No Heater	0	-	-	3.9 **	5	15	-	-	3.9 **	5	15
BAYEA(13/AC)04+ +1	1	3.84	13100	16.0	25	25	2.88	9800	13.8	22	25
BAYEA(13/AC)05+ +1	1	4.80	16400	20.0	30	30	3.60	12300	17.3	27	30
BAYEA(13/AC)08+ +1	1	7.68	26200	32.0	45	45	5.76	19700	27.7	39	40
BAYEA(13/AC)10+ +1 ^(a)	1	9.60	32800	40.0	55	60	7.20	24600	34.6	48	50
BAYEA(13/AC)10LG3	1-3 PH	9.60	32800	23.1	33	35	7.20	24600	20.0	29	30
Note: ** Motor Amps											

^(a) Heater not qualified for 208V when installed in horizontal left position without Heat Pump

Note: See Product Data or Air Handler nameplate for approved combinations of Air Handlers and Heaters.

Note: Heater model numbers may have additional suffix digits.

5TAMX Air Flow Performance Tables

5TAMXB02AV21DA AIRFLOW PERFORMANCE CONSTANT CFM MODE / CONSTANT TORQUE MODE														
OUTDOOR MULTIPLIER (TONS)	COOLING AIRFLOW SETTING	AIRFLOW POWER	EXTERNAL STATIC PRESSURE (Constant CFM/ Constant Torque)					HEATING AIRFLOW SETTING	AIRFLOW POWER	EXTERNAL STATIC PRESSURE				
			0.1	0.3	0.5	0.7	0.9			0.1	0.3	0.5	0.7	0.9
1.5 tons	290 CFM/ton	CFM Watts	407/546 22/40	430/403 51/48	398/NA 77/NA	347/NA 103/NA	255/NA 133/NA	290 CFM/ton	CFM Watts	416 22	426 49	401 76	330 101	291 134
	350 CFM/ton	CFM Watts	534/630 39/57	549/531 71/68	542/360 103/73	509/NA 132/NA	445/NA 156/NA	350 CFM/ton	CFM Watts	532 37	550 69	542 101	507 129	434 152
	400 CFM/ton	CFM Watts	617/697 54/72	633/617 90/86	632/501 125/96	604/NA 156/NA	559/NA 181/NA	400 CFM/ton	CFM Watts	660 62	680 99	679 136	658 169	614 197
	450 CFM/ton	CFM Watts	691/762 72/91	710/693 111/106	707/602 148/119	688/478 183/127	649/NA 212/NA	450 CFM/ton	CFM Watts	690 69	710 108	709 145	690 180	651 208
	290 CFM/ton	CFM Watts	593/680 54/68	613/595 85/81	607/470 119/90	583/208 150/94	527/132 175/138	290 CFM/ton	CFM Watts	593 48	613 82	608 116	582 147	527 172
2 tons †	350 CFM/ton	CFM Watts	717/783 79/98	733/717 118/114	733/632 157/127	714/519 192/136	678/355 222/143	350 CFM/ton	CFM Watts	714 75	734 115	734 153	716 189	679 218
	400 † CFM/ton	CFM Watts	810/868 108/128	827/811 152/146	827/740 194/161	813/652 233/173	782/543 265/182	400 (a) CFM/ton	CFM Watts	862 122	881 168	884 213	874 254	849 290
	450 CFM/ton	CFM Watts	903/954 144/165	918/902 192/182	920/839 238/201	909/764 280/215	884/674 316/224	450 CFM/ton	CFM Watts	899 136	917 184	921 231	912 273	889 310
	290 CFM/ton	CFM Watts	741/820 86/110	757/759 126/127	757/681 166/141	739/582 202/152	705/452 232/159	290 CFM/ton	CFM Watts	738 81	757 122	758 162	742 198	707 229
	350 CFM/ton	CFM Watts	880/947 134/162	896/895 182/181	896/832 226/198	885/757 267/211	859/665 302/221	350 CFM/ton	CFM Watts	876 127	895 174	898 220	888 261	864 297
2.5 tons	400 CFM/ton	CFM Watts	996/1059 188/220	1011/ 241/240	1014/954 291/257	1006/887 336/271	985/807 375/280	400 CFM/ton	CFM Watts	1064 215	1083 272	1089 326	1084 375	1066 418
	450 CFM/ton	CFM Watts	1120/ 1180	1135/ 1134	1137/ 1081	1129/ 1019	1108/946 463/355	450 CFM/ton	CFM Watts	1115 244	1133 304	1139 360	1133 410	1116 453
	290 CFM/ton	CFM Watts	875/943 132/160	891/891 179/179	892/891 224/196	880/751 265/209	854/659 300/218	290 CFM/ton	CFM Watts	871 125	890 172	894 217	883 259	859 295
3 tons	350 CFM/ton	CFM Watts	1045/ 1106	1060/ 1059	1063/ 1004	1055/939 369/299	1035/862 409/308	350 CFM/ton	CFM Watts	1040 202	1058 257	1064 310	1059 358	1041 401
	400 CFM/ton	CFM Watts	1200/ 1257	1212/ 1211	1212/ 1159	1200/ 1099	1129/ 1030	400 CFM/ton	CFM Watts	1291 368	1302 432	1300 487	1220 478	1138 470
	450 CFM/ton	CFM Watts	1358/ 1403	1333/ 1359	1256/ 1308	1177/ 1251	1095/ 1187	450 CFM/ton	CFM Watts	1355 422	1360 483	1286 476	1208 468	1128 462
• † Factory Setting • Status LED will blink once per 100 CFM requested. In torque mode, actual airflow may be lower. • Torque mode will reduce airflow when static is above approximately 0.3" water column. • All heating modes default to Constant CFM. • Cooling airflow values are with wet coil, no filter														
5TAMXB02AV21DA Minimum Heating Airflow Settings														
MODEL NO.	BAYEAAAC04BK1 BAYEAAAC04LG1 BAYEAAAC05BK1 BAYEAAAC05LG1	BAYEAAAC08BK1 BAYEAAAC08LG1	BAYEAAAC10BK1 BAYEAAAC10LG1		BAYEAAAC10LG3		BAYEABC15BK1	BAYEACB15LG3	BAYEABC20BK1					
TAMXB0A24	638/713	638/900	675/900		600/713		-	-	-					
WITHOUT HEAT PUMP / WITH HP — SEE AIR HANDLER NAMEPLATE FOR APPROVED COMBINATIONS														

(a) Factory heating default setting is 430 CFM/ton

Features and Benefits

- Unique cabinet design
 - 2% or less air leakage
 - Precision applied — durable door seals
 - Specially designed air seal around refrigerant, condensate and conduit connections
 - Double wall foamed cabinet system
 - R-4.2 Insulating Value (Avg Insulating Value R-8.2)
 - No loose fiber design
 - Smooth cleanable interior design
 - Sweat eliminating design
 - Composite foamed cabinet doors
 - Water proof cabinet design
 - Integrated horizontal drain pans
 - Modular cabinet
- Multi-position up/down flow horizontal left/right
- Link™ Communicating or 24V Control
- Side return option (sold as accessory)
- Pre-marked Conduit Connection Locations
- Alert code notification
- Low voltage terminal connection point
- Phillips head door fasteners
- **Vortica®** blower with polarized plug connections and integrated slide deck for easy removal
- Aluminum coil with integrated slide deck for easy removal and polarized plug connections on coil EEV
- Patented enhanced coil fin
- Electronic Expansion Valve (EEV) with low ambient and low superheat compressor protection
- Slide in electric heaters with polarized plug connections (sold as accessory)
- Slide in hot water coils with polarized plug connections (sold as accessory)
- UVC light kit with safety switch and polarized plug connections (sold as accessory)
- Labeled panels and connections
- Molded in 1" standard filter rail
- Variable speed ECM motor
- Soft start fan motor operation
- **Comfort R™** mode
- Built in fan delay modes
- Maximum width of 23.5"
- Compact 20.8" depth with doors removed
- Fused 24V power
- **5 Year Warranty**
- **10 Year Warranty Registered**
- **Optional Extended Warranty Available**

About Trane and American Standard Heating and Air Conditioning

Trane and American Standard create comfortable, energy efficient indoor environments for residential applications. For more information, please visit www.trane.com or www.americanstandardair.com.



The manufacturer has a policy of continuous data improvement and it reserves the right to change design and specifications without notice. We are committed to using environmentally conscious print practices.