

Miscellaneous

MISCELLANEOUS	
POND LOOP SPACED COIL	
3647	Pond loop spaced coil, 3/4" PE X 300'

Spaced coils are designed to enhance convective flow through the coil via factory-installed spacers. The assembly is bound with nylon ties, and strapped to pallet for shipping. These coils are typically 0.5 to 1 ton [1.76 to 3.52 kW] of heat rejection/heat absorption capacity per coil (must be verified with Pond Coil Calculator at www.geo-flo.com).



EQUIPMENT PADS- high density rubber equipment pads	
4055	24" x 36", boxed- individual
4056	28" x 36", boxed- individual
4027	24" x 36", bulk- 30 piece minimum/multiples-pallet
4028	28" x 36", bulk- 30 piece minimum/multiples-pallet

Geo-Flo's geothermal equipment pads are made of high density SBR recycled rubber, which provides a high degree of vibration and sound absorption for compressor-bearing units installed indoors.

Equipment Pad Features:

- Absorbs low frequency sound/vibration (particularly suited for compressors)
- Environmentally friendly recycled material (SBR bonded black recycled rubber)
- High density (60 lbs/cu. ft.)
- Anti-skid texture
- Non-porous, both sides
- Rated for packaged unit weight (very little compression)

