



5" UNIVERSAL IC REMODEL HOUSING

INCANDESCENT LAMPS

IC20R

Project: _____

Fixture Type: _____

Location: _____

Contact/Phone: _____

PRODUCT DESCRIPTION

IC Air-Loc® Remodel Housing • Energy efficient, sealed housing
 • IC Remodel Housing for remodel application where back side of ceiling is not accessible • Installs through an opening in the ceiling from below • Secured in place by factory installed remodel springs
 • Can be completely covered with insulation • When used with Air-Loc Gasket, stops infiltration and exfiltration of air, reducing heating and cooling costs • Trims shown with Air-Loc symbol  do not require gasket.

PRODUCT SPECIFICATIONS

Lamp Lamp ratings based on trim selected—see page 2.

Socket Medium base porcelain with nickel-plated copper screw shell
 • Drop socket with spring to accommodate certain trim installation.

Trims Trim selection shown on reverse.

Labels UL listed for through-branch wiring, damp locations and IP
 • Product thermally protected against improper use of lamps
 • Union made • UL Listed/CSA certified • Trims 210N, 211 and 212N are wet location approved for covered ceiling applications
 • Trims 215 and 216 are wet location approved for covered ceiling applications, **when used with outdoor rated lamps.**

Testing All reports are based on published industry procedures; field performance may differ from laboratory performance.



Specifications subject to change without notice.

INSTALLATION

Junction Box Pre-wired junction box, UL listed/CSA certified for through-branch wiring maximum 4 No. 12 AWG 90° C branch circuit conductors (2 in, 2 out) • Junction box provided with removable access plate, (5) 1/2" knockouts, (4) Non-metallic sheathed cable connectors and ground wire • Knockouts equipped with pryout slots.

Housing IC housing, .032" aluminum sealed for Air-Loc Compliance • Remodel springs accommodate up to 1 1/8" ceiling thickness.

DIMENSIONS



5 1/2" CEILING CUTOUT

Accessories

Catalog Number	Description
ALG5R	Air-Loc Gasket

To order, specify catalog number.

PRODUCT CODES

Catalog Number	Input Voltage	Lamp Rating
IC20R 5" Incandescent Remodel IC Housing	120V	A19/BR30/PAR20/PAR30/PAR30L/R20/R30 (See page 2 for max. trim rating)

Housing and trim can be ordered together or separate, but will always ship separately.

5" UNIVERSAL IC REMODEL HOUSING

INCANDESCENT LAMPS IC2OR

TRIMS/LAMPS

	Catalog Number	Description	Max. Lamp Rating	
	201N WH	Open Frame Trim, White	65W BR30	
	205 BWH	Black Baffle, White Trim Ring	50W PAR30	
**	205 WWH	White Baffle, White Trim Ring		
	205 BSC	Black Baffle, Satin Chrome Trim Ring		
	205 BABZ	Black Baffle, Classic Aged Bronze Trim Ring		
	204 CWH	Clear Alzak® Cone, White Trim Ring	50W PAR30	
	204 GWH	Gold Alzak® Cone, White Trim Ring		
	204 BWH	Black Alzak® Cone, White Trim Ring		
**	204 PTSC	Pewter Alzak® Cone, Satin Chrome Trim Ring		
	204 HZWH	Haze Cone, White Trim Ring		
	204 WWH	Gloss White Cone, White Trim Ring		
	204 WHZWH	Wheat Haze Cone, White Trim Ring		
	204 WHZABZ	Wheat Haze Cone, Classic Aged Bronze Trim Ring		
	206 CWH	Clear Alzak® Cone, White Trim Ring	50W PAR30	
	206 GWH	Gold Cone, White Trim Ring		
	206 BWH	Black Cone, White Trim Ring		
**	206 PTSC	Pewter Cone, Satin Chrome Trim Ring		
	206 HZWH	Haze Cone, White Trim Ring		
	206 WHZWH	Wheat Haze Cone, White Trim Ring		
	206 WHZABZ	Wheat Haze Cone, Classic Aged Bronze Trim Ring		
	207 CWH	Clear Alzak® Cone, White Trim Ring	50W PAR20/R20	
	207 GWH	Gold Cone, White Trim Ring		
	207 BWH	Black Cone, White Trim Ring		
**	207 WWH	White Cone, White Trim Ring		
	207 HZWH	Haze Cone, White Trim Ring		
	207 WHZWH	Wheat Haze Cone, White Trim Ring		
AIR-LOC	215 BWH ◆◆	Black Baffle, White Trim Ring	65W BR30, 75W PAR30L, 75W PAR30 w/Socket Extender	
	215 WWH ◆◆	White Baffle, White Trim Ring		
	216 CWH ◆◆	Clear Alzak® Cone, White Trim Ring	65W BR30, 75W PAR30L, 75W PAR30 w/Socket Extender	
AIR-LOC	216 GWH ◆◆	Gold Cone, White Trim Ring		
	216 WWH ◆◆	White Cone, White Trim Ring		
	216 HZWH ◆◆	Haze Cone, White Trim Ring		
	216 WHZWH ◆◆	Wheat Haze Cone, White Trim Ring		
	208N BWH	Eyeball with Black Baffle, White Trim Ring	50W PAR20/R20	
	208N WWH	Eyeball with White Baffle, White Trim Ring		
	529 WH	Eyeball Trim, White	75W PAR30	
	529 SC	Eyeball Trim, Satin Chrome		
	529 ABZ	Eyeball Trim, Classic Aged Bronze		
	209N WH	Gimbal Ring with Flat Trim, White	75W PAR30	
	688 BWH	Black Baffle, White Trim Ring	50W PAR30	
	688 WWH	White Baffle, White Trim Ring		
	689 CWH	Clear Alzak® Cone, White Trim Ring	50W PAR30	
	689 GWH	Gold Cone, White Trim Ring		
	689 WWH	White Cone, White Trim Ring		
	689 HZWH	Haze Cone, White Trim Ring		
	689 WHZWH	Wheat Haze Cone, White Trim Ring		
AIR-LOC	210N WH ◆	Lensed Flat Glass Shower Trim, White	40W A19	
	210N SC ◆	Lensed Flat Glass Shower Trim, Satin Chrome		
	210N ABZ ◆	Lensed Flat Glass Shower Trim, Classic Aged Bronze		
AIR-LOC	211 PW ◆	Lensed Dome Glass Shower Trim, Plastic White	40W A19	
	212N WH ◆	Frosted Lens with Clear Center Trim, White	40W A15, 50W PAR30	
AIR-LOC	212N SC ◆	Frosted Lens with Clear Center Trim, Satin Chrome		
	212N ABZ ◆	Frosted Lens with Clear Center Trim, Classic Aged Bronze		

Trim Size: 6¼" O.D. (except Cat No. 529 - 6½" O.D.)
Alzak is a registered trademark of Alcoa Corp.
Note: In Canada when insulation is present,
Type IC fixtures must be used.

AIR-LOC JUNO IC housings meet IECC Energy Code requirements per ASTM E283.

Air-Loc® rated trims are pre-gasketed for minimum air leakage with IC housings.

◆ UL Listed for use in wet location.

◆◆ UL Listed for use in wet location with outdoor rated lamp.

** NOTE: TR5 Trim Ring compatible with 204, 205, 206, 207 trims.

Housing and trim can be ordered together or separate, but will always ship separately.