



PJ-32N



Product Description

4 square inch electrical junction box for use with nonmetallic sheathed cable

Brand: flexBOX®
Catalog #: PJ-32N

Carton Quantity: 48
Carton Weight: 13 lb.

Height: 4 in.
Width: 4 in.
Depth: 2-1/2 in.
Volume: 32.5 cu. in.
Type of Installation: New Work
Wall Box

UPC: 085339990031
UNSPSC: 39121332
Patents:
U.S. Patent No. 6,365,831 B1
Country of Origin: United States of America

FEATURES

Machine tapped cover screw holes, cover screws included

APPLICATION

In the wall junction box with optional single and two gang plaster ring covers for junction box capacity and device applications - 2 HR fire resistive walls

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)
Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Black

ADDITIONAL MATERIALS

Carbon steel fasteners

MATERIAL

Polyvinyl Chloride

Plated carbon steel fasteners

MOUNTING

Angled mid-nails