

SR TRACE®

SELF-REGULATING, PRE-TERMINATED CABLE



SR Trace® is a self-regulating heating cable that automatically varies its heat output with changes in surrounding temperature. Normally installed in commercial applications, SR Trace helps provide maximum freeze protection for pipes and vessels in ambient temperatures down to -40°F/-40°C. Use SR Trace cables to prevent water pipes from freezing, to maintain liquids in pipes at a constant temperature in order to prevent degradation of the liquid, or to maintain viscosity for flow conditions. SR Trace can be installed in dry or wet environments. Available in power densities of 3, 5, and 8 watts per foot at 50°F/10°C, for both 120 Vac and 240 Vac applications. 240 Vac can be used for 208 Vac or 277 Vac applications. SR Trace cables are UL Listed to US and Canadian Safety Standards and CSA Certified. See item specific certifications below.

| CATALOG NUMBER | DESCRIPTION | CTN QTY | CTN WGT | UPC | CERTIFICATIONS |
|----------------|---|---------|---------|-----------------|---|
| SR31CB | 3 w/ft, 120 Vac, cut-to-order | - | - | - |  |
| JP31CB | 3 w/ft, 120 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS) | 1 | 8 | 0-13627-06931-2 | |
| SR32CB | 3 w/ft, 240 Vac, cut-to-order | - | - | - | |
| JP32CB | 3 w/ft, 240 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS) | 1 | 8 | 0-13627-06932-9 | |
| SR51CB | 5 w/ft, 120 Vac, cut-to-order | - | - | - | |
| JP51CB | 5 w/ft, 120 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS) | 1 | 8 | 0-13627-06930-5 | |
| SR52CB | 5 w/ft, 240 Vac, cut-to-order | - | - | - | |
| JP52CB | 5 w/ft, 240 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS) | 1 | 8 | 0-13627-06929-9 | |
| SR81CB | 8 w/ft, 120 Vac, cut-to-order | - | - | - | |
| SR82CB | 8 w/ft, 240 Vac, cut-to-order | - | - | - | |
| SR31J | 3 w/ft, 120 Vac, cut-to-order | - | - | - |  |
| SR31J250 | 250' self-dispensing reel | 1 | 20 | 0-13627-06925-1 | |
| SR32J | 3 w/ft, 240 Vac, cut-to-order | - | - | - | |
| SR32J250 | 250' self-dispensing reel | 1 | 20 | 0-13627-06923-7 | |
| SR51J | 5 w/ft, 120 Vac, cut-to-order | - | - | - | |
| SR51J250 | SR51J on a 250' Reel | 1 | 20 | 0-13627-06921-3 | |
| SR51J750 | 750' self-dispensing reel | 1 | 72 | 0-13627-06922-0 | |
| JP51J | 5 w/ft, 120 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS) | 1 | 8 | 0-13627-06927-5 | |
| SR52J | 5 w/ft, 240 Vac, cut-to-order | - | - | - | |
| SR52J250 | SR52J on a 250' Reel | 1 | 20 | 0-13627-06919-0 | |
| SR52J750 | 750' self-dispensing reel | 1 | 72 | 0-13627-06920-6 | |
| JP52J | 5 w/ft, 240 Vac Job Pack (100' cable, 2-SRP,1-SRST,1-SRTCS) | 1 | 8 | 0-13627-06928-2 |  |
| SR81J | 8 w/ft, 120 Vac, cut-to-order | - | - | - | |
| SR81J250 | 250' self-dispensing reel | 1 | 20 | 0-13627-06917-6 | |
| SR82J | 8 w/ft, 240 Vac, cut-to-order | - | - | - | |
| SR82J250 | 250' self-dispensing reel | 1 | 20 | 0-13627-06815-2 | |

SR TRACE ACCESSORIES

Specially designed kits ease installation and connection of SR Trace products. SR Trace accessories are UL Listed and CSA Certified.



| CATALOG NUMBER | DESCRIPTION | CTN QTY | CTN WGT | UPC | CERTIFICATIONS |
|----------------|---|---------|---------|-----------------|---|
| SRP | Heat shrink power/end connection kit | 1 | 3 | 0-13627-06947-3 |   |
| SRST | Heat shrink splice and "T" connection kit | 2 | 2 | 0-13627-06959-6 | |
| SRES | Heat shrink end seal kit | 5 | 2 | 0-13627-06968-8 | |
| SRTCS | Fiberglass application tape and caution signs | 1 | 2 | 0-13627-06970-1 | |