

Browse Catalog

- Ballasts
- Compact Fluorescent
- Fluorescent
- Halogen
- High Intensity Discharge (HID)
- Incandescent
- Lampholders/Sockets
- Smart Connected Light
- LED Lamps
- LED Luminaires & Retrofit Kits
- LED Modules
- LED Power Supplies

[Return to Search](#)

[Print Page](#)



Product Number: 62870

Order Abbreviation: RT561A900ST9SC3SMWHE26

General Description: Performance Class Downlight 5/6" can, 900lm, 120V, > 90 CRI, 2700K/3000K/3500K/4000K/5000K, smooth finish, w/E26 adaptor. Wet rated with metal housing. Title 20/24 Compliant and Energy Star Listed

Product Information

Diameter (in)	7.36 in
Diameter (mm)	187.00 mm
Power Factor	≥0.90
Total Harmonic Distortion (THD)	< 20 %
Efficacy (LPW)	80 lm/W
Operating Voltage (V)	120
Power (W)	120
Abbrev. With Packaging Info.	RT561A900ST9SC3SMWHE26 6/CS 1/SKU
Color Temperature/CCT (K)	2700
Ordering Abbreviation	RT561A900ST9SC3SMWHE26
Average Rated Life 1 (hr)	50000
UPC Code	UPC046135628702
Color Rendering Index (CRI)	90
Service Life Rating	50000
Lumens (lm)	900 lm
Wattage (W)	10.00 W
Color Range	2700 K
Energy Star Rated	X
Fixture Warranty	5 years
Housing	Polycarbonate (PC)
Luminaire Finish	White
Luminaire Type	Downlight
Mounting	Recessed
Certification Listing	RoHS,FCC,cULus,CEC
Height (in)	2.756 in