



2021 CORDLESS CATALOG

**M12**  
SYSTEM

**M18**  
SYSTEM

**MX**  
FUEL  
SYSTEM



Nothing but **HEAVY DUTY.**

**M12**  
SYSTEM

**M18**  
SYSTEM

**MX**  
FUEL  
SYSTEM



## THE WORLD LEADER IN CORDLESS INNOVATION

**M12**  
SYSTEM

**M18**  
SYSTEM

**MX  
FUEL**  
SYSTEM

### DEDICATION TO THE TRADES

Since the company began in 1924, Milwaukee Tool has led the industry in both durability and performance. With an unwavering commitment to the trades, MILWAUKEE® continues to lead with a focus on providing innovative, cordless, trade-specific solutions. MILWAUKEE® is dedicated to delivering a steady stream of advanced solutions for the trades that offer increased productivity and unmatched durability.

### GAME-CHANGING SOLUTIONS

At MILWAUKEE®, the phrase “good enough” doesn’t exist in our vocabulary. Our goal is to solve problems in ways that have never been done before. The result: tools and equipment that offer unmatched levels of performance, productivity and durability.



### BUILT ON THE BEST FOUNDATION



#### REDLITHIUM™ BATTERIES

They last longer, think faster and work harder than all other professional LITHIUM-ION batteries. Built to withstand even the harshest environments, REDLITHIUM™ Batteries deliver more work over the life of the battery, no matter what the job.



#### MILWAUKEE® HIGH PERFORMANCE MOTORS

Highly advanced motor technology boosts efficiency, generating more power from a compact power source. That means the ultimate performance, durability and run-time comes in a smaller, lighter package.



#### REDLINK™ INTELLIGENCE

An advanced combination of hardware and software, REDLINK™ Intelligence enables full-circle communication between our batteries and tools, allowing for unmatched levels of performance, protection and productivity.

USER-DRIVEN INNOVATIONS

Instead of making assumptions about what users need, we set out to deliver disruptive innovation by getting out on the jobsite, alongside trade professionals, to understand their challenges – the frustrations, needs, and previous limitations. We set out to completely rethink a solution with new-to-world technology and unparalleled levels of design and engineering. Whether it's bringing cordless power to traditionally corded or gas products and manual activities, or advances to fundamental tools and equipment, we are dedicated to improving workplace productivity and safety.



M18™ FORCE LOGIC™ Press Tool w/ ONE-KEY™  
THE SMALLEST, MOST INTELLIGENT PRESS TOOL

The M18™ FORCE LOGIC™ Press Tool w/ ONE-KEY™ is the industry's smallest, most intelligent press tool. With an in-line design and brushless motor, it achieves more run-time per charge and faster cycle times while being significantly smaller and nearly 20% lighter than the leading competitor. The M18™ FORCE LOGIC™ Press Tool w/ ONE-KEY™ and compatible jaws are designed to work with over 20 unique fitting systems offering 1/2" to 4" capacity. With the addition of ONE-KEY™ compatibility, the press tool automatically logs and wirelessly uploads connection data from every press made with the tool which can be passed onto key stakeholders through customizable reports.



M18 FUEL™ 8-1/4" Table Saw w/ ONE-KEY™

GENERATES  
**15A**  
CORDED  
**POWER**

**24 1/2"**  
RIP  
CAPACITY

RIP UP TO  
**600 LFT**  
PER CHARGE

The world's first 18V table saw, the M18 FUEL™ 8-1/4" Table Saw w/ ONE-KEY™ generates the power of a 15 amp corded saw. With a rip capacity up to 24-1/2" and a vertical capacity up to 2-1/2" to tackle 2x dimensional lumber, this saw boasts the impressive capacity that users have come to expect on a traditional corded table saw. Equipped with ONE-KEY™, users can also easily track, manage, and secure the table saw through the ONE-KEY™ app on their phone.



M12 FUEL™ 3/8" Digital Torque Wrench w/ ONE-KEY™

UP TO  
**50% FASTER**  
INSTALLATION

DELIVERS TORQUE  
**ACCURACY**  
UP TO +/- 2%

FASTER, MORE  
**PRODUCTIVE**  
TORQUE REPORTING

The M12 FUEL™ Digital Torque Wrench w/ ONE-KEY™ is the industry's first torque wrench with a motor, delivering increased productivity, precise torque accuracy, and user demanded reporting functionality. The torque wrench delivers up to 50% faster installation time, replacing the hand tool or two tool installation process and providing accuracy within 2% for torque critical fasteners. This battery powered torque wrench is equipped with MILWAUKEE® ONE-KEY™, giving you the power to record all the fasteners and produce a downloadable report via ONE-KEY™.

M18™ FORCE LOGIC™  
10 Ton Knockout Tool

THE EASIEST  
WAY TO PUNCH

The MILWAUKEE® Knockout System makes every step in the hole making process both faster and easier. The EXACT™ Punches and Dies are set up separate from the tool for extreme ease of use, utilizing a quick-connect alignment system that allows users to snap the tool onto the punches and dies without fighting against its weight and pull the trigger to punch the hole with ease.



M18 FUEL™ 1" D-Handle Extended Anvil  
High Torque Impact Wrench w/ ONE-KEY™

UP TO  
**2,000**  
FT-LBS  
NUT-BUSTING  
TORQUE

UP TO  
**200**  
BOLTS  
PER CHARGE

**ELIMINATES**  
COMPRESSORS &  
HOSES

Our M18 FUEL™ 1" D-Handle Extended Anvil High Torque Impact Wrench w/ ONE-KEY™ is engineered for the performance, run-time, and unmatched portability heavy duty technicians demand. The POWERSTATE™ Brushless Motor delivers up to 2,000 ft-lbs of nut-busting torque and 1,900 ft-lbs of fastening torque, enabling you to complete the most demanding applications. With the run-time for up to 120 lug nut removals and installations on a single HIGH OUTPUT™ HD12.0 Battery, this portable impact wrench provides unmatched performance. Lug Nut Mode, which can be enabled through the ONE-KEY™ app, prevents the over-torque of lug nuts by automatically shutting off the tool, providing more control. The REDLINK PLUS™ Intelligence ensures you achieve maximum performance and protects the High Torque Impact Wrench against overloads, over-heating, and over-discharge.



M18 FUEL™ Pipe Threader w/ ONE-KEY™

**AUTOSTOP™**  
KICKBACK  
CONTROL

**SIDE-GRIP**  
THREAD STARTS

**THREADS  
FASTER**  
THAN CORDED

The M18 FUEL™ Pipe Threader w/ ONE-KEY™ revolutionizes pipe threading. Featuring AUTOSTOP™ kickback control, the tool protects against severe kickback. This, combined with the integrated side-grip for easier thread starts, delivers unrivaled tool control. The world's first cordless pipe threader threads faster than corded alternatives and delivers unmatched productivity.

MX FUEL™ 14" Cut-Off Saw  
INSTANT START,  
ZERO EMISSIONS

**NO**  
GAS  
HEADACHES

**FASTEST**  
CUTS FROM  
START TO FINISH

**6FT**  
IN CONCRETE,  
**72CUTS**  
IN #5 REBAR  
PER CHARGE

The MX FUEL™ 14" Cut-Off Saw delivers instant starts and zero emissions while providing you with no gas headaches, fastest cuts from start to finish, and can cut 6 ft of concrete or 72 cuts in #5 rebar per charge. By providing a 5" cut depth and eliminating the hassle of pull starts, the MX FUEL™ 14" Cut-Off Saw helps you maximize your productivity in every application. The MX FUEL™ REDLITHIUM™ Battery Pack provides instant power with less noise and vibration, and zero emissions for a safer workspace indoors or outdoors.



M18™ FORCE LOGIC™ 10,000 PSI Hydraulic Pump

THE EASIEST WAY  
TO POWER HYDRAULICS

The M18™ FORCE LOGIC™ 10,000 PSI Hydraulic Pump is designed to be fully compatible with all existing 10,000 PSI rated hydraulic hoses and heads. Delivering the easiest set-up, at up to 80% smaller and up to 75 lbs lighter than gas units, the pump can easily be carried by a single person. Delivering 3X the flow rate of competitive cordless pumps; 24-second cycle times and up to 60 presses on a single battery on 1590 ACSR connectors, the pump provides gas-like performance.

# THE WORLD LEADER IN CORDLESS INNOVATION

Milwaukee Tool is committed to driving unrivaled performance and productivity for the professional trades through our groundbreaking developments in cordless technology.

Our leadership in cordless innovation has helped to shape the industry. We were the first to introduce LITHIUM-ION technology to power tools, and have achieved significant leaps forward in advanced motors, the most intelligent electronics, and connected tools. This leadership allows us to continue providing a steady stream of solutions that exceed the demands of the trades.

## REDLITHIUM™ BATTERIES

### CELL TECHNOLOGY

Not all batteries are created equal. In our world-class battery lab, battery cells are engineered to deliver the highest performing packs on the jobsite.

### PACK CONSTRUCTION

Unique patented designs protect every REDLITHIUM™ Battery, safeguarding your investment through drops, weather exposure, and harsh environments.

### ROBUST ELECTRONICS

Innovative communication systems monitor cells, providing temperature and overload protection, while optimizing performance for every tool and battery combination.

**MORE POWER** | **MORE RUN-TIME** | **LONGER BATTERY LIFE**



## POWERSTATE™ BRUSHLESS MOTORS

### HIGH PERFORMANCE

MILWAUKEE's high performance POWERSTATE™ Brushless Motors contain top-grade rare earth magnets and greater copper content, delivering more power and torque for superior application performance.

### PURPOSE BUILT

Each motor is uniquely engineered for the demands of the tool.

Motor-optimization ensures the perfect combination of performance, portability and productivity.



**LONGER MOTOR LIFE** | **MORE POWER** | **MORE RUN-TIME**

## REDLINK™ INTELLIGENCE

### DURABILITY

Best-in-class thermal and overload monitoring protects tools in extreme jobsite conditions.

### PRODUCTIVITY

Advanced communication features, such as DRIVE CONTROL™, allow users to quickly move from light to heavy applications with the touch of a button.


### ONE-KEY™

Get more out of your tools and equipment than ever before with integrated tool tracking, security and customization. ONE-KEY™ combines smarter tools with the industry's only free-to-use inventory management program.



### FULL SYSTEM COMPATIBILITY

With industry-leading intelligence connecting every battery, tool and charger. MILWAUKEE's M18™ System has upheld full forward and backward compatibility for over a decade.



**UNMATCHED PROTECTION** | **OPTIMIZED PERFORMANCE** | **MORE PRODUCTIVITY**

# THE WORLD LEADER IN CORDLESS INNOVATION

**M12**

**PORTABLE PRODUCTIVITY.**  
TRADE FOCUSED. SYSTEM WIDE.

Pages 9 – 36

**M18**

**PERFORMANCE DRIVEN.**  
TRADE FOCUSED. SYSTEM WIDE.

Pages 37 – 82

**MX  
FUEL**

**EQUIPMENT REDEFINED.**  
TRADE FOCUSED. SYSTEM WIDE.

Pages 83 – 94

**ONEKEY**

UNLOCKING THE DIGITAL JOBSITE.



SMART TOOLS  
& EQUIPMENT



SYNC  
WIRELESSLY



ONLINE + MOBILE  
RECORD KEEPING

DIGITAL PLATFORM FOR  
TOOLS & EQUIPMENT



**CUSTOMIZE. TRACK. MANAGE.**



Customize  
by dialing in  
performance



Track your tools  
and equipment  
location from  
anywhere



Lock and  
disable  
remotely



Manage  
your assets  
your way



See pages 18, 22, 41, 43, 45-49, 53, 55, 61 – 64, 67 – 69, 71, 75, 77, 89 – 94  
for ONE-KEY™ Compatible Tools and Equipment



Apple, the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries.  
App Store is a service mark of Apple Inc. Google Play and the Google Play logo are trademarks of Google Inc.

VISIT [ONEKEY.MILWAUKEETOOL.COM](https://onekey.milwaukeetool.com)  
FOR MORE INFORMATION

DOWNLOAD THE  
FREE APP NOW!





**PORTABLE PRODUCTIVITY  
TRADE FOCUSED  
SYSTEM WIDE**

**ALL M12™ TOOLS FIT  
M12™ BATTERIES**  
125+ TOOLS



# DRIVEN TO OUTPERFORM.™

M12 FUEL™ is engineered for the most demanding tradesmen in the world. M12 FUEL™ delivers unrivaled performance in a compact structure and features three MILWAUKEE® exclusive innovations – the POWERSTATE™ Brushless Motor, REDLITHIUM™ Battery Pack and REDLINK PLUS™ Intelligence Hardware and Software – that deliver unmatched power, run-time and durability.

Simply put, M12 FUEL™ is best-in-class, full-circle technology that drives, protects and powers your cordless tools beyond the rest.

# M12 FUEL

**LONGER**  
MOTOR LIFE


**MORE**  
POWER

**MORE**  
RUN-TIME



## 1 POWERSTATE™ BRUSHLESS MOTOR

- MILWAUKEE® Designed and Built Brushless Motor
- Outperforms All Leading Competitors
- Up to 10X Longer Motor Life



## 2 REDLINK PLUS™ INTELLIGENCE

- Most Advanced Electronic System on the Market for Maximum Performance
- Total System Communication with Overload Protection Increases Tool Life
- Built-In Fuel Gauge Displays Remaining Charge



## 3 REDLITHIUM™ CP2.0 & XC4.0 BATTERY PACKS

- Up to 2X More Run-Time
- Up to 20% More Power
- Over 2X More Recharges than Leading Competitors
- Operates Below -18°C / 0°F



# M12

**PORTABLE PRODUCTIVITY  
TRADE FOCUSED  
SYSTEM WIDE**

Peak Torque	350 in-lbs
RPM	0 – 1,700
BPM	0 – 25,500
Chuck Type	1/2" Metal Single Sleeve – Ratcheting Chuck
Length / Weight	6.6" / 2.3 lbs

Peak Torque	275 in-lbs
RPM	0 – 400 / 0 – 1,500
BPM	0 – 22,500
Chuck Type	3/8" Metal Single Sleeve
Length / Weight	7.5" / 2.7 lbs

Peak Torque	350 in-lbs
RPM	0 – 1,700
Chuck Type	1/2" Metal Single Sleeve – Ratcheting Chuck
Length / Weight	6.6" / 2.3 lbs

Max Torque	300 in-lbs
RPM (2-Mode)	0 – 400 / 0 – 1,600
Attachments	3/8" Metal Chuck, 1/4" Hex, Offset and Right Angle
Length / Weight	5.1" / 2.0 lbs

Peak Torque	275 in-lbs
RPM	0 – 400 / 0 – 1,500
Chuck Type	3/8" Metal Single Sleeve
Length / Weight	7.4" / 2.5 lbs

Peak Torque	100 in-lbs
RPM	0 – 800
Clutch Settings	11 Settings plus Drill Mode
Chuck Type	3/8" Single Sleeve
Head Profile	3.8"
Weight	2.4 lbs

<b>Specifications:</b>	
Peak Torque	325 in-lbs
RPM	0 – 450 / 0 – 1,700
Chuck Type	1/4" Hex Quick Change
Length / Weight	6.6" / 2.0 lbs

Peak Torque	275 in-lbs
RPM	0 – 400 / 0 – 1,500
Chuck Type	1/4" Hex Quick Change
Length / Weight	6.8" / 1.8 lbs

Peak Torque	175 in-lbs
RPM	0 – 500
Chuck Type	1/4" Hex Quick Change
Length / Weight	6.5" / 2.0 lbs

<b>Specifications:</b>	
Fastening Torque	1,300 in-lbs
IPM	0 – 4,000
RPM	0 – 3,300
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.1" / 1.8 lbs



**SURGE™**

<b>Specifications:</b>	
Sustained Fastening Torque	450 ft-lbs
IPM	0 – 3,400
RPM	0 – 3,200
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.2" / 2.4 lbs

Fastening Torque	1,000 in-lbs
IPM	0 – 3,300
RPM	0 – 2,500
Chuck Type	1/4" Hex
Length / Weight	6.5" / 2.3 lbs



Fastening Torque	600 in-lbs
IPM	0 – 3,300
RPM	0 – 2,450
Chuck Type	1/4" Hex
Head Profile	1.4"
Weight	2.6 lbs

<b>Specifications:</b>	
Peak Torque	250 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,700
Anvil Type	1/2" Friction Ring
Length / Weight	4.9" / 2.1 lbs

Peak Torque	250 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,700
Anvil Type	3/8" Friction Ring
Length / Weight	4.8" / 2.1 lbs

Peak Torque	100 ft-lbs
IPM	0 – 4,300
RPM	0 – 3,200
Anvil Type	1/4" Friction Ring
Length / Weight	5.1" / 1.8 lbs

Peak Torque	117 ft-lbs
IPM	0 – 3,500
RPM (2-Mode)	0 – 1,200 / 0 – 2,650
Anvil Type	3/8" Friction Ring
Length / Weight	6.5" / 2.4 lbs

Peak Torque	100 ft-lbs
IPM	0 – 3,300
RPM	0 – 2,500
Anvil Type	3/8" Friction Ring
Length / Weight	6.5" / 2.3 lbs

Peak Torque	38 ft-lbs
IPM	0 – 3,800
RPM	0 – 2,500
Anvil Type	1/4" Friction Ring
Length / Weight	6.0" / 2.1 lbs

**Includes:** (2) M12™ REDLITHIUM™ CP1.5 Battery Packs,  
Belt Clip, Charger, Carrying Case

**M12 FUEL**

**1/2" Right Angle Impact Wrench w/ Friction Ring Kit**

2565-22 (2565-20 Tool-Only)

**Specifications:**

Peak Torque	220 ft-lbs
IPM / RPM	0 – 3,600 / 0 – 3,000
Head Profile	2.2"
Length / Weight	14.2" / 3.3 lbs

**Includes:** (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case  
**Related Accessory:**  
**49-16-2564** M12 FUEL™ Right Angle Impact Wrench Rubber Boot



**M12 FUEL**

**1/2" Right Angle Impact Wrench w/ Pin Detent Kit**

2565P-22 (2565P-20 Tool-Only)

**Specifications:**

Peak Torque	220 ft-lbs
IPM / RPM	0 – 3,600 / 0 – 3,000
Head Profile	2.2"
Length / Weight	14.2" / 3.3 lbs

**Includes:** (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case  
**Related Accessory:**  
**49-16-2564** M12 FUEL™ Right Angle Impact Wrench Rubber Boot



**M12 FUEL**

**3/8" Right Angle Impact Wrench w/ Friction Ring Kit**

2564-22 (2564-20 Tool-Only)

**Specifications:**

Peak Torque	220 ft-lbs
IPM / RPM	0 – 3,600 / 0 – 3,000
Head Profile	2.2"
Length / Weight	14.2" / 3.2 lbs

**Includes:** (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case  
**Related Accessory:**  
**49-16-2564** M12 FUEL™ Right Angle Impact Wrench Rubber Boot



**M12 FUEL**

**1/2" Ratchet Kit**

2558-22 (2558-20 Tool-Only)

**Specifications:**

Fastening Torque	60 ft-lbs
RPM	0 – 175
Anvil Type	1/2" Ball Detent
Head Profile	1.1"
Length / Weight	12.5" / 3.1 lbs

**Includes:** (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case  
**Related Accessory:**  
**49-16-2558** M12 FUEL™ 1/2" Ratchet Rubber Boot



**M12 FUEL**

**3/8" Ratchet Kit**

2557-22 (2557-20 Tool-Only)

**Specifications:**

Fastening Torque	55 ft-lbs
RPM	0 – 200
Anvil Type	3/8" Ball Detent
Head Profile	1.1"
Length / Weight	11.8" / 2.8 lbs

**Includes:** (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case  
**Related Accessory:**  
**49-16-2557** M12 FUEL™ 3/8" Ratchet Rubber Boot



**M12 FUEL**

**3/8" Extended Reach Ratchet Kit**

2560-21 (2560-20 Tool-Only)

**Specifications:**

Fastening Torque	55 ft-lbs
RPM	0 – 200
Anvil Type	3/8" Ball Detent
Head Profile	1.1"
Length / Weight	15.1" / 3.1 lbs

**Includes:** (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charger, Contractor Bag  
**Related Accessory:**  
**49-16-2560** M12 FUEL™ 3/8" Extended Reach Ratchet Rubber Boot



**M12 FUEL**

**1/4" Extended Reach Ratchet Kit**

2559-21 (2559-20 Tool-Only)

**Specifications:**

Fastening Torque	40 ft-lbs
RPM	0 – 250
Anvil Type	1/4" Ball Detent
Head Profile	0.76"
Length / Weight	14.4" / 2.3 lbs

**Includes:** (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charger, Contractor Bag  
**Related Accessory:**  
**49-16-2559** M12 FUEL™ 1/4" Extended Reach Ratchet Rubber Boot



**M12 FUEL**

**3/8" High Speed Ratchet Kit**

2567-22 (2567-20 Tool-Only)

**Specifications:**

Fastening Torque	35 ft-lbs
RPM	0 – 450
Anvil Type	3/8" Ball Detent
Head Profile	0.75"
Length / Weight	11.1" / 2.1 lbs

**Includes:** (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case  
**Related Accessories:**  
**49-16-2567** M12 FUEL™ High Speed Ratchet Rubber Boot  
**49-09-2567** 3/8" High Speed Ratchet Tall Shift Knob Assembly



**M12 FUEL**

**1/4" High Speed Ratchet Kit**

2566-22 (2566-20 Tool-Only)

**Specifications:**

Fastening Torque	35 ft-lbs
RPM	0 – 450
Anvil Type	1/4" Ball Detent
Head Profile	0.75"
Length / Weight	11.1" / 2.1 lbs

**Includes:** (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case  
**Related Accessories:**  
**49-16-2567** M12 FUEL™ High Speed Ratchet Rubber Boot  
**49-09-2566** 1/4" High Speed Ratchet Tall Shift Knob Assembly



**M12™ 3/8" Ratchet Kit**

2457-21 (2457-20 Tool-Only)

**Specifications:**

Fastening Torque	35 ft-lbs
RPM	0 – 250
Anvil Type	3/8" Ball Detent
Head Profile	0.8"
Length / Weight	10.8" / 1.9 lbs

**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, 3/8" – 1/4" Adapter, Charger, Soft Carrying Case



**M12™ 1/4" Ratchet Kit**

2456-21 (2456-20 Tool-Only)

**Specifications:**

Fastening Torque	30 ft-lbs
RPM	0 – 250
Anvil Type	1/4" Ball Detent
Head Profile	0.8"
Length / Weight	10.8" / 1.9 lbs

**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger, Soft Carrying Case



**M12™ Rivet Tool Kit**

2550-22 (2550-20 Tool-Only)

**Specifications:**

Pull Force	2,000 lbs
Stroke Length	0.8"
Rivet Sizes	3/32" – 3/16"
Rivet Material	Aluminum, Steel and Stainless Steel
Length / Weight	6.5" (without mandrel collector) / 4.5 lbs

**Includes:** (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, (4) Nose Pieces (3/32", 1/8", 5/32", 3/16"), Belt Hook, Charger, Contractor Bag



**M12 FUEL**

**5/8" SDS Plus Rotary Hammer Kit**

2416-21XC

**Specifications:**

RPM	0 – 900
BPM	0 – 6,200
2-Mode Operation	Rotary Hammer and Rotation Only
Length / Weight	10.0" / 3.9 lbs

**Includes:** (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Charger, Carrying Case  
**Related Accessory:**  
**2509-22** M12™ HAMMERVAC™ Universal Dust Extractor Kit



**M12™ 1/2" SDS Plus Rotary Hammer Kit**

2412-22XC (2412-20 Tool-Only)

**Specifications:**

RPM	0 – 800
BPM	0 – 5,350
2-Mode Operation	Rotary Hammer and Rotation Only
Length / Weight	9.0" / 3.9 lbs

**Includes:** (2) M12™ REDLITHIUM™ XC3.0 Battery Packs, Charger, Carrying Case  
**Related Accessory:**  
**2509-22** M12™ HAMMERVAC™ Universal Dust Extractor Kit



**M12™ HAMMERVAC™ Universal Dust Extractor**

2509-22 (2509-20 Tool-Only)

**Specifications:**

Universal Handle System	Compatible with Major Brands of SDS Plus Rotary Hammers and AC and DC Hammer Drills
Replaceable Certified HEPA Filter	Filters 99.97% of Debris 0.3 Microns and Above
AUTOPULSE™	Filter Cleaning Mechanism achieves Table 1 OSHA Compliance
Self-Powered by M12™ REDLITHIUM™ Battery Pack	No Cords or Hoses for Maximum Portability
3-Mode Switch	Yes (Auto-On and Auto-Off w/ Delay)
Max Diameter	1-1/4"
Max Depth	8"

**Includes:** Small Diameter Nozzle, Large Diameter Nozzle; **2509-22** (2) M12™ REDLITHIUM™ CP2.0 Batteries, Charger, Contractor Bag  
**Related Accessories:**  
**49-90-2302** M12™ HAMMERVAC™ Universal Dust Extractor Nozzle  
**49-90-2343** M12™ HAMMERVAC™ Universal Dust Extractor Dust Box, Filter  
**49-90-2016** 3 pk Fleece Dust Bags





2458-21 (2458-20 Tool-Only)

### Specifications:

Impact Energy	2.2 ft-lbs (3.0 J)
BPM	0 – 2,700
Collet Capacity	6D – 16D
Head Profile	3/4"
Magnetic Tip	Yes
Weight	3.4 lbs

### 2540-21 (2540-20 Tool-Only)

### Specifications:

Nail Diameter	23 Gauge
Nail Size	1/2" – 1-3/8"
Magazine Capacity	120 Nails
Magazine Loading	Side Load
Firing Modes	Sequential
Length / Weight	8.7" / 3.8 lbs

**23** GA  
PIN NAIL

2447-21 (2447-20 Tool-Only)

### Specifications:

Staple Crown Size	3/8" Flat Crown
Staple Length	1/4" – 9/16"
Staple Type	T-50
Length / Weight	7.3" / 3.0 lbs

**T-50**  
STAPLES




### 2486-22 (2486-20 Tool-Only)

### Specifications:

Power Output	0.3 HP
RPM	0 - 21,000
Collet Size	1/4"
Accessory Size	2"
Height / Length	2" / 11"
Weight	1.6 lbs

**Includes:** (2) M12™ REDLITHIUM™ CP2.0 Battery Packs,  
(2) Wrenches, Charger, Carrying Case  
**Related Accessories:**  
**48-07-2486** 1/4" Cut-Off Wheel Arbor  
**48-66-2486** 1/8" Collet & Nut Kit  
**49-94-2000** 2" Metal Cut-Off Wheel



### 2465-22 (2465-20 Tool-Only)

### Specifications:

Torque Range	10 – 100 ft-lbs
RPM	0 – 100
Tool Accuracy	CW: +/-2% of Full Scale / CCW: +/-3% of Full Scale (Range: 20% – 100% of Full Scale)
Ratcheting Angle	4.5°
Anvil Size	3/8" Ball Detent
Measuring Units	ft-lbs, in-lbs, Nm, kg-cm
Length / Weight	23.3" / 5.5 lbs



2438-22X, 2438-22 (2438-20 Tool-Only)

### Specifications:

Polishing RPM	0 – 2,800
Sanding RPM	0 – 8,300
Length / Weight	5.1" / 2.4 lbs

### 2409-22 (2409-20 Tool-Only)

### Specifications:

DRIVE CONTROL™	2-Mode
Collet	7/16" Quick Change
RPM (Buffing)	0 – 2,500
RPM (Drilling)	0 – 1,200
Length / Weight	10.1" / 1.8 lbs

**Includes:** (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery, Quick Change Adapter, Charger, Carrying Case

**Related Accessories:**  
**49-93-2410** 2" Flared Contour Buffing Wheel  
**49-93-2409** 2-1/2" Flared Contour Buffing Wheel



### 2530-21XC (2530-20 Tool-Only)

### Specifications:

RPM	3,600
Bevel Capacity	50°
Cut Capacity	1-5/8" at 90°; 1-1/8" at 45°
Arbor	10 mm
Blade Guards	Aluminum
Weight	6.2 lbs

**M12 FUEL**  
**HACKZALL® One-Handed Reciprocating Saw Kit**

2520-21XC (2520-20 Tool-Only)

**Specifications:**

SPM	0 – 3,000
Stroke Length	5/8"
Keyless Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blades)
Length / Weight	13.3" / 4.1 lbs

**Includes:** (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Charger, Contractor Bag



**M12™ HACKZALL® One-Handed Reciprocating Saw Kit**

2420-22, 2420-21 (2420-20 Tool-Only)

**Specifications:**

SPM	0 – 3,000
Stroke Length	1/2"
Keyless Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blades)
Length / Weight	11.0" / 2.6 lbs

**Includes:** 2420-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs; 2420-21 (1) M12™ REDLITHIUM™ CP1.5 Battery Pack; **All Kits Include:** Charger, Contractor Bag



**M12™ High Performance Jig Saw Kit**

2445-21 (2445-20 Tool-Only)

**Specifications:**

SPM	0 – 2,800
Stroke Length	3/4"
Bevel Capacity	45° (Positive Locks at 90° and 45°)
Blade Clamp	QUIK-LOK™ T-Shank
Length / Weight	8.8" / 4.2 lbs

**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Anti-Splintering Insert, Non-Marring Shoe, Charger, Contractor Bag



**M12 FUEL**  
**Oscillating Multi-Tool Kit**

2526-21XC (2526-20 Tool-Only)

**Specifications:**

Speed Settings	12
OPM	10,000 – 20,000
Oscillation Angle	3.9°
Tool-Free Accessory Change	Yes
LED Light	Yes
Length / Weight	13" / 3.2 lbs

**Includes:** (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (5) Sanding Sheets, (1) Sanding Pad, (1) Wood Cutting Blade, Charger, Contractor Bag



**M12™ Oscillating Multi-Tool Kit**

2426-22, 2426-21 (2426-20 Tool-Only)

**Specifications:**

Speed Settings	12
OPM	5,000 – 20,000
Length / Weight	10.9" / 2.1 lbs

**Includes:** 2426-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs; 2426-21 (1) M12™ REDLITHIUM™ CP1.5 Battery Pack; **All Kits Include:** Wood Cutting Blade, Sanding Pad, (5) Assorted Sanding Sheets, Charger, Contractor Bag



**M12 FUEL**  
**HATCHET™ 6" Pruning Saw Kit**

2527-21 (2527-20 Tool-Only)

**Specifications:**

Bar Length	6"
Chain Gauge	.043"
Chain Pitch	3/8" Low Profile
Chain Speed	5 m/s
Oiler	Automatic
Trigger	Variable Speed
Length / Weight	18.3" / 4.8 lbs

**Includes:** (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, 6" Oregon® Bar & Chain, Scrench, Scabbard, Charger  
**Related Accessories:**  
49-16-2732 6" Saw Chain  
49-16-2733 6" Guide Bar



**M12 FUEL**  
**Compact Band Saw Kit**

2529-21XC (2529-20 Tool-Only)

**Specifications:**

SFPM	0 – 570
Blade Size	30-9/16"
Cut Capacity	2-1/2" x 2-1/2"
LED Light	Yes
Hang Hook	Yes
Reamer Attachment	Yes
Compatibility	

**Includes:** (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, 12/14 TPI Compact Extreme Thin Metal Band Saw Blade, Charger, Contractor Bag  
**Related Accessories:**  
49-90-2029 Compact Band Saw Reamer Attachment  
48-39-0630 30-9/16" 8/10 TPI Compact Extreme Thick Metal Band Saw Blade 3 pk  
48-39-0631 30-9/16" 12/14 TPI Compact Extreme Thick Metal Band Saw Blade 3 pk  
48-39-0635 30-9/16" 8/10 TPI Compact Extreme Thick Metal Band Saw Blade 25 pk  
48-39-0636 30-9/16" 12/14 TPI Compact Extreme Thick Metal Band Saw Blade 25 pk  
48-39-0637 30-9/16" 8/10 TPI Compact Extreme Thick Metal Band Saw Blade 100 bulk  
48-39-0639 30-9/16" 12/14 TPI Compact Extreme Thick Metal Band Saw Blade 100 bulk



**M12™ Sub-Compact Band Saw Kit**

2429-21XC (2429-20 Tool-Only)

**Specifications:**

SFPM	280
Blade Size	27"
Cut Capacity	1-5/8" x 1-5/8"
Length / Weight	11.0" / 6.7 lbs

**Includes:** (1) M12™ REDLITHIUM™ XC3.0 Battery Pack, 18 TPI Sub-Compact Portable Band Saw Blade, Charger, Carrying Case  
**Related Accessories:**  
48-39-0572 18 TPI Sub-Compact Portable Band Saw Blades (3 pk)  
48-39-0711 12/14 TPI Extreme Metal Sub-Compact Portable Band Saw Blades (3 pk)



**Meets OSHA Guarding Requirements. Suitable for One-Handed Use.**



**M12 FUEL**  
**3" Compact Cut-Off Tool Kit**

2522-21XC (2522-20 Tool-Only)

**Specifications:**

Blade Size	3"
RPM	20,000
Arbor Size	3/8"
Cut Depth	0.64"
Blade Rotation	Reversible
Length / Weight	8.9" / 2.4 lbs

**Includes:** (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Dust Accessory Shoe, (3) Accessory Blades (Metal Cut-Off, Carbide Abrasive, Diamond Tile), Blade Wrench, Charger, Contractor Bag



**M12™ Rotary Tool Kit**

2460-21 (2460-20 Tool-Only)

**Specifications:**

Speed Settings	6
RPM	5,000 – 32,000
Collet	1/8", Universal
Length / Weight	9.5" / 1.3 lbs

**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, (5) Cutting Wheels, Mandrel, Wrench, Charger, Soft Carrying Case  
**Related Accessory:**  
49-94-1500 5 Pc Reinforced Cut-Off Wheels



**M12™ 10 oz Caulk & Adhesive Gun Kit**

2441-21 (2441-20 Tool-Only)

**Specifications:**

Force	400 lbs
Inches Per Minute	0 – 29
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	4.1 lbs

**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, 10 oz Carriage, M12™ 10 oz Plunger Rod and Piston Assembly, Charger



**M12™ 20 oz Aluminum Barrel Sausage Style Caulk & Adhesive Gun Kit**

2442-21

**Specifications:**

Force	400 lbs
Inches Per Minute	0 – 29
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	4.9 lbs

**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, 20 oz Aluminum Sausage Style Barrel, M12™ 20 oz Plunger Rod and Piston Assembly, Nozzle, Charger



**M12™ Quart Caulk & Adhesive Gun Kit**

2444-21

**Specifications:**

Force	400 lbs
Inches Per Minute	0 – 29
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	5.5 lbs

**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Quart Carriage, M12™ Quart Plunger Rod and Piston Assembly, Charger



**Caulk Gun Accessories**

Compatible with 2441-21, 2442-21, 2444-21

**31-12-0700** Caulk Gun Nozzle – Black  
**48-08-0900** M12™ 10 oz Caulk and Adhesive Gun Conversion Kit  
**48-08-0905** M12™ 20 oz Aluminum Barrel Sausage Style Caulk and Adhesive Gun Conversion Kit  
**48-08-0910** M12™ Quart Caulk and Adhesive Gun Conversion Kit  
**48-08-1091** 20 oz Aluminum Barrel Kit  
**48-08-1096** 20 oz Clear Barrel Kit

**M12™ Grease Gun Kit**

2446-21XC (2446-20 Tool-Only)

**Specifications:**

Output Pressure	Over 8,000 PSI
Run-Time	Up to 7 Grease Cartridges Per Charge
Grease Capacity	14 oz Cartridge, 16 oz Bulk, 16 oz Suction
Air Bleeder Valve	Yes
Weight	7.2 lbs

**Includes:** (1) M12™ REDLITHIUM™ XC3.0 Battery Pack, 36" Flex Hose with Spring Guard, Grease Coupler, Charger, Carrying Case



**M12™ Soldering Iron Kit**

2488-21 (2488-20 Tool-Only)

**Specifications:**

Max Temperature	750°F
Heat Output	90 Watts
Heat-Up Time	18 Seconds
Heat Indicator	Yes
Interchangeable Tips	Chisel and Point
Length / Weight	11.6" / 0.9 lbs

**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Chisel Tip, Pointed Tip, Charger, Carrying Case



**M12™ Cable Stapler Kit**

2448-21 (2448-20 Tool-Only)

**Specifications:**

Firing Mode	Sequential
Magazine Capacity	45
Magazine Loading	Front Load
Run-Time	1,200 Staplers per Charge on M12™ CP2.0 Battery
Length / Weight	6.5" / 5.0 lbs

**Includes:** (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charger, Carrying Case  
**Related Accessory:**  
MNM1-600 1" Insulated Cable Staples



### M12™ Cable Stripper Kit

2435CU-21S, 2435AL-21, 2435X-21 (2435-20 Tool-Only)

#### Specifications:

Variable Speed Trigger	Yes
Tool Free Depth Gauge	Yes
Compatible Bushing Types	Industry Standard Quick-Change
Dimensions (L x W x H)	8.6" x 2.8" x 11.5"
Weight	3.6 lbs



**Includes:** 2435CU-21S 1/0 AWG – 750 MCM Cu THHN / XHHW Bushings; 2435AL-21 1/0 AWG – 750 MCM Al THHN / XHHW Bushings; 2435X-21 1/0 AWG – 500 MCM Cu RHW / RHH / USE Bushings; **All Kits Include:** (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Carrying Case

Reference Available Bushings on Pg. 66



### M12™ 600 MCM Cable Cutter Kit

2472-21XC (2472-20 Tool-Only)

#### Specifications:

Cut Capacity	600 MCM Copper, 750 MCM Aluminum, 1-3/16" Communication Cable
Jaw Opening	1-7/16"
Two-Speed	Yes
Length / Weight	10.5" / 6.7 lbs



**Includes:** (1) M12™ REDLITHIUM™ XC3.0 Battery Pack, Charger, Carrying Case  
**Related Accessory:** 48-44-0410 M12™ 600 MCM Cable Cutter Blade

### M12™ Plastic Pipe Shear Kit

2470-21 (2470-20 Tool-Only)

#### Specifications:

Cut Capacity	Up to 2" Schedule 80 PVC
Torque	1,900 in-lbs
Blade	3 mm Reinforced Stainless Steel
Length / Weight	14.4" / 4.4 lbs



**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger, Carrying Case  
**Related Accessory:** 48-44-0405 M12™ Plastic Pipe Shear Blade

### M12™ Copper Tubing Cutter Kit

2471-22, 2471-21 (2471-20 Tool-Only)

#### Specifications:

Cut Capacity	3/8" – 1" (1/2" – 1-1/8" O.D.)
Tubing Type	M, L and K Copper
RPM	500
Length / Weight	14.0" / 3.2 lbs



**Includes:** 2471-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs; 2471-21 (1) M12™ REDLITHIUM™ CP1.5 Battery Pack; **All Kits Include:** Charger, Carrying Case  
**Related Accessory:** 48-38-0010 Copper Cutter Wheel (2 pk)



### M12 FUEL ProPEX® Expander Kit w/ 1/2" - 1" RAPID SEAL™ ProPEX® Expander Heads

2532-22 (2532-20 Tool-Only)

#### Specifications:

Capacity	3/8" – 1"
Auto Rotate	Built-In
Trigger	Dual Actuating
Dimensions (L x W x H)	7.1" x 3.7" x 12.8"
Weight	4.5 lbs



**Includes:** (3) ProPEX® Expander Heads w/ RAPID SEAL™ (1/2", 3/4", 1"), ProPEX® Expander Cone Grease, Carrying Case; 2532-22 (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger  
**Related Accessories:** 49-16-2414 1/2" ProPEX® Expander Head w/ RAPID SEAL™ 49-16-2415 5/8" ProPEX® Expander Head w/ RAPID SEAL™ 49-16-2416 3/4" ProPEX® Expander Head w/ RAPID SEAL™ 49-16-2418 1" ProPEX® Expander Head w/ RAPID SEAL™

### M12™ ProPEX® Expansion Tool Kit

2432-22 (2432-20 Tool-Only)

#### Specifications:

Capacity	3/8" – 1"
Auto-Rotate	Built-In
Head Compatibility	3/8" – 1" M12™ / Uponor
Dimensions (L x W x H)	7.1" x 3.7" x 12.8"
Weight	5.0 lbs



**Includes:** (3) ProPEX® Expansion Heads (1/2", 3/4", 1"), ProPEX® Tool Cone Grease, Carrying Case; 2432-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Charger  
**Related Accessories:** 49-08-2400 ProPEX® Expander Cone Grease 49-16-2403 3/8" ProPEX® Expansion Head 49-16-2404 1/2" ProPEX® Expansion Head 49-16-2405 5/8" ProPEX® Expansion Head 49-16-2406 3/4" ProPEX® Expansion Head 49-16-2408 1" ProPEX® Expansion Head

### M12™ PEX Expansion Tool Kit

2474-22

#### Specifications:

Capacity	3/8" – 1"
Auto-Rotate	Built-In
Head Compatibility	3/8" – 1" M12™
Dimensions (L x W x H)	7.1" x 3.7" x 12.8"
Weight	5.0 lbs



**Includes:** (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, (3) PEX Expansion Heads (1/2", 3/4", 1"), PEX Tool Cone Grease, Charger, Carrying Case  
**Related Accessories:** 49-16-2424 1/2" PEX Expander Head 49-16-2426 3/4" PEX Expander Head 49-16-2428 1" PEX Expander Head 49-08-2402 PEX Tool Grease



### M12™ TRAPSSNAKE™ 6' Toilet Auger Kit

2576-21 (2576-20 Tool-Only)

#### Specifications:

RPM	0 – 500
Cable Lock	Yes
Cable Size	6' x 1/2"
Cable Head	Retriever Bulb
Replacement Cables	Available
Weight	9.0 lbs



**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Cable, Charger  
**Related Accessories:** 48-53-2576 TRAPSSNAKE™ 6' Toilet Auger Replacement Cable 48-22-2576 TRAPSSNAKE™ Toilet Auger Case

### M12™ TRAPSSNAKE™ 4' Urinal Auger Kit

2574-21 (2574-20 Tool-Only)

#### Specifications:

RPM	0 – 500
Cable Lock	Yes
Cable Size	4' x 3/8"
Cable Head	Bulb
Replacement Cables	Available
Weight	6.4 lbs



**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Cable, Charger  
**Related Accessories:** 48-53-2577 TRAPSSNAKE™ 4' Urinal Auger Replacement Cable 48-22-2577 TRAPSSNAKE™ Urinal Auger Case

### M12™ TRAPSSNAKE™ Driver Upgrade Kit

2575-21

#### Specifications:

RPM	500
Height	11"
Weight	4.5 lbs



**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger  
**Related Accessories:** 49-16-2576 TRAPSSNAKE™ 6' Toilet Auger 49-16-2574 TRAPSSNAKE™ 4' Urinal Auger 49-16-2573 TRAPSSNAKE™ 25' Auger w/ CABLE DRIVE™

### M12™ Pipeline Locator Kit

2580-21

#### Specifications:

Sonde Frequencies	512Hz, 640Hz, 8,192kHz, 33kHz, 83kHz
Line Trace	33kHz, 83kHz
Power Frequency	50Hz, 60Hz
Radio Frequency	10kHz – 22.7kHz Bandwidth
Display Type	4.3" Color LCD Display
Water & Dust Rating	IP65



**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger, Carrying Case



### M12™ Drain Snake Kit

2571-21 (2571-20 Tool-Only)

#### Specifications:

Max Drain Line Capacity	1-1/4" – 2-1/2", Up to 25'
Drum Capacity	1/4" x 25', Best for 1-1/4" – 2" drain lines; 5/16" x 25', Best for 1-1/4" – 2-1/2" drain lines
Variable Speed Spin	0 – 500 RPM
LED Light	Yes
Weight (without cable)	6.5 lbs



**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, 5/16" x 25' Inner Core Bulb Head Cable with Inner Drum, Charger, 5 Gallon Storage Bucket  
**Related Accessories:** 48-53-2561 5/16" x 25' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating 48-53-2562 5/16" x 25' Inner Core Drop Head Cable w/ RUST GUARD™ Plating 48-53-2563 1/4" x 25' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating 48-53-2564 1/4" x 25' Inner Core Drop Head Cable w/ RUST GUARD™ Plating

### M12™ AIRSNAKE™ Drain Cleaning Air Gun Kit

2572B-21, (2572B-20 Tool-Only)

#### Specifications:

Max Drain Line Capacity	1" – 4", Up to 35'
Automatic Pressure Loading	Yes
Variable Pressure	0 – 50 PSI
Variable Pressure Dial	Yes
LED Light	Yes
Length / Weight	20.8" / 7.1 lbs



**Includes:** 2572B-21 (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charger; **All Kits Include:** 2572B-20: 1" – 2" Drain Plug, 2" – 3" Drain Plug, 3" – 4" Drain Plug, Drain Shroud Attachment, Toilet Seal Attachment, 10" Extension, (3) Straight Connectors, 15° Offset Connector, Carrying Case



### M12™ FORCE LOGIC™ Press Tool Kit

2473-22 (2473-20 No Jaw Kit)

#### Specifications:

Capacity	1/2" – 1-1/2" Varies by Material
Calibration Interval	32,000 Cycles (LED Indicator)
Approximate Cycle Time	5 Seconds
Press Force	5,400 lbs
Length / Weight	12.8" / 3.8 lbs

**Includes:** 2473-22 (3) Jaws (1/2", 3/4", 1");  
2473-20 (No Jaws Included);  
**All Kits Include:** (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Charger, Carrying Case

#### Related Accessories:

49-16-2450 1/2" CTS-V Press Jaw  
49-16-2451 3/4" CTS-V Press Jaw  
49-16-2452 1" CTS-V Press Jaw  
49-16-2453 1-1/4" CTS-V Press Jaw  
49-16-2450B 1/2" IPS-P Press Jaw  
49-16-2451B 3/4" IPS-P Press Jaw  
49-16-2452B 1" IPS-P Press Jaw  
49-16-2451C 1/2" PEX-Crimp Press Jaw  
49-16-2453C 3/4" PEX-Crimp Press Jaw  
49-16-2454C 1" PEX-Crimp Press Jaw  
49-16-2455C 1-1/4" PEX-Crimp Press Jaw  
49-16-2456C 1-1/2" PEX-Crimp Press Jaw  
49-16-2496B 1/2"-1" IPS-P Press Jaw Kit



### M12™ M-SPECTOR FLEX™ 9 ft Inspection Camera Cable Kit

2316-21

#### Specifications:

Screen Size	3.5" High-Resolution LCD
Camera Resolution	640 x 480
Camera Head Diameter	12.5 mm (0.49")
Cable Length	9 ft
Wireless Distance	Up to 15 ft

**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, SD Card, USB Cable, Charger, Carrying Case



### M12™ M-SPECTOR FLEX™ 3 ft Inspection Camera Cable Kit

2315-21

#### Specifications:

Screen Size	3.5" High-Resolution LCD
Camera Resolution	640 x 480
Camera Head Diameter	12.5 mm (0.49")
Cable Length	3 ft
Wireless Distance	Up to 15 ft

**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, SD Card, USB Cable, Charger, Carrying Case



### M-SPECTOR FLEX™ Inspection Camera Accessories

Compatible with 2317-21, 2316-21, 2315-21

48-53-0155 M-SPECTOR FLEX™ 3 ft Inspection Camera Cable w/ PIVOTVIEW™

48-53-0151 M-SPECTOR FLEX™ 9 ft Inspection Camera Cable

48-53-0150 M-SPECTOR FLEX™ 3 ft Inspection Camera Cable



### M12™ M-SPECTOR 360™ Rotating Inspection Scope Kit

2313-21 (2313-20 Tool-Only)

#### Specifications:

Screen Size	2.7" High-Resolution LCD
Display Resolution	320 x 240
Camera Head Diameter	9 mm (0.35")
Cable Length	3 ft
LED Brightness	4 LEDs, 5 Settings

**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Hook, Magnet, Mirror Attachments, Charger, Contractor Bag



### M12™ M-SPECTOR 360™ 9 ft Rotating Inspection Scope Kit

2314-21

#### Specifications:

Screen Size	2.7" High-Resolution LCD
Display Resolution	320 x 240
Camera Head Diameter	9 mm (0.35")
Cable Length	9 ft
LED Brightness	4 LEDs, 5 Settings

**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Hook, Magnet, Mirror Attachments, Pipe Guide, Charger, Contractor Bag



### M-SPECTOR 360™ Rotating Inspection Scope Accessories

Compatible with 2313-21, 2314-21

48-53-0112 3 Pc Accessory (Includes Hook, Magnet, Mirror Attachments)

48-53-0113 Pipe Guide Accessory



### M12™ 12:1 Infrared TEMP-GUN™

2278-20 Tool-Only

#### Specifications:

Distance-to-Spot Ratio	12:1
Temperature Range	-22°F – 1,022°F (-30°C – 550°C)
Basic Accuracy	+/-1.8%
Max/Min/Avg/Dif	Yes
High/Low Alerts	Yes
Emissivity	Fixed, .95
Drop Test	6 ft

Battery and Charger Sold Separately



### M12™ Green Laser Kit - 360° 3-Plane

3632-21

#### Specifications:

Range with Detector	165 ft
Working Range	125 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m

**Includes:** (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Target, Charger, Carrying Case



### M12™ Green Laser Kit - Cross Line & Plumb Points

3622-21 (3622-20 Tool-Only)

#### Specifications:

Range with Detector	165 ft
Working Range	125 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m

**Includes:** (1) M12™ REDLITHIUM™ CP3.0 Battery Pack, Target, Charger, Carrying Case



### USB Rechargeable Green Laser - Cross Line & Plumb Points

3522-21

#### Specifications:

Ranger with Detector	165 ft
Working Range	100 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m

**Includes:** (1) REDLITHIUM™ USB 3.0 Battery, Heavy Duty Cord and Wall Plug, Riser, Carrying Case



### USB Rechargeable Green Laser - Cross Line

3521-21

#### Specifications:

Ranger with Detector	165 ft
Working Range	100 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m

**Includes:** (1) REDLITHIUM™ USB 3.0 Battery, Heavy Duty Cord and Wall Plug, Carrying Case



### USB Rechargeable Green Laser - 3-Point

3510-21

#### Specifications:

Working Range	150 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m

**Includes:** (1) REDLITHIUM™ USB 3.0 Battery, Heavy Duty Cord and Wall Plug, Carrying Case



### Laser Accessories

Compatible with 3632-21, 3622-21, 3522-21, 3521-21, 3510-21

48-35-1211 165' Laser Line Detector

48-35-1411 72" Laser Tripod

48-35-1311 360° Laser Bracket

48-35-1111 Responsive Laser Alignment Target

48-35-1313 Laser Track Clip


### M12™ ROCKET™ Dual Power Tower Light

2132-20 Tool-Only

#### Specifications:

Lumens	1,400 / 700
Modes	High, Low
Height	30.5" Collapsed, 5' 8" Fully Extended
Weight	6.7 lbs

Battery and Charger Sold Separately



### M12™ ROVER™ Service & Repair Flood Light w/ USB Charging

2367-20 Tool-Only

#### Specifications:

Lumens	700 / 250
Modes	High, Low
Run-Time (w/ M12™ XC4.0 Battery)	8 hr / 24 hr
Water & Dust Rating	IP54
USB Charger	2.1A USB Charging Port for External Devices

Battery and Charger Sold Separately



### M12™ Metal Flashlight Kit

2355-21 (2355-20 Tool-Only)

#### Specifications:

Lumens	800 / 325 / 800
Modes	High, Medium, Strobe
Beam Distance	375 yd / 343 m
Beam Focus	Slide, Spot/Flood
Water & Dust Rating	IP54
Structure	6000 Series Aluminum, Type II Anodize Finish
Length / Weight	9.0" / 1.2 lbs

**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Lanyard, Charger



### M12™ Spot Light

2353-20 Tool-Only

#### Specifications:

Lumens	750 / 400 / 750
Modes	High, Low, Strobe
Beam Distance	700 yd / 640 m
Water & Dust Rating	IP54
Length / Weight	6.1" / 1.4 lbs

Battery and Charger Sold Separately

**Includes:** Lanyard



### M12™ Trouble Light w/ USB Charging

2362-20 Tool-Only

#### Specifications:

Lumens	400 / 200 / 40 / 400
Modes	High, Medium, Low, Strobe
Run-Time	Up to 67 Hours
Beam Pattern	Adjustable Task – Area
Water & Dust Rating	IPX4
Hands-Free	2 Hooks for Hanging
USB Charger	2.1A USB Charging Port for External Devices
Length / Weight	10.5" / 1.0 lb

Battery and Charger Sold Separately



### M12™ ROVER™ Mounting Flood Light

2364-20 Tool-Only

#### Specifications:

Lumens	1,000 / 400 / 200
Modes	High, Medium, Low
Hands-Free	Integrated Magnet, Spring Loaded Clamp
Water & Dust Rating	IP54
Length / Weight	7.5" / 2.2 lbs

Battery and Charger Sold Separately



### M12™ Underhood Light Kit

2125-21XC (2125-20 Tool-Only)

#### Specifications:

Lumens	1,350 / 600
Modes	High, Low
Hooks	FINISHGUARD™ to Resist Wear & Provide Lasting Protection
Length / Weight	48" Collapsed, 78" Fully Extended / 2.2 lbs

**Includes:** (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Charger



### M12™ Underbody Light

2126-21 (2126-20 Tool-Only)

#### Specifications:

Lumens	1,200 / 800 / 600
Modes	High, Medium, Low
Water & Dust Rating	IP54
Mounting	Magnetic Base

Battery and Charger Sold Separately

**Includes:** 2126-21 M12™ Underbody Light, (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Charger; 2126-20 M12™ Underbody Light



### M12™ Stick Light

2351-20 Tool-Only

#### Specifications:

Lumens	220
Hands-Free	Multi-Position Stainless Steel Hook
Water & Dust Rating	IP54
Length / Weight	9.3" / 0.6 lbs

Battery and Charger Sold Separately

**Related Accessory:**  
49-24-2351 M12™ Stick Light Magnet  
Holds light to metal surfaces for hands-free use



### M12™ Work Light

49-24-0146 Tool-Only

#### Specifications:

Lumens	100
Hands-Free	Integrated Magnet
Head Rotation	90°

Battery and Charger Sold Separately



### M12™ Heated TOUGHSHELL™ Jacket Kit

Black 204B-21 (S – 3X)\*, 204B-20 Jacket-Only

Gray 204G-21 (S – 3X)\*, 204G-20 Jacket-Only

Red 204R-21 (S – 3X)\*, 204R-20 Jacket-Only

Blue 204BL-21 (S – 3X)\*, 204BL-20 Jacket-Only

#### Specifications:

Heat Zones	3 (Chest, Back, Pockets)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 12 Hours
Battery Pocket	Battery Pass-Thru, Front or Back Pocket
Outer Material	TOUGHSHELL™ Stretch Polyester
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes

**Includes:** (1) M12™ REDLITHIUM™ CP3.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source



### M12™ Women's Heated SOFTSHELL Jacket Kit

Black 232B-21 (S – 2X)\*, 232B-20 Jacket-Only

#### Specifications:

Heat Zones	3 (Back, Collar, Pockets)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 8 Hours
Outer Material	Polyester SOFTSHELL
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes

**Includes:** (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source



### M12™ Heated QUIETSELL Jacket Kit

Camo 222C-21 (S – 3X)\*, 222C-20 Jacket-Only

#### Specifications:

Heat Zones	3 (Chest, Back, Pockets)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 8 Hours
Outer Material	QUIETSELL™ Stretch Polyester
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes

Realtree EDGE © 2021 of Jordan Outdoor Enterprises, Ltd., all rights reserved

**Includes:** (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source



### M12™ Heated AXIS™ Layering System w/ HYDROBREAK™ Rain Shell Kit

Black/Gray 203RN-21 (S – 3X)\*

#### Specifications:

Heat Zones	3 (Chest, Back, Shoulders)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 8 Hours
Outer Material	Polyurethane Laminate / Ripstop Polyester
Waterproof	10K mm
Washer / Dryer Safe	Yes

**Includes:** HYDROBREAK™ Rain Shell, M12™ Heated AXIS™ Jacket, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source



### M12™ Heated AXIS™ Layering System w/ GRIDIRON™ Work Shell Kit

Black 255B-21 (S – 3X)\*

#### Specifications:

Heat Zones	3 (Chest, Back, Shoulders)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 8 Hours
Outer Material	GRIDIRON™ Ripstop Polyester
Insulation	60G Body / 40G Sleeve
Washer / Dryer Safe	Yes

**Includes:** GRIDIRON™ Work Shell, M12™ Heated AXIS™ Jacket, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source



\*MODEL NUMBER EXAMPLE

202B-21XL = M12™ Heated TOUGHSHELL™ Black Jacket Kit in Extra Large








# PERSONAL LIGHTING

MILWAUKEE® delivers the industry's first line of trade focused, high performance personal lights designed to ADAPT, PERFORM AND SURVIVE. Built to withstand the toughest conditions on and off the jobsite, MILWAUKEE® lights combine the best cordless battery and LED technology delivering convenient, portable solutions that increase productivity and safety.



**REDLITHIUM™ USB**

**RECHARGEABLE**

**ALL DAY  
RUN-TIME\***

**MORE  
RECHARGES**

**3X FASTER  
CHARGE TIME\*\***

MILWAUKEE® delivers the industry's first line of trade focused, high performance personal lights designed to get maximum performance and user driven innovation with REDLITHIUM™ USB Personal Lights. REDLITHIUM™ USB lights combine the best in cordless battery and LED technology to deliver High Output with ALL DAY RUN-TIME, More Recharges and 3X Faster Charge Time. Get more from REDLITHIUM™ USB with one battery that powers multiple solutions.

**POWERED BY**



\*Dependent on mode selection and based on 10 hour work day  
\*\*Compared to 0.5a charge rate



**RECHARGEABLE**

## ALL NEW SUB-COMPACT RECHARGEABLE LIGHTS

Where work makes size critical, MILWAUKEE® Rechargeable Personal Lights leverage a built-in battery and USB charging to deliver high performance output and rechargeable capabilities in the most compact personal lights.



**BUILT-IN  
BATTERY**



# PERSONAL LIGHTING **M12**

## REDLITHIUM™ USB Hard Hat Headlamp Kit 2111-21

Lumens	475 / 300 / 300, 150, 25
Modes	Spot/Flood, Spot – High, Flood – High/Medium/Low
Water & Dust Rating	IP54
Powered By	REDLITHIUM™ USB

**Includes:** (1) REDLITHIUM™ USB Battery, 2 ft Heavy Duty USB Cord, Hard Hat Clips



## REDLITHIUM™ USB 1,100L Twist Focus Flashlight 2161-21

Lumens	1,100 / 600 / 100
Modes	High, Medium, Low
Spot Beam Distance	175 m
Beam Focus	Twist Focus, Spot/Flood
Water & Dust Rating	IP54
Powered By	REDLITHIUM™ USB

**Includes:** (1) REDLITHIUM™ USB 3.0 Battery, 2 ft Heavy Duty USB Cord



## REDLITHIUM™ USB Low-Profile Headlamp Kit 2115-21

Lumens	600 / 350 / 125 / 25
Modes	High, Medium, Low, Eco
Battery Position	Rear
Water & Dust Rating	IP54
Powered By	REDLITHIUM™ USB

**Includes:** (1) REDLITHIUM™ USB Battery, 2 ft Heavy Duty USB Cord, (4) Hard Hat Clips



## REDLITHIUM™ USB ROVER™ Magnetic Flood Light Kit 2112-21

Lumens	445 / 100
Modes	High, Low
Hands-Free	Dual Magnets
Water & Dust Rating	IP54
Height	6.0"
Powered By	REDLITHIUM™ USB

**Includes:** (1) REDLITHIUM™ USB Battery, 2 ft Heavy Duty USB Cord



## REDLITHIUM™ USB BEACON™ Hard Hat Light Kit 2116-21

Lumens	600 / 400, 200, 25 / 400
Modes	Spot/Flood, Flood – High/Medium/Low, Spot – High
BEACON™ Mode	Steady & Blinking
Spot Beam Distance	125 m
Water & Dust Rating	IP54
Powered By	REDLITHIUM™ USB

**Includes:** (1) REDLITHIUM™ USB Battery, 2 ft Heavy Duty USB Cord, (2) Hard Hat Clips



## REDLITHIUM™ USB Pivoting Flashlight Kit 2113-21

Lumens	500 / 400 / 100
Modes	Spot – High, Flood – High, Flood – Low
Spot Beam Distance	155 m
Pivoting Head	110°
Water & Dust Rating	IP54
Height	6.3"
Powered By	REDLITHIUM™ USB

**Includes:** (1) REDLITHIUM™ USB Battery, 2 ft Heavy Duty USB Cord



REDLITHIUM™ USB ROVER™  
Pivoting Flood Light Kit

Lumens	550 / 250 / 100
Modes	High, Medium, Low
Pivoting Head	210°
Water & Dust Rating	IP54
Height	4.4"
Powered By	REDLITHIUM™ USB



**Includes:** (1) REDLITHIUM™ USB Battery, 2 ft Heavy Duty USB Cord



REDLITHIUM™ USB Portable  
Power Source and Charger Kit

Cell Chemistry	LITHIUM-ION
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes
USB Charging Port	2.1A USB Charging Port for External Devices
Height	3.9"

**Includes:** (1) REDLITHIUM™ USB Battery, REDLITHIUM™ USB Portable, 2 ft Heavy Duty USB Cord, Power Source and Charger



Rechargeable 450L Magnetic  
Headlamp and Task Light

Lumens	500 / 100 / 10
Modes	High, Medium, Low
Water & Dust Rating	IP67
Mounting	Detachable Magnetic Light Head
Powered By	Built-In-Battery

**Includes:** USB Charging Cable



MILWAUKEE® Spot/Flood  
Headlamp

Lumens	450 / 350, 150, 25 / 350
Modes	Spot/Flood, Flood – High/Medium/Low, Spot
Spot Beam Distance	100 m
Water & Dust Rating	IP54
Powered By	(3) AAA

**Includes:** (4) Hard Hat Clips, (3) AAA Batteries



REDLITHIUM™ USB  
Utility Hot Stick Light Kit

Lumens	350, 100
Modes	Flood – High/Low
kV Rating	100kV
Water & Dust Rating	IP67
Height / Length	0.5" / 7.4"
Powered By	REDLITHIUM™ USB

**Includes:** (2) REDLITHIUM™ USB Batteries, 2 ft Heavy Duty USB Cord, REDLITHIUM™ USB Charger & Portable Power Source, 12V DC Vehicle Plug, 2.1A Wall Plug



Rechargeable 250L Penlight w/ Laser  
2010R

Lumens	250 / 50
Modes	High, Low
Water & Dust Rating	IP54
Laser	Integrated Laser Pointer
Powered By	Built-In-Battery

**Includes:** USB Charging Cable



MILWAUKEE® Penlight  
2105

Lumens	100
Water & Dust Rating	IP67
Height	5.4"
Powered By	(2) AAA

**Includes:** (2) AAA Batteries



MILWAUKEE® Headlamp  
2103

Lumens	350 / 150 / 25
Modes	High, Medium, Low
Impact Rating	2 m
Water & Dust Rating	IP54
Powered By	(3) AAA

**Includes:** (4) Hard Hat Clips, (3) AAA Batteries



ROVER™ Magnetic Flood Light  
2108

Lumens	300 / 100
Modes	High, Low
Water & Dust Rating	IP54
Height	4.8"
Powered By	(2) AA

**Includes:** (2) AA Batteries



REDLITHIUM™ USB Portable  
Power Source and Charger

Cell Chemistry	LITHIUM-ION
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes
USB Charging Port	2.1A USB Charging Port for External Devices
Height	3.9"

**Includes:** REDLITHIUM™ USB Portable, 2 ft Heavy Duty USB Cord, Power Source and Charger



MILWAUKEE® C I, II, III / D 1 Intrinsically  
Safe Spot/Flood Headlamp

Lumens	310 / 155 / 235 / 155 / 25
Modes	Spot/Flood Hybrid, Spot High, Flood High, Flood Medium, Flood Low
Intrinsically Safe Rating	Classes I, II, III / Division 1 Groups A – G
Impact Rating	9 ft
Water & Dust Rating	IP64
Powered By	(3) AAA

**Includes:** Rubber Strap, Nylon Strap, DUAL LOCK™ Adhesive, (4) Hard Hat Clips, Hex Wrench, (3) AAA Batteries



M12™  
COMBO KITS

	2 PIECE KITS							4 PIECE KIT
	2459-22	2494-22	2497-22	2577-21	2582-22	2596-22	2598-22	2498-24
Kit Tool Total	2	2	2	2	2	2	2	4
M12 FUEL™ Low Speed Tire Buffer	■							
M12 FUEL™ 1/2" Hammer Drill/Driver					■		■	
M12™ 3/8" Hammer Drill/Driver			■					
M12 FUEL™ 1/2" Drill/Driver	■					■		
M12™ 3/8" Drill/Driver		■						■
M12 FUEL™ 1/4" Hex Impact Driver						■	■	
M12™ 1/4" Hex Impact Driver		■	■					■
M12 FUEL™ SURGE™ 1/4" Hex Hydraulic Driver					■			
M12™ HACKZALL® Reciprocating Saw								■
M12™ TRAPSSNAKE™ 6' Toilet Auger				■				
TRAPSSNAKE™ 4' Urinal Auger Extension				■				
M12™ Work Light								■
Also Includes								
M12™ Charger	■	■	■	■	■	■	■	■
M12™ REDLITHIUM™ CP1.5 Battery Pack		2	2	1				2
M12™ REDLITHIUM™ CP2.0 Battery Pack	1				1	1	1	
M12™ REDLITHIUM™ XC4.0 Battery Pack	1				1	1	1	
Carrying Case	■							
Contractor Bag		■	■		■	■	■	■

M18 M12

RAPID CHARGER

- Charges All M18™ and M12™ Batteries
- Charges Batteries Sequentially (First In, First Charged)

CHARGES  
PACKS  
UP TO  
40% FASTER



M12™ REDLITHIUM™  
CP3.0/XC6.0

- Up to 3X More Run-Time
- Up to 20% More Power
- Over 2X More Life




M12



M12

PORTABLE PRODUCTIVITY  
TRADE FOCUSED  
SYSTEM WIDE





**PERFORMANCE DRIVEN  
TRADE FOCUSED  
SYSTEM WIDE**

**ALL M18™ TOOLS FIT  
M18™ BATTERIES**  
200+ TOOLS



## DRIVEN TO OUTPERFORM.™

For the first time in power tool history, M18 FUEL™ products are delivering game-changing corded performance without the cord. The motors on MILWAUKEE® M18 FUEL™ tools are more powerful and energy efficient – outliving any other brand. To add to the revolutionary technology, M18 FUEL™ possesses the smartest electronics found in any power tool. REDLINK PLUS™ electronics manage an array of power requirements across 200+ M18™ tools using one common battery. MILWAUKEE® built, the M18™ Battery delivers cleaner, more consistent power, lasts longer and delivers more run-time in the harshest jobsite conditions.

# M18 FUEL

**LONGER**  
MOTOR LIFE

**MORE**  
POWER

**MORE**  
RUN-TIME

NOW AVAILABLE

HIGH OUTPUT™

**50%** MORE POWER  
vs REDLITHIUM™ HD

**& RUNS COOLER**



REDLITHIUM™  
HIGH OUTPUT™ HD12.0



## 1 POWERSTATE™ BRUSHLESS MOTOR

This best-in-class brushless motor works harder and lives longer than all leading competitors.

- MILWAUKEE® Designed and Built Brushless Motor
- Outperforms All Leading Competitors
- Longer Motor Life



## 2 REDLINK PLUS™ INTELLIGENCE

The most advanced system of hardware and software in cordless power tool electronics today.

- Most Advanced Electronic System on the Market for Maximum Performance
- Total System Communication with Overload Protection Increases Tool Life



## 3 REDLITHIUM™ XC5.0 BATTERY PACK

Compatible with the entire M18™ System, it delivers more run-time, power and recharges than the competition.

- Most Durable Pack on the Market
- Over 2X More Recharges than Leading Competitor
- Fuel Gauge Displays Remaining Charge
- Operates Below -18°C / 0°F



M18

PERFORMANCE DRIVEN  
TRADE FOCUSED  
SYSTEM WIDE



**REDLITHIUM**  
HIGH OUTPUT XC6.0



**RED LITHIUM**  
HIGH OUTPUT HD120

**REDLITHIUM™**  
**HIGH OUTPUT™ XC60**

**REDLITHIUM™**  
**HIGH OUTPUT XC8.0**

**REDLITHIUM™**  
**HIGH OUTPUT™ XC8.0**

**REDLITHIUM**  
HIGH OUTPUT XC8.0

**REDLITHIUM™**  
**HIGH OUTPUT™ XC6.0**



**REDLITHIUM™**  
**HIGH OUTPUT™ XC6.0**

**REDLITHIUM™**  
**HIGH OUTPUT™ XC6.0**

**Includes:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Pack,  
Rapid Charger

M18 FUEL

1/4" Hex Impact Driver w/ ONE-KEY™ Kit

2857-22, 2857-22CT (2857-20 Tool-Only)

<b>Specifications:</b>	
Max Torque	2,000 in-lbs
IPM	0 – 4,300
RPM	0 – 3,600
DRIVE CONTROL™	4-Mode (Customizable)
Chuck Type	1/4" Hex
Single Hand Bit Insertion	Yes
Length / Weight	4.6" / 3.8 lbs

**Includes:** 2857-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs;  
2857-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs;  
**All Kits Include:** Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/4" Hex Impact Driver Kit

2853-22, 2853-22CT (2853-20 Tool-Only)

<b>Specifications:</b>	
Max Torque	2,000 in-lbs
IPM	0 – 4,300
RPM	0 – 3,600
DRIVE CONTROL™	4-Mode
Chuck Type	1/4" Hex
Single-Handed Bit Insertion	Yes
Length / Weight	4.6" / 3.8 lbs

**Includes:** 2853-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs;  
2853-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs;  
**All Kits Include:** Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18 FUEL

SURGE™ 1/4" Hex Hydraulic Driver Kit

2760-22, 2760-22CT (2760-20 Tool-Only)

<b>Specifications:</b>	
Sustained Max Torque	450 in-lbs
IPM	0 – 4,000
RPM	0 – 3,000
DRIVE CONTROL™	4-Mode
Length / Weight	5.0" / 3.9 lbs

**Includes:** 2760-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs;  
2760-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs;  
**All Kits Include:** Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18™

Brushless 1/4" Hex 3-Speed Impact Driver

2851-20 Tool-Only

<b>Specifications:</b>	
Max Torque	1,600 in-lbs
IPM	0 – 4,200
RPM	0 – 3,400
Chuck Type	1/4" Hex
DRIVE CONTROL™	3-Mode
Length / Weight	5.1" / 2.0 lbs

Battery and Charger Sold Separately

**Includes:** Belt Clip



M18™

Compact Brushless 1/4" Hex Impact Driver Kit

2850-22CT (2850-20 Tool-Only)

<b>Specifications:</b>	
Max Torque	1,600 in-lbs
IPM	0 – 4,200
RPM	0 – 3,400
Chuck Type	1/4" Hex
Length / Weight	5.1" / 2.9 lbs

**Includes:** (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18™

1/4" Hex Compact Impact Driver Kit

2656-22CT (2656-20 Tool-Only)

<b>Specifications:</b>	
Max Torque	1,500 in-lbs
IPM	0 – 3,450
RPM	0 – 2,750
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.5" / 3.8 lbs

**Includes:** (2) M18™ REDLITHIUM™ CP1.5 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18™

1/4" 2-Speed Impact Driver Kit

2657-22, 2657-22CT (2657-20 Tool-Only)

<b>Specifications:</b>	
Max Torque	1,500 in-lbs
IPM	0 – 3,450
RPM	0 – 2,750
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.5" / 3.8 lbs

**Includes:** 2657-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs;  
2657-22CT (2) M18™ REDLITHIUM™ CP1.5 Battery Packs;  
**All Kits Include:** Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/4" Blind Rivet Tool w/ ONE-KEY™ Kit

2660-22CT (2660-20 Tool-Only)

<b>Specifications:</b>	
Rivet Sizes	3/16" (4.8 mm), 7/32" (6.0 mm), 1/4" (6.4 mm), 9/32" (7.0 mm)
Rivet Material	Aluminum, Steel, Stainless Steel
Pull Force	4,500 lbs
Length / Weight	12.5" / 5.6 lbs

**Includes:** (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, (4) Retention Nose Pieces, Nose Piece Wrench, Mandrel Collector, Hanging Ring, Belt Clip, Multi-Voltage Charger, Contractor Bag

**Related Accessories:**  
49-16-2660NR Non-Retention Nose Piece 4 pk  
49-16-2660EXT 6" Extension  
49-16-2660B Protective Boot



M18 FUEL

Drywall Screw Gun Kit

2866-22, 2866-22CT (2866-20 Tool-Only)

<b>Specifications:</b>	
RPM	0 – 4,500
Belt Clip	Yes
Auto Start Mode	Yes
Length / Weight	9.0" / 4.1 lbs

**Includes:** 2866-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs;  
2866-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs;  
**All Kits Include:** Belt Clip, PR2 Bit, Multi-Voltage Charger, Contractor Bag  
**Related Accessory:**  
49-20-0001 MILWAUKEE® Collated Magazine  
Screw Capacity: Up to 2"  
Compatible with all major screw brands

**Related Tool:**  
2627-22 M18™ Cut Out Tool Kit **Pg. 52**



M18™

Right Angle Impact Driver Kit

2667-22, 2667-21CT (2667-20 Tool-Only)

<b>Specifications:</b>	
Max Torque (2-Mode)	350 / 675 in-lbs
IPM	0 – 2,400 / 0 – 3,400
RPM	0 – 1,500 / 0 – 2,250
Anvil Type	1/4" Hex
Length / Weight	14.1" / 3.9 lbs

**Includes:** 2667-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs; 2667-21CT (1) M18™ REDLITHIUM™ CP1.5 Battery Pack;  
**All Kits Include:** Belt Clip, Multi-Voltage Charger, Carrying Case



M18™

Right Angle Impact Wrench Kit

2668-22, 2668-21CT (2668-20 Tool-Only)

<b>Specifications:</b>	
Fastening Torque (2-Mode)	30 / 60 ft-lbs
Nut-Busting Torque	60 ft-lbs
IPM	0 – 2,400 / 0 – 3,400
RPM	0 – 1,500 / 0 – 2,250
Anvil Type	3/8"
Length / Weight	14.3" / 3.9 lbs

**Includes:** 2668-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs;  
2668-21CT (1) M18™ REDLITHIUM™ CP1.5 Battery Pack;  
**All Kits Include:** Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" Compact Impact Wrench w/ Pin Detent w/ ONE-KEY™ Kit

2759-22, 2759B-22 (2759-20, 2759B-20 Tool-Only)

<b>Specifications:</b>	
Fastening Torque	220 ft-lbs
Nut-Busting Torque	220 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,500
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	6.1" / 4.2 lbs

**Includes:** 2759-22 1/2" Compact Impact Wrench w/ Pin Detent w/ ONE-KEY™; 2759B-22 1/2" Compact Impact Wrench w/ Friction Ring w/ ONE-KEY™;  
**All Kits Include:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" Compact Impact Wrench w/ Friction Ring Kit

2855-22 (2855-20 Tool-Only)

<b>Specifications:</b>	
Fastening Torque	250 ft-lbs
Nut-Busting Torque	250 ft-lbs
IPM	0 – 3,500
RPM	0 – 2,400
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" Compact Impact Wrench w/ Pin Detent Kit

2855P-22 (2855P-20 Tool-Only)

<b>Specifications:</b>	
Fastening Torque	250 ft-lbs
Nut-Busting Torque	250 ft-lbs
IPM	0 – 3,500
RPM	0 – 2,400
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18™

1/2" Compact Impact Wrench Kit

2659-22 (2659-20 Tool-Only)

<b>Specifications:</b>	
Fastening Torque	183 ft-lbs
Nut-Busting Torque	183 ft-lbs
IPM	0 – 3,350
RPM	0 – 2,450
Anvil Type	1/2" Pin Detent
Length / Weight	6.0" / 4.1 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

3/8" Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2758-22, 2758-22CT (2758-20 Tool-Only)

Specifications:

Fastening Torque	210 ft-lbs
Nut-Busting Torque	210 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,500
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	5.9" / 4.2 lbs

**Includes:** 2758-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2758-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; **All Kits Include:** Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18 FUEL

3/8" Compact Impact Wrench w/ Friction Ring Kit

2854-22, 2854-22CT (2854-20 Tool-Only)

Specifications:

Fastening Torque	250 ft-lbs
Nut-Busting Torque	250 ft-lbs
IPM	0 – 3,500
RPM	0 – 2,400
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs

**Includes:** 2854-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2854-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; **All Kits Include:** Belt Clip, Multi-Voltage Charger, Carrying Case



M18™ 3/8" Compact Impact Wrench Kit

2658-22, 2658-22CT (2658-20 Tool-Only)

Specifications:

Fastening Torque	167 ft-lbs
Nut-Busting Torque	167 ft-lbs
IPM	0 – 3,350
RPM	0 – 2,450
Anvil Type	3/8" Friction Ring
Length / Weight	6.0" / 4.1 lbs

**Includes:** 2658-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs; 2658-22CT (2) M18™ REDLITHIUM™ CP1.5 Battery Packs; **All Kits Include:** Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" Mid-Torque Impact Wrench w/ Pin Detent Kit

2962P-22 (2962P-20 Tool-Only)

Specifications:

Fastening Torque	650 ft-lbs
Nut-Busting Torque	550 ft-lbs
IPM	0 – 3,500
RPM	0 – 2,400
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" Mid-Torque Impact Wrench w/ Friction Ring Kit

2962-22 (2962-20 Tool-Only)

Specifications:

Fastening Torque	650 ft-lbs
Nut-Busting Torque	550 ft-lbs
IPM	0 – 3,100
RPM	0 – 2,575
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	6.0" / 5.1 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

3/8" Mid-Torque Impact Wrench w/ Friction Ring Kit

2960-22, 2960-22CT (2960-20 Tool-Only)

Specifications:

Fastening Torque	600 ft-lbs
Nut-Busting Torque	550 ft-lbs
IPM	0 – 3,100
RPM	0 – 2,575
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	6.0" / 5.0 lbs

**Includes:** 2960-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2960-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; **All Kits Include:** Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

1" D-Handle High Torque Impact Wrench w/ ONE-KEY™ Kit

2868-22HD (2868-20 Tool-Only)

Specifications:

Fastening Torque	1,900 ft-lbs
Nut-Busting Torque	2,000 ft-lbs
IPM	0 – 1,440
RPM	0 – 1,200
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	17.94" / 21 lbs

**Includes:** (2) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Packs, Tool-Free Adjustable Handle, Lanyard Loop, Rapid Charger, Contractor Bag



M18 FUEL

1" D-Handle Ext. Anvil High Torque Impact Wrench w/ ONE-KEY™ Kit

2869-22HD (2869-20 Tool-Only)

Specifications:

Fastening Torque	1,900 ft-lbs
Nut-Busting Torque	2,000 ft-lbs
IPM	0 – 1,440
RPM	0 – 1,200
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	23.2" / 27.2 lbs

**Includes:** (2) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Packs, Tool-Free Adjustable Handle, Lanyard Loop, Rapid Charger, Contractor Bag



M18 FUEL

1" High Torque Impact Wrench w/ ONE-KEY™ Kit

2867-22 (2867-20 Tool-Only)

Specifications:

Fastening Torque	1,500 ft-lbs
Nut-Busting Torque	1,800 ft-lbs
IPM	0 – 2,450
RPM	0 – 1,650
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	10.9" / 13 lbs

**Includes:** (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Packs, Tool-Free Adjustable Handle, Lanyard Loop, Rapid Charger, Contractor Bag



REDLITHIUM  
HIGH OUTPUT XC8.0

M18 FUEL

3/4" High Torque Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2864-22 (2864-20 Tool-Only)

Specifications:

Fastening Torque	1,200 ft-lbs
Nut-Busting Torque	1,600 ft-lbs
IPM	0 – 1,850
RPM	0 – 1,850
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	8.6" / 7.9 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18™ 3/4" High Torque Impact Wrench w/ Friction Ring Kit

2664-22 (2664-20 Tool-Only)

Specifications:

Fastening Torque	525 ft-lbs
Breakaway Torque	700 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Length / Weight	9.0" / 6.8 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" Ext. Anvil Controlled Torque Impact Wrench w/ ONE-KEY™ Kit

2769-22 (2769-20 Tool-Only)

Specifications:

Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 – 2,400
RPM	0 – 1,800
DRIVE CONTROL™	4-Mode (Customizable)
Anvil Type	1/2" Friction Ring
Length / Weight	10.1" / 5.8 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Contractor Bag



M18 FUEL

1/2" High Torque Impact Wrench w/ Pin Detent w/ ONE-KEY™ Kit

2862-22 (2862-20 Tool-Only)

Specifications:

Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 – 2,400
RPM	0 – 1,800
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	8.1" / 7.2 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" High Torque Impact Wrench w/ Pin Detent Kit

2766-22 (2766-20 Tool-Only)

Specifications:

Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 – 2,400
RPM	0 – 1,850
DRIVE CONTROL™	4-Mode w/ Bolt Removal Mode
Length / Weight	8.1" / 7.1 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18™ 1/2" High Torque Impact Wrench w/ Pin Detent Kit

2662-22 (2662-20 Tool-Only)

Specifications:

Fastening Torque	450 ft-lbs
Breakaway Torque	640 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Length / Weight	8.9" / 6.7 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" High Torque Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2863-22 (2863-20 Tool-Only)

Specifications:

Fastening Torque	1,000 ft-lbs
Nut-Busting Torque	1,400 ft-lbs
IPM	0 – 2,100
RPM	0 – 1,750
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	8.4" / 7.6 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case





### M18™ 6-1/2" Circular Saw Kit

2630-22 (2630-20 Tool-Only)

**Specifications:**

RPM	3,500
Bevel Capacity	50°
Cut Capacity	2-1/8" at 90°; 1-9/16" at 45°
Arbor	5/8"
Blade Guards	Plastic
Weight	8.5 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Circular Saw Blade, Rip Fence, Wrench, Multi-Voltage Charger, Contractor Bag



### M18 FUEL D-Handle Jig Saw Kit

2737-21 (2737-20 Tool-Only)

**Specifications:**

SPM	3,500
Stroke Length	1"
Bevel Capacity	45°
Blade Clamp	Lever-Action QUIK-LOK™ T-Shank
Orbital Settings	4
Weight	6.4 lbs

**Includes:** (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Dust Collection Tube, Shoe Guard, Anti-Splinter Guard, Dust Cover, Wrench, Multi-Voltage Charger, Carrying Case



### M18™ Random Orbit Sander Kit

2648-21 (2648-20 Tool-Only)

**Specifications:**

OPM	12,000
Variable Speed	7,000 – 12,000 OPM
Pad Size	5.0"
Orbit Diameter	3/32"
Weight	2.7 lbs

**Includes:** (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, (2) Pieces of 80 Grit Sandpaper, Universal Hose Adapter, Universal Hook & Loop Pad, Multi-Voltage Charger, Contractor Bag



### M18™ 3-1/4" Planer Kit

2623-21 (2623-20 Tool-Only)

**Specifications:**

RPM	14,000
Planing Width	3-1/4"
Max Planing Depth	5/64"
Rabbet Depth	27/64"
Length / Weight	12.4" / 7.8 lbs

**Includes:** (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, Bevel Edge Guide, (2) Double-Edged Carbide Blades, Multi-Voltage Charger, Contractor Bag



### M18 FUEL Barrel Grip Jig Saw

2737B-20 Tool-Only

**Specifications:**

SPM	3,500
Stroke Length	1"
Bevel Capacity	45°
Blade Clamp	Lever-Action QUIK-LOK™ T-Shank
Orbital Settings	4
Weight	4.6 lbs

Battery and Charger Sold Separately

**Includes:** Dust Collection Tube, Shoe Guard, Anti-Splinter Guard, Dust Cover, LED Cover, Wrench



### M18 FUEL Compact Router

2723-20 Tool-Only

**Specifications:**

RPM	10,000 – 31,000
Speeds	6
Collet Size	1/4"
Adjustable Range	1.5"
Height / Weight	6.9" / 3.0 lbs

Battery and Charger Sold Separately

**Includes:** Fixed Base, Straight Edge Guide, 5-3/4" Template Bushing Sub-base plate, Dust Shroud, 11/16" Collet Wrench, 7/16" Spindle Wrench  
**Related Accessories:**  
**48-10-5601** Compact Router Plunge Base  
**48-10-5602** Compact Router Offset Base



### M18 FUEL Oscillating Multi-Tool Kit

2836-21 (2836-20 Tool-Only)

**Specifications:**

Speed Settings	12
OPM	10,000 – 20,000
Oscillation Angle	4.2°
Auto-Load Feature	Yes
LED Light	Yes
Length / Weight	14.5" / 4.2 lbs

**Includes:** (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, (5) Sanding Sheets, Sanding Pad, Wood Cutting Blade, Charger, Contractor Bag



### M18™ Multi-Tool Kit

2626-22 (2626-20 Tool-Only)

**Specifications:**

Speed Settings	12
OPM	11,000 – 18,000
Tool-Free Accessory Change	Yes
Length / Weight	14.0" / 4.2 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Wood Cutting Blade, Sanding Pad, (5) Assorted Sanding Sheets, Multi-Voltage Charger, Contractor Bag



### M18™ Cut Out Tool Kit

2627-22, 2627-22CT (2627-20 Tool-Only)

**Specifications:**

RPM	28,000
Tool-Free Depth Adjustment	Yes
LED Light	Yes
Belt Clip	Yes
Length / Weight	8.9" / 1.8 lbs

**Includes:** **2627-22** (2) M18™ REDLITHIUM™ XC3.0 Battery Packs; **2627-22CT** (2) M18™ REDLITHIUM™ CP1.5 Battery Packs;  
**All Kits Include:** Belt Clip, (2) 1/8" Drywall Bits, 1/8" Collet, 1/4" Collet, Wrench, Multi-Voltage Charger, Contractor Bag  
**Related Tool:**  
**2866-22** M18 FUEL™ Drywall Screw Gun Kit **Pg. 46**



### M18™ 10 oz Caulk and Adhesive Gun Kit

2641-21CT (2641-20 Tool-Only)

**Specifications:**

Force	950 lbs
Inches Per Minute	0 – 21
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	5.8 lbs

**Includes:** (1) M18™ REDLITHIUM™ CP1.5 Battery Pack, 10 oz Carriage, M18™ 10 oz Plunger Rod and Piston Assembly, Multi-Voltage Charger



### M18™ 20 oz Aluminum Barrel Sausage Style Caulk & Adhesive Gun Kit

2642-21CT

**Specifications:**

Force	950 lbs
Inches Per Minute	0 – 21
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	6.5 lbs

**Includes:** (1) M18™ REDLITHIUM™ CP1.5 Battery Pack, 20 oz Aluminum Sausage Style Barrel, M18™ 20 oz Plunger Rod and Piston Assembly, Nozzle, Multi-Voltage Charger



### M18™ 20 oz Clear Barrel Sausage Style Caulk & Adhesive Gun Kit

2643-21CT

**Specifications:**

Force	950 lbs
Inches Per Minute	0 – 21
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	6.6 lbs

**Includes:** (1) M18™ REDLITHIUM™ CP1.5 Battery Pack, 20 oz Clear Sausage Style Barrel, M18™ 20 oz Plunger Rod and Piston Assembly, Nozzle, Multi-Voltage Charger



### Caulk Gun Accessories

Compatible with 2641-21CT, 2642-21CT, and 2643-21CT

**31-12-0700** Caulk Gun Nozzle – Black  
**48-08-1076** M18™ 10 oz Caulk and Adhesive Gun Conversion Kit  
**48-08-1091** 20 oz Aluminum Barrel Kit  
**48-08-1093** M18™ 20 oz Aluminum Barrel Sausage Style Caulk and Adhesive Gun Conversion Kit  
**48-08-1094** M18™ 20 oz Clear Barrel Sausage Style Caulk and Adhesive Gun Conversion Kit  
**48-08-1095** M18™ Quart Caulk and Adhesive Gun Conversion Kit  
**48-08-1096** 20 oz Clear Barrel Kit



**M18 FUEL**  
**7-1/4" Dual Bevel Sliding Compound Miter Saw Kit**  
2733-21 (2733-20 Tool-Only)

**Specifications:**

Blade Size	7-1/4"
No Load RPM	5,000
Max Bevel Angle	48° / 48°
Max Miter Angle	48° / 48°
Max Vertical Capacity	3-1/2"
Max Horizontal Capacity	2x8
Weight	28.0 lbs

**M18 FUEL**  
**8-1/4" Table Saw w/ ONE-KEY™ Kit**  
2736-21HD (2736-20 Tool-Only)

**Specifications:**

RPM	6,300
Blade Size	8-1/4"
Arbor Size	5/8"
Max Bevel	47°
Cut Depth	2-1/2" at 90°; 1-3/4" at 45°
Rip Capacity	24" Left of Blade; 12" Right of Blade
Weight	45.0 lbs

**Includes:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Blade, Wrench, Anti-Kickback Pawls, Guard, Riving Knife, Fence, Push Stick, Miter Gauge, Rapid Charger

**M18 FUEL**  
**12" Dual Bevel Sliding Compound Miter Saw w/ ONE-KEY™ Kit**  
2739-21HD (2739-20 Tool-Only)

**Specifications:**

Blade Size	12"
No Load RPM	3,500
Max Bevel Angle	48° / 48°
Max Miter Angle	50° / 60°
Max Vertical Capacity	6-3/4"
Max Horizontal Capacity	2x14
Weight	47.6 lbs

**M18 FUEL**  
**15 Gauge Finish Nailer Kit**  
2839-21CT (2839-20 Tool-Only)

**Specifications:**

Nail Diameter	15 Gauge
Nail Size	1-1/4" – 2-1/2"
Magazine Capacity	110
Magazine Loading	Bottom Load
Max Fire Rate	3 Nails per Second
Nails Per Charge	750
Firing Modes	Sequential & Contact Actuation

**Includes:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Blade, Clamp, Handles, Rapid Charger

**M18 FUEL**  
**10" Dual Bevel Sliding Compound Miter Saw Kit**  
2734-21 (2734-20 Tool-Only)

**Specifications:**

Blade Size	10"
No Load RPM	4,000
Max Bevel Angle	48° / 48°
Max Miter Angle	50° / 60°
Max Vertical Capacity	5-3/4"
Max Horizontal Capacity	2x12
Weight	47.0 lbs

**M18 FUEL**  
**16 Gauge Straight Finish Nailer Kit**  
2741-21CT (2741-20 Tool-Only)

**Specifications:**

Nail Diameter	16 Gauge
Nail Size	3/4" – 2-1/2"
Nail Collation Angle	0°
Magazine Capacity	110 Nails
Max Fire Rate	3 Nails per Second
Magazine Loading	Bottom Load
Length / Weight	11.9" / 7.2 lbs

**Includes:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Blade Wrench, Carbide Tipped Blade, Clamp, Dust Bag, Rapid Charger

**M18 FUEL**  
**7-1/4" Dual Bevel Sliding Compound Miter Saw Kit**  
2733-21 (2733-20 Tool-Only)

**Specifications:**

Blade Size	7-1/4"
No Load RPM	5,000
Max Bevel Angle	48° / 48°
Max Miter Angle	48° / 48°
Max Vertical Capacity	3-1/2"
Max Horizontal Capacity	2x8
Weight	28.0 lbs

**M18 FUEL**  
**16 Gauge Angled Finish Nailer Kit**  
2841-21CT (2841-20 Tool-Only)

**Specifications:**

Nail Diameter	16 Gauge
Nail Size	1-1/4" – 2-1/2"
Magazine Capacity	110
Magazine Loading	Bottom Load
Max Fire Rate	3 Nails per Second
Nails per Charge	800
Firing Modes	Sequential & Contact Actuation

**Includes:** (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Blade Wrench, Blade, Clamp, Multi-Voltage Charger



**M18 FUEL**  
**15 Gauge Finish Nailer Kit**  
2839-21CT (2839-20 Tool-Only)

**Specifications:**

Nail Diameter	15 Gauge
Nail Size	1-1/4" – 2-1/2"
Magazine Capacity	110
Magazine Loading	Bottom Load
Max Fire Rate	3 Nails per Second
Nails Per Charge	750
Firing Modes	Sequential & Contact Actuation

**M18 FUEL**  
**21° Framing Nailer Kit**  
2744-21 (2744-20 Tool-Only)

**Specifications:**

Collation Angle	21° Round Head Nail
Nail Size	2" – 3-1/2"
Nail Collation	20° – 22°
Magazine Capacity	45 Nails
Max Fire Rate	3 Nails per Second
Firing Modes	Sequential or Contact Actuation

**Includes:** (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Contractor Bag



**M18 FUEL**  
**16 Gauge Angled Finish Nailer Kit**  
2841-21CT (2841-20 Tool-Only)

**Specifications:**

Nail Diameter	16 Gauge
Nail Size	1-1/4" – 2-1/2"
Magazine Capacity	110
Magazine Loading	Bottom Load
Max Fire Rate	3 Nails per Second
Nails per Charge	800
Firing Modes	Sequential & Contact Actuation

**M18 FUEL**  
**18 Gauge Brad Nailer Kit**  
2746-21CT (2746-20 Tool-Only)

**Specifications:**

Nail Diameter	18 Gauge
Nail Size	5/8" – 2-1/8"
Magazine Capacity	110 Nails
Max Fire Rate	3 Nails per Second
Magazine Loading	Side Load
Firing Modes	Sequential or Contact Actuation

**Includes:** (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Contractor Bag

**M18 FUEL**  
**21° Framing Nailer Kit**  
2744-21 (2744-20 Tool-Only)

**Specifications:**

Collation Angle	21° Round Head Nail
Nail Size	2" – 3-1/2"
Nail Collation	20° – 22°
Magazine Capacity	45 Nails
Max Fire Rate	3 Nails per Second
Firing Modes	Sequential or Contact Actuation

**M18 FUEL**  
**18 Gauge 1/4" Narrow Crown Stapler Kit**  
2749-21CT (2749-20 Tool-Only)

**Specifications:**

Staple Diameter	18 Gauge
Staple Crown Size	1/4"
Staple Length	3/8" – 1-1/2"
Magazine Capacity	108 Staples
Max Fire Rate	4 Staples per Second
Magazine Loading	Front Load

**Includes:** (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Rafter Hook, Hex Key, Multi-Voltage Charger, Contractor Bag  
**Related Accessory:** 48-08-2744 21° Framing Nailer Extended Capacity Magazine



**M18 FUEL**  
**30° Framing Nailer Kit**  
2745-21 (2745-20 Tool-Only)

**Specifications:**

Collation Angle	30° Clipped or Full Head Nail
Nail Size	2" – 3-1/2"
Nail Collation	30° – 34°
Magazine Capacity	57 Nails
Max Fire Rate	3 Nails per Second
Firing Modes	Sequential or Contact Actuation

**M18 FUEL**  
**18 Gauge Brad Nailer Kit**  
2746-21CT (2746-20 Tool-Only)

**Specifications:**

Nail Diameter	18 Gauge
Nail Size	5/8" – 2-1/8"
Magazine Capacity	110 Nails
Max Fire Rate	3 Nails per Second
Magazine Loading	Side Load
Firing Modes	Sequential or Contact Actuation

**Includes:** (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Rafter Hook, Hex Key, Multi-Voltage Charger, Contractor Bag  
**Related Accessory:** 48-08-2745 30° Framing Nailer Extended Capacity Magazine

**M18 FUEL**  
**18 Gauge Brad Nailer Kit**  
2746-21CT (2746-20 Tool-Only)

**Specifications:**

Nail Diameter	18 Gauge
Nail Size	5/8" – 2-1/8"
Magazine Capacity	110 Nails
Max Fire Rate	3 Nails per Second
Magazine Loading	Side Load
Firing Modes	Sequential or Contact Actuation

**M18 FUEL**  
**18 Gauge 1/4" Narrow Crown Stapler Kit**  
2749-21CT (2749-20 Tool-Only)

**Specifications:**

Staple Diameter	18 Gauge
Staple Crown Size	1/4"
Staple Length	3/8" – 1-1/2"
Magazine Capacity	108 Staples
Max Fire Rate	4 Staples per Second
Magazine Loading	Front Load

**Includes:** (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Reversible Belt Hook, Multi-Voltage Charger, Contractor Bag

**M18 FUEL**  
**18 Gauge 1/4" Narrow Crown Stapler Kit**  
2749-21CT (2749-20 Tool-Only)

**Specifications:**

Staple Diameter	18 Gauge
Staple Crown Size	1/4"
Staple Length	3/8" – 1-1/2"
Magazine Capacity	108 Staples
Max Fire Rate	4 Staples per Second
Magazine Loading	Front Load

**M18 FUEL**  
**16 Gauge Straight Finish Nailer Kit**  
2741-21CT (2741-20 Tool-Only)

**Specifications:**

Nail Diameter	16 Gauge
Nail Size	3/4" – 2-1/2"
Nail Collation Angle	0°
Magazine Capacity	110 Nails
Max Fire Rate	3 Nails per Second
Magazine Loading	Bottom Load
Length / Weight	11.9" / 7.2 lbs

**Includes:** (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Reversible Belt Hook, Multi-Voltage Charger, Contractor Bag

**M18 FUEL**  
**16 Gauge Straight Finish Nailer Kit**  
2741-21CT (2741-20 Tool-Only)

**Specifications:**

Nail Diameter	16 Gauge
Nail Size	3/4" – 2-1/2"
Nail Collation Angle	0°
Magazine Capacity	110 Nails
Max Fire Rate	3 Nails per Second
Magazine Loading	Bottom Load
Length / Weight	11.9" / 7.2 lbs

**M18 FUEL**  
**16 Gauge Straight Finish Nailer Kit**  
2741-21CT (2741-20 Tool-Only)

**Specifications:**

Nail Diameter	16 Gauge
Nail Size	3/4" – 2-1/2"
Nail Collation Angle	0°
Magazine Capacity	110 Nails
Max Fire Rate	3 Nails per Second
Magazine Loading	Bottom Load
Length / Weight	11.9" / 7.2 lbs

**Includes:** (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Contractor Bag



M18 FUEL

2 Gallon Compact Quiet Compressor

2840-20 Tool-Only

Specifications:

SCFM	1.2 @ 90 PSI
Capacity	2 Gallon
Sound Level	68 dB(a)
Dimensions (L x W x H)	16.3" / 18.5" / 10.3"
Weight	31.2 lbs
Regulator	Single Turn
Pump Type	Oil Free

Battery and Charger Sold Separately



M18 FUEL

9" Cut-Off Saw w/ ONE-KEY™ Kit

2786-22HD (2786-20 Tool-Only)

Specifications:

RPM	6,600
Blade Size	9"
Arbor Size	7/8"
Cut Depth	3.4"
Load Indicator Light	Yes
Blade Brake	RAPIDSTOP™
Weight	10.6 lbs

**Includes:** (2) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Packs, Abrasive Blade, Diamond Blade, Wrench, Hex Key, Rapid Charger



M18™ SWITCH TANK™ 4-Gallon Backpack Water Supply Kit

2820-21WS

Specifications:

Tank Capacity	4 Gallon
Pump Type	Dual Diaphragm Pump
PSI Range	20 – 60 PSI (5 Modes)
Flow Rate Range	0.16 – 1.13 Gal/Min
Dry Weight	18.5 lbs

**Includes:** M18™ SWITCH TANK™ Powered Base, SWITCH TANK™ 4 Gallon Water Supply Tank Assembly, (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, 10' Hose w/ Quick-Connect, Water Spray Nozzle, Multi-Voltage Charger



M18™ SWITCH TANK™ 4-Gallon Backpack Concrete Sprayer Kit

2820-21CS

Specifications:

Tank Capacity	4 Gallon
Pump Type	Dual Diaphragm Pump
PSI Range	20 – 120 PSI (5 Modes)
Spray Distance	Up to 25'
Flow Rate Range	0.14 – 0.82 Gal/Min
Dry Weight	18.3 lbs

**Includes:** M18™ SWITCH TANK™ Powered Base, SWITCH TANK™ 4 Gallon Concrete Sprayer Tank Assembly, (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, Adjustable Nozzle, Fan Nozzle, Multi-Voltage Charger



SWITCH TANK™ Accessories

Compatible with 2820-20

Related Accessories:

**49-16-28WS** SWITCH TANK™ 4 Gallon Water Supply Tank Assembly  
**49-16-28CS** SWITCH TANK™ 4 Gallon Concrete Sprayer Tank Assembly  
**49-16-28PS** SWITCH TANK™ 4 Gallon Sprayer Tank Assembly

M18 FUEL

Deep Cut Band Saw Kit

2729-22, 2729-21 (2729-20 Tool-Only)

Specifications:

SFPM	0 – 380
Cut Capacity	5" x 5"
Shoe	Tool-Free
LED Light	Yes
Hang Hook	Yes
Weight	15.9 lbs

**Includes:** 2729-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2729-21 (1) M18™ REDLITHIUM™ XC5.0 Battery Pack;  
**All Kits Include:** Blade, Multi-Voltage Charger, Carrying Case



M18 FUEL

Deep Cut Dual-Trigger Band Saw Kit

2729S-22 (2729S-20 Tool-Only)

Specifications:

SFPM	0 – 380
Cut Capacity	5" x 5"
Shoe	Tool-Free Locking
LED Light	Yes
Hang Hook	Yes
Dual-Trigger Design	Yes
Weight	13.8 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Set of Band Saw Blade Covers, Blade, Multi-Voltage Charger, Contractor Bag



M18 FUEL

Compact Band Saw Kit

2829-22 (2829-20 Tool-Only)

Specifications:

SFPM	0 – 540
Cut Capacity	3-1/4" x 3-1/4"
Shoe	Tool-Free Locking
LED Light	Yes
Hang Hook	Yes
Dual-Trigger Design	No
Weight	7.7 lbs

**Includes:** (2) M18™ REDLITHIUM™ HIGH OUTPUT™ CP3.0 Battery Packs, Blade, Rapid Charger, Contractor Bag



M18 FUEL

Compact Dual-Trigger Band Saw Kit

2829S-22

Specifications:

SFPM	0 – 540
Cut Capacity	3-1/4" x 3-1/4"
Shoe	Tool-Free Locking
LED Light	Yes
Hang Hook	Yes
Dual-Trigger Design	Yes
Weight	7.7 lbs

**Includes:** (2) M18™ REDLITHIUM™ HIGH OUTPUT™ CP3.0 Battery Packs, Set of Band Saw Blade Covers, Blade, Rapid Charger, Contractor Bag



Band Saw Accessories

Deep Cut Band Saw Accessory:

Compatible with 2729-20, 2729S-22

**49-90-2729** Deep Cut Band Saw Blade Covers

Compact Band Saw Accessories:

Compatible with 2829-20, 2829S-20

**49-90-2829** Compact Band Saw Blade Covers

**49-90-2029** Compact Band Saw Reamer Attachment

M18 FUEL

Metal Cutting Circular Saw Kit

2782-22 (2782-20 Tool-Only)

Specifications:

RPM	3,900
Blade Size	5-3/8" – 5-7/8"
Arbor Size	20 mm
Hang Hook	Yes
Length / Weight	4.7" / 6.5 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, 30T Blade, Multi-Voltage Charger, Contractor Bag



M18 FUEL

8" Metal Cutting Circular Saw Kit

2982-21 (2982-20 Tool-Only)

Specifications:

Blade Cut Capacity	2-9/16"
RPM	4,000
Arbor Size	5/8"
Chip Collection	Yes
Overload Indicator Light	Yes
Electric Blade Brake	Yes
Length / Weight	15.5" / 12.1 lbs

**Includes:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Blade, Allen Key, Rapid Charger, Contractor Bag





M18™ Compact Heat Gun Kit

2688-21 (2688-20 Tool-Only)

Specifications:

Temperature	750°F
Guarded Nozzle	Yes
Ladder Hook	Yes
Length / Weight	6.4" / 3.3 lbs

**Includes:** (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, 3/8" Concentrator Nozzle, Hook Nozzle, Multi-Voltage Charger, Carrying Case



M18™ 18 Gauge Double Cut Shear Kit

2635-22 (2635-20 Tool-Only)

Specifications:

Head	18 Gauge Double Cut
360° Tool-Free Rotating Head	Yes
Variable Speed Trigger	Yes
Length / Weight	17.3" / 5.6 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Hex Key, Belt Clip, Multi-Voltage Charger, Contractor Bag



M18™ 14 Gauge Double Cut Shear Kit

2636-22 (2636-20 Tool-Only)

Specifications:

Head	14 Gauge Double Cut
360° Tool-Free Rotating Head	Yes
Variable Speed Trigger	Yes
Length / Weight	17.3" / 6.2 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Hex Key, Belt Clip, Multi-Voltage Charger, Contractor Bag



M18™ 18 Gauge Single Cut Shear Kit

2637-22 (2637-20 Tool-Only)

Specifications:

Head	18 Gauge Single Cut
360° Tool-Free Rotating Head	Yes
Variable Speed Trigger	Yes
Length / Weight	18.0" / 5.8 lbs

**Includes:** (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Hex Key, Belt Clip, Multi-Voltage Charger, Contractor Bag



M18 FUEL

7" Variable Speed Polisher Kit

2738-22, 2738-21 (2738-20 Tool-Only)

Specifications:

Capacity	7" Maximum
RPM	0 – 2,200
Variable Speed Dial and Trigger	Yes
Lock-On / Lock-Off	Yes
Length / Weight	19.8" / 6.4 lbs

**Includes:** 2738-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Backing Pad; 2738-21 (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack; **All Kits Include:** Screen Cover, Side Handle, Bail Handle with (2) Bolts, Rapid Charger



M18™ 2-Speed Grease Gun Kit

2646-22CT, 2646-21CT (2646-20 Tool-Only)

Specifications:

Output Pressure	Up to 10,000 PSI (690 BAR)
Run-Time	Up to 10 Cartridges Per Charge
Grease Capacity	14 oz Cartridge, 16 oz Bulk, 16 oz Suction
Air Bleeder Valve	Yes
Weight	8.5 lbs

**Includes:** 2646-22CT (2) M18™ REDLITHIUM™ CP1.5 Battery Packs; 2646-22CT (1) M18™ REDLITHIUM™ CP1.5 Battery Pack; **All Kits Include:** 48" Flex Hose with Spring Guard, High Pressure Grease Coupler, Shoulder Strap, Multi-Voltage Charger, Carrying Case **Related Accessories:** 49-16-2646 M18™ Grease Gun 400g Clear Barrel 49-16-2647 M18™ Replacement Grease Gun Hose with High Pressure Coupler 49-16-2648 M18™ Right Angle Grease Gun Coupler 49-16-2649 M18™ High Pressure Grease Coupler (2 pk)



M18™ Brushless Threaded Rod Cutter Kit

2872-21 (2872-20 Tool-Only)

Specifications:

Cutting Capacity	1/4", 3/8" and 1/2"
Replacement Cutting Dies	Yes
Dimensions (L x W x H)	10.0" x 5.0" x 6.3"
Weight	7.7 lbs

**Includes:** (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Cutting Dies, Allen Key, Multi-Voltage Charger, Carrying Case **Related Accessory:** 48-44-2872 1/4", 3/8", 1/2" Replacement Cutting Die Set



### M18™ FORCE LOGIC™ 6T Utility Crimper Kits



**w/ BG-D3 Jaw**  
2678-22BG  
(2678-20 Tool-Only)



**w/ O-D3 Jaw**  
2678-22O  
(2678-20 Tool-Only)



**w/ Snub Nose Jaw**  
2678-22  
(2678-20 Tool-Only)



**w/ Kearney Jaw**  
2678-22K  
(2678-20 Tool-Only)

#### Specifications:

Output Force	6 Tons
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Cycle Time	2.9 Seconds
Head Rotation	340°
Height / Length	5.4" / 14.0"

**Includes:** 2678-22BG 6T Fixed BG Crimping Jaw; 2678-22O 6T Fixed O Crimping Jaw; 2678-22 6T Snub Nose Crimping Jaw; 2678-22K 6T Kearney Crimping Jaw; **All Kits Include:** (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger, Utility Bag

### M18™ FORCE LOGIC™ 6T Pistol Utility Crimper Kits



**w/ BG-D3 Jaw**  
2977-22BG  
(2977-20 Tool-Only)



**w/ O-D3 Jaw**  
2977-22O  
(2977-20 Tool-Only)

#### Specifications:

Output Force	6 Tons
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Cycle Time	2.9 Seconds
Head Rotation	340°
Height / Length	12.3" / 17.3"

**Includes:** 2977-22BG 6T Fixed BG Crimping Jaw; 2977-22O 6T Fixed O Crimping Jaw; **All Kits Include:** (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger, Utility Bag



### M18™ FORCE LOGIC™ 6T Utility Crimper Accessories

Compatible with 2678-20, 2977-20, 2978-20

#### 6T Utility Crimper Jaws

**49-16-BGD3** 6T Fixed BG Crimping Jaw  
**49-16-1OD3** 6T Fixed O Crimping Jaw  
**49-16-11D3** 6T Snub Nose Crimping Jaw  
**49-16-KEAR** 6T Kearney Crimping Jaw

#### Cutter Jaws

Also Compatible with 2672-21, 2672-21S, and 2672-21F

**49-16-2772** 750 MCM Cu/Al Cutting Jaw  
**49-16-2773** 477 ACSR Cutting Jaw  
**49-16-2777** 1/2" EHS Guy Wire Cutting Jaw  
**49-16-2778** Fine-Stranded Wire Cutting Jaw

#### Cutter Replacement Blades

**48-44-0411** Replacement Copper Blades  
**48-44-0412** Replacement Steel Blades  
**48-44-2777** 1/2" EHS Guy Wire Replacement Blades  
**48-44-2778** Fine-Stranded Wire Replacement Blades

#### W Style Dies

**49-16-WBG0** W Style Die: "W-BG"  
**49-16-WO00** W Style Die: "W-O"  
**49-16-WC00** W Style Die: "W-C"  
**49-16-W161** W Style Die: "W-161"  
**49-16-W162** W Style Die: "W-162"  
**49-16-W163** W Style Die: "W-163"  
**49-16-W164** W Style Die: "W-164"  
**49-16-W165** W Style Die: "W-165"  
**49-16-W166** W Style Die: "W-166"  
**49-16-W237** W Style Die: "W-237"  
**49-16-W239** W Style Die: "W-239"  
**49-16-W243** W Style Die: "W-243"  
**49-16-W247** W Style Die: "W-247"  
**49-16-W249** W Style Die: "W-249"  
**49-16-W840** W Style Die: "W-K840"

### M18™ FORCE LOGIC™ 600 MCM Crimper Kit



2679-22, 2679-750C, 2679-750A,  
2679-350A, 2679-600C

#### Specifications:

Output Force	6 Tons
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Cycle Time	2.9 Seconds
Head Rotation	350°
Height / Length	5.4" / 13.3"

**Includes:** 2679-750C 750 MCM Cu/Al Crimping Jaw, All Copper U Style Dies (49-16-KITC Die Kit and 49-16-750C Die Kit); **2679-750A** 750 MCM Cu/Al Crimping Jaw, All Aluminum U Style Dies (49-16-KITA Die Kit and 49-16-750A Die Kit); **2679-350A** 49-16-KITA Die Kit; **2679-600C** 49-16-KITC Die Kit; **All Kits Include:** 2679-22 600 MCM Commercial U Crimping Jaw, (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger, Carrying Case

### FORCE LOGIC™ 600 MCM Crimper Accessories

Compatible with 2679-22, 2679-750C, 2679-750A,  
2679-350A, 2679-600C

#### Related Accessories:

**49-16-U000** 600 MCM Crimping Jaw  
**49-16-U111** 750 MCM Cu/Al Cable Crimping Jaw  
**49-16-2780** 750 MCM Cu/Al Cable Cutting Jaw

#### Cutter Replacement Blades

**48-44-0411** 750 MCM Cu/Al Cable Cutting Blades

#### Accessory Kits

**49-16-KITA** #8 AWG – 350 MCM Aluminum U Style Die Kit  
**49-16-750A** 400 – 750 MCM Aluminum U Style Die & Jaw Kit  
**49-16-KITC** #8 AWG – 600 MCM Copper U Style Die Kit  
**49-16-750C** 750 MCM Copper U Style Die & Jaw Kit

#### Copper U Style Dies

**49-16-U001C** #1 Copper U Style Die  
**49-16-U002C** #2 Copper U Style Die  
**49-16-U004C** #4 Copper U Style Die  
**49-16-U006C** #6 Copper U Style Die  
**49-16-U008C** #8 Copper U Style Die  
**49-16-U01AC** 1/0 Copper U Style Die  
**49-16-U02AC** 2/0 Copper U Style Die  
**49-16-U03AC** 3/0 Copper U Style Die  
**49-16-U04AC** 4/0 Copper U Style Die  
**49-16-U250C** 250 MCM Copper U Style Die  
**49-16-U300C** 300 MCM Copper U Style Die  
**49-16-U350C** 350 MCM Copper U Style Die  
**49-16-U400C** 400 MCM Copper U Style Die  
**49-16-U500C** 500 MCM Copper U Style Die  
**49-16-U600C** 600 MCM Copper U Style Die  
**49-16-U750C** 750 MCM Copper U Style Die

#### Aluminum Dual-Rated U Style Dies

**49-16-U001** #1 Aluminum U Style Die  
**49-16-U002** #2 Aluminum U Style Die  
**49-16-U004** #4 Aluminum U Style Die  
**49-16-U006** #6 Aluminum U Style Die  
**49-16-U008** #8 Aluminum U Style Die  
**49-16-U01A** 1/0 Aluminum U Style Die  
**49-16-U02A** 2/0 Aluminum U Style Die  
**49-16-U03A** 3/0 Aluminum U Style Die  
**49-16-U04A** 4/0 Aluminum U Style Die  
**49-16-U250** 250 MCM Aluminum U Style Die  
**49-16-U300** 300 MCM Aluminum U Style Die  
**49-16-U350** 350 MCM Aluminum U Style Die  
**49-16-U400** 400 MCM Aluminum U Style Die  
**49-16-U500** 500 MCM Aluminum U Style Die  
**49-16-U600** 600 MCM Aluminum U Style Die  
**49-16-U750** 750 MCM Aluminum U Style Die

### M18™ FORCE LOGIC™ 750 MCM Dieless Crimper Kit



2877-22

#### Specifications:

Crimping Capacity	#6 – 750 MCM Cu & Al
Adaptive Distance Control	Yes; Auto Distance Control
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Dimensions (L x W x H)	18.9" x 3.3" x 6.5"
Weight	9.0 lbs

**Includes:** (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger, Carrying Case



### M18™ FORCE LOGIC™ 12T Utility Crimper Kit



2778-22 (2778-20 Tool-Only)

#### Specifications:

Output Force	12 Tons
Head Rotation	350°
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Length / Weight	16.0" / 11.9 lbs

**Includes:** (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Carabiner, Multi-Voltage Charger and Inverter, Utility Bag





### M18™ FORCE LOGIC™ 6 Ton Knockout Tool Kit

2677-23, 2677-21 (2677-20 No Punches or Dies)

#### Specifications:

Mild Steel Capacity	4" in 14 Gauge
Stainless Steel Capacity	2" in 14 Gauge
Output Force	6 Tons
Quick-Connect Draw Stud	Yes
Rapid Reset	Yes
Height / Weight	4.5" / 4.3 lbs

**Includes:** **2677-23** (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, EXACT™ 1/2" – 4" Conduit Punches and Dies; **2677-21** (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, EXACT™ 1/2" – 2" Conduit Punches and Dies; **2677-20** (1) M18™ REDLITHIUM™ CP2.0 Battery Pack (No Punches or Dies Included); **All Kits Include:** (2) Draw Studs, Quick Connect Alignment System, Multi-Voltage Charger, Carrying Case



### M18™ FORCE LOGIC™ 10 Ton Knockout Tool Kit

2676-23, 2676-22 (2676-20 No Punches or Dies)

#### Specifications:

Mild Steel Capacity	6" in 12 Gauge
Stainless Steel Capacity	6" in 14 Gauge
Output Force	10 Tons
Quick-Connect Draw Stud	Yes
Rapid Reset	Yes
Height / Weight	5.5" / 7.1 lbs

**Includes:** **2676-23** (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, EXACT™ 1/2" – 4" Conduit Punches and Dies; **2676-22** (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, 1/2" – 2" EXACT™ Conduit Punches and Dies; **2676-20** (2) M18™ REDLITHIUM™ XC3.0 Battery Packs (No Punches or Dies Included); **All Kits Include:** (3) Draw Studs, Quick-Connect Alignment System, Multi-Voltage Charger, Carrying Case

### M18™ FORCE LOGIC™ Knockout Accessories

Compatible with 2677-20 and 2676-20

#### EXACT™ Accessory Kits

- 49-16-2692** 1/2" – 1-1/4" Knockout Set
- 49-16-2693** 1/2" – 2" Knockout Set
- 49-16-2694** 1/2" – 2" Hand Ratchet Knockout Set
- 49-16-2695** 2-1/2" – 4" Knockout Set

#### EXACT™ Punches and Dies

- 49-16-2660\*** 1/2" Die
- 49-16-2660S** 1/2" Die
- 49-16-2661\*** 1/2" Punch
- 49-16-2661S** 1/2" Punch
- 49-16-2662** 3/4" Die
- 49-16-2663** 3/4" Punch
- 49-16-2664** 1" Die
- 49-16-2665** 1" Punch
- 49-16-2666** 1-1/4" Die
- 49-16-2667** 1-1/4" Punch
- 49-16-2668** 1-1/2" Die
- 49-16-2669** 1-1/2" Punch
- 49-16-2670** 2" Die
- 49-16-2671** 2" Punch
- 49-16-2672** 2-1/2" Die
- 49-16-2673** 2-1/2" Punch
- 49-16-2674** 3" Die
- 49-16-2675** 3" Punch
- 49-16-2676** 3-1/2" Die
- 49-16-2677** 3-1/2" Punch
- 49-16-2678** 4" Die
- 49-16-2679** 4" Punch
- 49-16-2686** 5" Die
- 49-16-2687** 5" Punch
- 49-16-2688** 6" Die
- 49-16-2689** 6" Punch

\*These items are intended only for Mild Steel.

#### EXACT™ Sink Punches & Dies

- 49-16-2705** 7/8" Sink Die
- 49-16-2706** 7/8" Sink Punch
- 49-16-2700** 1-3/8" Sink Die
- 49-16-2701** 1-3/8" Sink Punch

#### Rapid Reset Draw Studs





- 49-16-2703** Rapid Reset 3/4" Draw Stud
- 49-16-2704** Rapid Reset 1-1/8" Draw Stud
- 49-16-2708** Rapid Reset 1-1/8" Long Draw Stud

#### Draw Studs

- 49-16-2621** 3/8" Ball Bearing Draw Stud
- 49-16-2622** 3/4" Ball Bearing Draw Stud
- 49-16-2680** 7/16" Draw Stud
- 49-16-2681** 3/4" Draw Stud
- 49-16-2682** 1-1/8" Draw Stud
- 49-16-2707** 1-1/8" Long Draw Stud

#### Adapters

- 49-16-2684** 3/8" Adapter for EXACT™ 2-1/2" – 4" Dies to 3/4" Draw Studs
- 49-16-2685** Adapter for M18™ FORCE LOGIC™ Knockout Tool to other major brands of punches and dies



### M18™ Cable Stripper Kit

2935CU-21S, 2935AL-21, 2935X-21 (2935-20 Tool-Only)

#### Specifications:

Variable Speed Trigger	Yes
Tool Free Depth Gauge	Yes
Compatible Bushing Types	Industry Standard Quick-Change
Dimensions (L x W x H)	8.5" x 2.8" x 11.3"
Weight	3.8 lbs

**Includes:** **2935CU-21S** 1/0 AWG – 750 MCM Cu THHN / XHHW Bushings; **2935AL-21** 1/0 AWG – 750 MCM Al THHN / XHHW Bushings; **2935X-21** 1/0 AWG – 500 MCM Cu RHW / RHH / USE Bushings; **All Kits Include:** (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Carrying Case



### M18 FUEL™ ANGLER™ Pulling Fish Tape Kit

2873A-22, 2873B-22 (2873-20 Tool-Only)

#### Specifications:

Pull Force	(4) #10 Wires
Powered Feed & Retract	Yes, AUTO-RUN™ Powered
Dimensions (L x W x H)	13.2" x 6.0" x 17.7"
Weight	19.1 lbs (2873B), 16.2 lbs (2873A), 8.3 lbs (2873-20)



**Includes:** **2873A-22:** ANGLER™ 120' x 1/8" Steel Pulling Fish Tape; **2873B-22:** ANGLER™ 240' x 1/8" Steel Pulling Fish Tape Replacement Cartridge; **All Kits Include:** (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger  
**Related Accessories:**  
**48-44-5176** M18 FUEL™ ANGLER™ 120' x 1/8" Steel Pulling Fish Tape Replacement Cartridge  
**48-44-5178** M18 FUEL™ ANGLER™ 240' x 1/8" Steel Pulling Fish Tape Replacement Cartridge  
**48-44-5195** M18 FUEL™ ANGLER™ 100' Non-Conductive Polyester Pulling Fish Tape Replacement Cartridge





M18 FUEL

Sewer Sectional Machine Kit w/ CABLE DRIVE™ for 7/8" & 1-1/4" Cable

2871A-22, 2871-22

Specifications:

Maximum Drain Line Capacity	2" – 8" up to 200'
Cable Capacity	7/8" and 1-1/4"
Powered Cable Feed & Retract	Yes, CABLE DRIVE™
Cable Spin Speed	700 RPM
Height / Length	23" / 35"
Weight	74 lbs

**Includes:** 2871A-22 (7) 1-1/4" x 15' All Purpose Open Wind Cables, (2) Cable Containers, Straight Auger, Funnel Auger, Small Opening Tool, Medium Opening Tool, 3" Grease Cutter, 3" Root Cutter, 4" Root Cutter, Pin Key, Head Attachment Case;  
**All Kits Include:** (2) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Packs, Rear Guide Hose, Rapid Charger



M18 FUEL

Sectional Machine for 5/8" & 7/8" Cable

2818-21, 2818A-21, 2818B-21

Specifications:

Maximum Drain Line Capacity	1-1/4" – 6" out to 150'
Cable Capacity	5/8" and 7/8"
Cable Feed & Retract	Manual
Cable Spin Speed	650 RPM
Height / Length	15.1" / 14.6"
Weight	27.3 lbs

**Includes:** 2818-21: Large Rear Guide Hose; 2818A-21: Large Rear Guide Hose, Medium Cable Container, (5) 7/8" x 15' All Purpose Open Wind Sectional Cables, 2" – 4" Head Attachment Kit; 2818B-21: Small Rear Guide Hose, Small Cable Container, (6) 5/8" x 7-1/2' All Purpose Open Wind Sectional Cables, 1/4" – 2" Head Attachment Kit;  
**All Kits Include:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Carry Strap, Rapid Charger



Sectional Machine Cables and Accessories

Related Accessories:

- 47-53-2871 Cable Container
- 47-53-2872 Rear Guide Hose
- 47-53-2874 Small Rear Guide Hose
- 47-53-2873 Large Rear Guide Hose
- 47-53-2869 Small Cable Container
- 47-53-2870 Medium Cable Container
- 48-08-0555 Carrying Strap

Compatible with 2818-20

5/8"

- 48-53-2680 5/8" x 7.5' All Purpose Sectional Cable
- 48-53-3811 Drop Head Bulb Auger w/ RUST GUARD™ for 5/8" Sectional Cable
- 48-53-3812 Drop Head Straight Auger w/ RUST GUARD™ for 5/8" Sectional Cable
- 48-53-3813 Flexible Funnel Auger w/ RUST GUARD™ for 5/8" Sectional Cable
- 48-53-3814 Flexible Opening Tool w/ RUST GUARD™ for 5/8" Sectional Cable
- 48-53-3815 2" Opening Tool w/ RUST GUARD™ for 5/8" Sectional Cable
- 48-53-3820 1-1/4" – 2" Head Attachment Kit w/ RUST GUARD™ for 5/8" Sectional Cable

Compatible with 2818-20 and 2871-20

7/8"

- 48-53-2852 7/8" x 15' All Purpose Sectional Cable
- 48-53-3829 Flexible Straight Auger w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3830 Straight Auger w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3828 Flexible Funnel Auger w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3831 Funnel Auger w/ RUST GUARD™ for Sectional Cable
- 48-53-3825 2" Root Cutter w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3832 3" Root Cutter w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3833 4" Root Cutter w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3834 6" Root Cutter w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3827 2" Opening Tool w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3835 3" Opening Tool w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3836 4" Opening Tool w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3837 3" Grease Cutter w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3838 4" Grease Cutter w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3839 2" – 4" Head Attachment Kit w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3840 3" – 6" Head Attachment Kit w/ RUST GUARD™ for 7/8" Sectional Cable

Compatible with 2871-20

1-1/4"

- 48-53-2851 1-1/4" x 15' All Purpose Sectional Cable
- 48-53-2854 1-1/4" x 15' Heavy Duty Sectional Cable
- 48-53-4830 Straight Auger w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4831 Funnel Auger w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4832 3" Root Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4833 4" Root Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4834 6" Root Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4835 3" Opening Tool w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4836 4" Opening Tool w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4837 3" Grease Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4838 4" Grease Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4840 3" – 8" Head Attachment Kit w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 44-60-0005 Pin Key for Drain Cleaning
- 48-53-2839 Head Attachment Case



M18 FUEL

SWITCH PACK™ Sectional Kit for 5/16" - 5/8" Cable

2775-211, 2775A-211, 2775B-211, 2775C-222, 2775E-211

Specifications:

Maximum Drain Line Capacity	1-1/4" – 4" up to 100' (not for roots)
Drum Capacity	Inner Core Cables: 5/16" x 75', Best for 1-1/4" – 2-1/2" drain lines; 3/8" x 50', Best for 2" – 3" drain lines; 1/2" x 50', Best for 3" – 4" drain lines Open Wind Cables: 5/8" x 50', Best for 1-1/4" – 3" drain lines (soft blockages)
Backpack Straps	Yes
Removable Drum	Yes, Tool-Free
Cable Spin Speed	250 RPM
Electronic Foot Pedal	Yes
Integrated Drum Brake	Yes
Length	15.8"

**Includes:** 2775A-211: 5/16" x 75' Inner Core Drop Head Cable w/ RUST GUARD™ Plating; 2775B-211: 3/8" x 50' Inner Core Coupling Cable w/ RUST GUARD™ Plating, (4) Cable Head Attachments w/ RUST GUARD™ Plating (1-1/2" Spade Bit, 1-1/2" C-Cutter, Medium Funnel, Medium Drop Head), Pin Key; 2775C-222: Additional M18™ REDLITHIUM™ XC5.0 Battery Pack, Additional SWITCH PACK™ Drum w/ Anchor Cable, (2) 1/2" x 50' Inner Core Coupling Cables w/ RUST GUARD™ Plating, (4) Cable Head Attachments w/ RUST GUARD™ Plating (1-1/2" Spade Bit, 1-1/2" C-Cutter, Medium Funnel, Medium Drop Head), Pin Key; 2775E-211: 5/8" x 50' Open Wind Coupling Cable w/ RUST GUARD™ Plating, (4) Cable Head Attachments w/ RUST GUARD™ Plating (1" Spade Bit, 1" C-Cutter, Small Bulb Head, Small Drop Head), Pin Key;  
**All Kits Include:** 2775-211: SWITCH PACK™ Powered Base, SWITCH PACK™ Drum w/ Anchor Cable, (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Multi-Voltage Charger  
**Related Accessories:** 47-53-2775 SWITCH PACK™ Drum w/ Anchor Cable 47-53-2774 CABLE DRIVE™ Assembly 47-53-2773 Mounting Plate 47-53-2776 Guide Hose

Drain Cleaning Accessories

Compatible with MILWAUKEE® and other professional brand drain cleaning machines

RUST GUARD™ Plated Cables

- 48-53-2563 1/4" x 25' Inner Core Bulb Head Handheld Cable
- 48-53-2564 1/4" x 25' Inner Core Drop Head Handheld Cable
- 48-53-2671 1/4" x 35' Inner Core Bulb Head Handheld Cable
- 48-53-2672 1/4" x 50' Inner Core Bulb Head Handheld Cable
- 48-53-2561 5/16" x 25' Inner Core Bulb Head Handheld Cable
- 48-53-2562 5/16" x 25' Inner Core Drop Head Handheld Cable
- 48-53-2673 5/16" x 35' Inner Core Bulb Head Handheld Cable
- 48-53-2674 5/16" x 50' Inner Core Bulb Head Handheld Cable
- 48-53-2772 5/16" x 75' Inner Core Drop Head Cable
- 48-53-2676 3/8" x 25' Inner Core Handheld Cable
- 48-53-2675 3/8" x 35' Inner Core Handheld Cable

RUST GUARD™ Plated Cable Attachments

Compatible with MILWAUKEE® Coupling Cables  
48-53-2681 Small Bulb Head  
48-53-2682 Small Drop Head  
48-53-2683 1" Spade Bit  
48-53-2684 1" C-Cutter  
48-53-2685 2" – 3" Head Attachment Kit  
48-53-2786 Medium Funnel Head  
48-53-2787 Medium Drop Head  
48-53-2788 1-1/2" Spade Bit  
48-53-2789 1-1/2" C-Cutter  
48-53-2790 2" – 3" Head Attachment Kit

M18 FUEL

Drain Snake w/ CABLE DRIVE™ Kit for 1/4" - 3/8" Cable

2772A-21 (2772A-20 Tool-Only), 2772B-21XC

Specifications:

Maximum Drain Line Capacity	1-1/4" – 3" up to 50'
Drum Capacity	1/4" x 50', Best for 1-1/4" – 2" drain lines; 5/16" x 50', Best for 1-1/4" – 2-1/2" drain lines; 3/8" x 35', Best for 2" – 3" drain lines
Powered Cable Feed & Retract	Yes, CABLE DRIVE™
Variable Feed Speed	0 – 8" Per Second
Variable Spin Speed	0 – 600 RPM
Feed Lock	Yes, Twist Lock
Cable Lock	Yes, Twist Lock
LED Light	Yes
Length / Weight	19.5" / 8.2 lbs

**Includes:** 2772A-21 (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, 5/16" x 35' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating; 2772B-21XC (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, 1/4" x 35' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating, 3/8" x 35' Inner Core Coupling Cable w/ RUST GUARD™ Plating, (4) Cable Attachments (1" Spade Bit, 1" C-Cutter, Small Bulb Head, Small Drop Head), Pin Key; 2772A-20 Only Includes 5/16" x 35' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating, Battery and Charger Sold Separately;  
**All Kits Include:** Multi-Voltage Charger, Storage Bucket





**M18™ 200' Stiff Pipeline Inspection System Kit**

2974-21 (2974-20 Reel-Only)

**Specifications:**

Line Capacity	3" – 10"
Push Cable	12 mm, 200'
Camera Head	34 mm, Self-Leveling, Sapphire Lens
Camera Resolution	1080P
Internal Storage	500GB
Sonde Frequency	512kHz, 640Hz, 33kHz
Line Trace Frequency	33kHz, 83kHz



**Includes:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, 200' Stiff Pipeline Inspection Reel, M18™ 500GB Control Hub, Tablet Mount, Medium Camera Head Skid for 34 mm Camera, Small Camera Head Skid for 34 mm Camera, Rapid Charger

**M18™ Wireless Monitor**

2971-20 Tool-Only

**Specifications:**

Screen	8" Daylight Readable
Resolution	800 x 600
Wireless Range	200'
Weight	4 lbs

Battery and Charger Sold Separately

**Includes:** USB-C Cable



**M18™ 120' Pipeline Inspection System Kit**

2973-22 (2973-20 Tool-Only)

**Specifications:**

Line Capacity	2" – 6"
Push Cable	10 mm, 120'
Camera Head	25 mm, Self-Leveling, Sapphire Lens
Camera Resolution	1080P
Internal Storage	500GB
Sonde Frequency	512kHz, 33kHz
Line Trace Frequency	33kHz, 83kHz



**Includes:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, 120' Mid-Stiff Pipeline Inspection Reel, M18™ 500GB Control Hub, Tablet Mount, Medium Camera Head Skid for 25 mm Camera, Small Camera Head Skid for 25 mm Camera, Rapid Charger

**Related Accessories:**

2971-20 M18™ Wireless Monitor

2970-20 M18™ 500GB Control Hub

48-53-2970 Tablet Mount



**M18™ Transfer Pump Kit**

2771-21 (2771-20 Tool-Only)

**Specifications:**

Gallons Per Hour	480
Gallons Per Battery (w/ M18™ XC3.0 Battery)	144
Maximum Lift	18'
Maximum Head Height	75'
Self-Priming	Yes
Flexible Impeller	Yes
Fittings	3/4" Brass Inlet and Outlet
Weight	7.5 lbs



**Includes:** (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, (2) 3/4" Brass Fittings, Multi-Voltage Charger



**OUTDOOR POWER EQUIPMENT**

**M18 FUEL**  
DRIVEN TO OUTPERFORM.

**1 POWERSTATE™ BRUSHLESS MOTOR**

**2 REDLINK PLUS™ INTELLIGENCE**

**3 REDLITHIUM™ HIGH OUTPUT™ XC8.0 BATTERY PACK**

**MORE POWER**

**FULL THROTTLE UNDER 1 SECOND**

**MORE RUN-TIME**

**NO GAS HEADACHES**



**NO PULL START**



**NO ENGINE MAINTENANCE**



**LOW NOISE**



**NO EMISSIONS**



**NO MIXING GAS AND OIL**

**ALL M18™ TOOLS FIT M18™ BATTERIES**

**1 SYSTEM**



**200+ TOOLS**

M18 FUEL

16" Chainsaw Kit

2727-21HD (2727-20 Tool-Only)

Specifications:

Bar Length	16"
Chain Gauge	.043"
Chain Pitch	3/8" Low Profile
RPM	6,600
Length / Weight	33.0" / 13.9 lbs

**Includes:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, 16" Oregon® Bar and Chain, Srench, Scabbard, Rapid Charger



M18 FUEL

14" Chainsaw

2727-20C Tool-Only

Specifications:

Bar Length	14"
Chain Gauge	.043"
Chain Pitch	3/8" Low Profile
RPM	6,600
Length / Weight	31.0" / 10.4 lbs

Battery and Charger Sold Separately

**Includes:** 14" Oregon® Bar and Chain, Srench, Scabbard



M18 FUEL

String Trimmer Kit w/ QUIK-LOK™

2825-21ST (2825-20ST Tool-Only)

Specifications:

Cutting Swath	14" – 16"
Line Diameter	.080" / .095"
RPM	0 – 4,900 / 0 – 6,200
Trigger	Variable Speed
Feed System	Bump Feed
Length / Weight	73.6" / 12.3 lbs

**Includes:** M18 FUEL™ Power Head w/ QUIK-LOK™, M18 FUEL™ QUIK-LOK™ String Trimmer Attachment, (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Rapid Charger



M18 FUEL

Pole Saw Kit w/ QUIK-LOK™

2825-21PS (2825-20PS Tool-Only)

Specifications:

RPM	0 – 4,600
Bar Length	10"
Chain Gauge	.043"
Chain Pitch	3/8" Low Profile
Length / Weight	84.0" / 12.7 lbs

**Includes:** M18 FUEL™ Power Head w/ QUIK-LOK™, M18 FUEL™ QUIK-LOK™ 10" Pole Saw Attachment, QUIK-LOK™ 3' Attachment Extension, (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Oregon® Bar and Chain, Srench, Rapid Charger



M18 FUEL

QUIK-LOK™ Attachments

Compatible with M18 FUEL™ Power Head w/ QUIK-LOK™ (2825-20)

**49-16-2717** M18 FUEL™ String Trimmer Attachment  
**49-16-2718** M18 FUEL™ Edger Attachment  
**49-16-2719** M18 FUEL™ Articulating Hedge Trimmer Attachment  
**49-16-2720** M18 FUEL™ 10" Pole Saw Attachment  
**49-16-2721** M18 FUEL™ 3' Attachment Extension



M18™ Brushless

String Trimmer Kit

2828-21 (2828-20 Tool-Only)

Specifications:

Cutting Swath	14" – 16"
Line Diameter	.080" / .095"
RPM	0 – 4,600 / 0 – 6,200
Trigger	Variable Speed
Feed System	Bump Feed
Length / Weight	73.6" / 11.5 lbs

**Includes:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Pack, Multi-Voltage Charger



M18 FUEL

24" Hedge Trimmer Kit

2726-21HD (2726-20 Tool-Only)

Specifications:

Blade Length	24"
Cut Capacity	3/4"
SPM	3,400
Gear Case	All Metal
Length / Weight	45.5" / 11.1 lbs

**Includes:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Scabbard, Rapid Charger



M18 FUEL

18" Hedge Trimmer

3001-20 Tool-Only

Specifications:

Blade Length	18"
Cut Capacity	3/4"
SPM	3,400
Gear Case	All Metal
Length / Weight	36.5" / 8.4 lbs

Battery and Charger Sold Separately

**Includes:** Scabbard



M18 FUEL

Blower Kit

2724-21HD (2724-20 Tool-Only)

Specifications:

Max Air Volume	450 CFM
Max Air Speed	120 MPH
Noise Rating (db)	62 (ANSI B175)
Lock On Button	Yes
Length / Weight	36.9" / 7.3 lbs

**Includes:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Rapid Charger



M18™ SWITCH TANK™ 4-Gallon

Backpack Sprayer Kit

2820-21PS (2820-20PS Tool-Only)

Specifications:

Tank Capacity	4 Gallon
Pump Type	Dual Diaphragm Pump
PSI Range	20 – 120 PSI (5 Modes)
Spray Distance	Up to 25'
Flow Rate Range	0.10 – 0.51 Gal/Min
Dry Weight	18.3 lbs

**Includes:** M18™ SWITCH TANK™ Powered Base, SWITCH TANK™ 4 Gallon Sprayer Tank Assembly, (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, Adjustable Nozzle, Fan Nozzle, Multi-Voltage Charger

**Related Accessories:**

**49-16-28WS** SWITCH TANK™ 4 Gallon Water Supply Tank Assembly  
**49-16-28CS** SWITCH TANK™ 4 Gallon Concrete Sprayer Tank Assembly  
**49-16-28PS** SWITCH TANK™ 4 Gallon Sprayer Tank Assembly



M18™ ROCKET™ Dual Pack Tower Light w/ ONE-KEY™ Kit

2120-22HD (2120-20 Tool-Only)

Specifications:

Lumens	5,400 / 3,100 / 1,600 (Customizable)
Modes	High, Medium, Low
Water & Dust Rating	IP67
Height	22" Collapsed, 5'5" Fully Extended
Weight	8.2 lbs

**Includes:** (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Packs, Shoulder Strap, Rapid Charger



M18™ RADIUS™ Site Light/Charger w/ ONE-KEY™

2150-20 Tool-Only

Specifications:

Lumens	9,000 / 4,800 / 2,500 (Customizable)
Modes	High, Medium, Low
Water & Dust Rating	IP54
Height / Weight	29.5" / 27.1 lbs

Battery and Charger Sold Separately



CHARGES



POWERED BY



M18™ RADIUS™ Site Light

2151-20 Tool-Only

Specifications:

Lumens	9,000 / 4,800 / 2,500
Modes	High, Medium, Low
Height / Weight	29.5" / 23.2 lbs

Battery and Charger Sold Separately



POWERED BY



M18™ RADIUS™ Compact Site Light w/ Flood Mode

2144-20 Tool-Only

Specifications:

Lumens (Area)	2,200 / 1,100 / 550
Lumens (Flood)	1,000 / 500 / 250
Modes	High, Medium, Low
Hands-Free	Self-Centering Metal Hook
Height / Weight	10.4" / 4.4 lbs

Battery and Charger Sold Separately



POWERED BY



M18™ ROVER™ Flood Light

2361-20 Tool-Only

Specifications:

Lumens	1,500 / 780
Modes	High, Low
Water & Dust Rating	IP54
Hands-Free	(1) EMT Hanger
Length / Weight	8.8" / 3.1 lbs

Battery and Charger Sold Separately



M18™ PACKOUT™ Light/Charger

2357-20 Tool-Only

Specifications:

Lumens	3,000 / 1,500 / 1,000
Modes	High, Medium, Low
Battery Charger	Charges all M18™ Batteries
USB Charger	2.1A USB Charging Port for External Devices
Device Storage	Weather Sealed

Battery and Charger Sold Separately



CHARGES



POWERED BY



M18™ Stick Light

2352-20 Tool-Only

Specifications:

Lumens	300 / 150
Modes	High, Low
Water & Dust Rating	IP54
Pivoting Head	45°
Hands-Free	2 Stainless Steel Hooks
Length / Weight	11.6" / 1.1 lbs

Battery and Charger Sold Separately



M18™ ROCKET™ Tower Light/Charger Kit

2136-21 (2136-20 Tool-Only)

Specifications:

Lumens	6,000 / 3,200 / 1,700
Modes	High, Medium, Low
Battery Charger	Charges M18™ Batteries and USB Devices
Height	40" Collapsed, 7' Fully Extended
Weight	21 lbs

**Includes:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, M18™ ROCKET™ Tower Light Carry Bag



CHARGES



POWERED BY



M18™ RADIUS™ Compact Site Light w/ ONE-KEY™

2146-20 Tool-Only

Specifications:

Lumens	4,400 / 2,100 / 1,000 (Customizable)
Modes	High, Medium, Low
Water & Dust Rating	IP54
Hands-Free	Self-Centering Metal Hook
Daisy Chain Compatible	Yes
Weight	10.6 lbs

Battery and Charger Sold Separately

**Includes:** Security Cable; **2147-20** Equipped with NEMA L5-20 Twistlock Outlets Also Available



POWERED BY



M18™ ROVER™ Mounting Flood Light

2365-20 Tool-Only

Specifications:

Lumens	1,500 / 650 / 300
Modes	High, Medium, Low
Water & Dust Rating	IP54
Rotating Head	Horizontal and Vertical
Hands-Free	Integrated Magnet, Spring Loaded Clamp
Length / Weight	6.3" / 3.2 lbs

Battery and Charger Sold Separately



CHARGES



POWERED BY



M18™ Trouble Light w/ USB Charging

2363-20 Tool-Only

Specifications:

Lumens	700 / 350 / 70 / 700
Modes	High, Medium, Low, Strobe
Run-Time	Up to 100 Hours
Beam Pattern	Adjustable Task – Area
Water & Dust Rating	IPX4
Hands-Free	2 Stainless Steel Hooks
USB Charger	2.1A USB Charging Port for External Devices
Length / Weight	11.5" / 1.2 lbs

Battery and Charger Sold Separately



CHARGES



M18™ ROCKET™ Dual Power Tower Light

2131-20 Tool-Only

Specifications:

Lumens	2,500 / 1,100 / 700
Modes	High, Medium, Low
Height	40" Collapsed, 7' Fully Extended
Weight	15.3 lbs

Battery and Charger Sold Separately



POWERED BY



M18™ RADIUS™ Compact Site Light

2145-20 Tool-Only

Specifications:

Lumens	4,400 / 2,100 / 1,000
Modes	High, Medium, Low
Water & Dust Rating	IP54
Hands-Free	Self-Centering Metal Hook
Daisy Chain Compatible	Yes
Weight	10.6 lbs

Battery and Charger Sold Separately

**Includes:** Security Cable



POWERED BY



M18™ ROVER™ Dual Power Flood Light

2366-20 Tool-Only

Specifications:

Lumens	4,000 / 2,000 / 1,200
Modes	High, Medium, Low
Hands-Free	Keyholes for Hanging
Length / Weight	9.7" / 5.8 lbs

Battery and Charger Sold Separately



POWERED BY



M18™ Search Light Kit

2354-21 (2354-20 Tool-Only)

Specifications:

Lumens	1,250 / 1,200 / 600 / 1,200
Modes	Spot/Flood, Flood, Spot, Strobe
Beam Distance	730 yd / 668 m
Water & Dust Rating	IP54
Head Rotation	198°
Length / Weight	11.5" / 3.1 lbs

**Includes:** (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Shoulder Strap, Multi-Voltage Charger





M18™ Power Source

49-24-2371

Specifications:

USB Charging Port	2.1A USB Charging Port for External Devices
Run-Time	Up to 18 Hours
Powered By	All M18™ Batteries

Battery Sold Separately

Powers all MILWAUKEE® M12™ Heated Gear



M18™ TOP-OFF™ 175W Power Supply

2846-20 Tool Only

Specifications:

Continuous Watts	175W
Power Source	Any M18™ Battery
DC Output	(1) USB-A Port, (1) USB-C PD Port
AC Output	(1) AC Outlet

Battery Sold Separately

M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 System Starter Kit

48-59-1200

**Includes:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Rapid Charger



M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 System Starter Kit

48-59-1880

**Includes:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Rapid Charger



M18™ REDLITHIUM™ XC5.0 System Starter Kit

48-59-1850

**Includes:** (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Multi-Voltage Charger



M18™ REDLITHIUM™ HIGH OUTPUT™ CP3.0 System Starter Kit

48-59-1835

**Includes:** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ CP3.0 Battery Pack, Multi-Voltage Charger



M18™ & M12™ Super Charger

48-59-1811

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
Charge Speed	Charges up to 4X Faster, Charges All HIGH OUTPUT™ Batteries in One Hour Or Less
On-Board Indicator Light	Yes
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes

Batteries Sold Separately

M18™ Six-Pack Sequential Charger

48-59-1806

Specifications:

Compatibility	All M18™ Batteries
Charge Sequence	Sequential (Counter-Clockwise Rotation)
Skip Button	Manually Designate which Battery Charges First
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes
Pass-Through Plug	Yes

Batteries Sold Separately

M18™ & M12™ Rapid Charge Station

48-59-1807

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Charges 3 Batteries Simultaneously
Charge Speed	Charges Individual Batteries up to 40% Faster
Capacity	Holds (3) M18™ and (3) M12™ Batteries
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes
Pass-Through Plug	Yes

Batteries Sold Separately

M18™ Dual Bay Simultaneous Rapid Charger

48-59-1802

Specifications:

Compatibility	All M18™ Batteries
Charge Sequence	Simultaneous
Charge Speed	Charges Individual Batteries up to 40% Faster
Integrated Hang-Holes	Yes

Batteries Sold Separately

M18™ & M12™ Rapid Charger

48-59-1808

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
Charge Speed	Charges Individual Batteries up to 40% Faster
On-Board Indicator Light	Yes
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes

Batteries Sold Separately

M18™ & M12™ Multi-Voltage Charger

48-59-1812

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
Integrated Hang-Holes	Yes
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes

Batteries Sold Separately

M18™ & M12™ Vehicle Charger

48-59-1810

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes

Batteries Sold Separately

**M18 REDLITHIUM™**

**HIGH OUTPUT™**

**50% MORE POWER & RUNS COOLER**  
VS REDLITHIUM™

**HIGH OUTPUT™ CP**

**HIGH OUTPUT™ XC**

**HIGH OUTPUT™ HD**

**CP**

**XC**

**HD**

**LIGHT DEMAND**

**FITS M18 TOOLS**

**HEAVY DEMAND**

**CP**


Less weight and smaller size


**XC**


More power and run-time, great performance for all demands


**HD**


Best performance for high demand applications

**HIGH OUTPUT**  
**48-11-1835** M18™ REDLITHIUM™ HIGH OUTPUT™ CP3.0 Battery Pack  
**48-11-1837** 2-Pack

**HIGH OUTPUT**  
**48-11-1820** M18™ REDLITHIUM™ HIGH OUTPUT™ CP2.0 Battery Pack  
**48-11-1815** M18™ REDLITHIUM™ CP1.5 Battery Pack  
**48-11-1811** 2-Pack

**HIGH OUTPUT**  
**48-11-1880** M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack  
**48-11-1865** M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Pack  
**48-11-1850** M18™ REDLITHIUM™ XC5.0 Battery Pack  
**48-11-1840** M18™ REDLITHIUM™ XC4.0 Battery Pack  
**48-11-1828** M18™ REDLITHIUM™ XC3.0 Battery Pack

**HIGH OUTPUT**  
**48-11-1862** 2-Pack  
**48-11-1852** 2-Pack  
**48-11-1851** 10-Pack  
**48-11-1822** 2-Pack


**HIGH OUTPUT**  
**48-11-1812** M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack

MILWAUKEE® is committed to improving productivity by providing performance-driven and trade-focused solutions so users can perform an entire day's work on one battery system.  
\*Due to the physical size increase of the M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0, it does not fit the following tools prior to a 6/1/2018 manufacturing date without applicable service part: 2787-20, 2788-20, 2771-20, 2122-20, 2130-20, 2135-20, 2361-20, 2145-20, 2146-20, 2360-20. MILWAUKEE® is committed to protecting end user's investments, offering FREE service upgrades for the listed products to any customer that purchases a HIGH OUTPUT™ HD12.0 battery pack (starting summer 2018 you will be able to visit eService to request your service upgrade).

M18™  
COMBO KITS

M18™ COMBO KITS	2 PIECE KITS										3 – 4 PIECE KITS		LARGE KITS			
	2996-22	2997-22	2893-22CX	2893-22	2697-22CT	2892-22CT	2691-22	2694-22	2992-22	2999-22	2897-22CT	2695-24	2696-24	2998-25	2696-26	2997-27
Kit Tool Total	2	2	2	2	2	2	2	2	2	2	2	4	4	5	6	7
M18 FUEL™ 1/2" Hammer Drill/Driver w/ ONE-KEY™	■															
M18 FUEL™ 1/2" Hammer Drill/Driver		■								■				■		■
M18™ 1/2" Brushless Hammer Drill/Driver			■	■					■							
M18™ 1/2" Compact Hammer Drill/Driver					■			■				■	■		■	
M18™ 1/2" Compact Brushless Drill/Driver						■										
M18™ 1/2" Compact Drill/Driver							■									
M18 FUEL™ Drywall Screw Gun											■					
M18 FUEL™ 1/4" Hex Impact Driver w/ ONE-KEY™	■															
M18 FUEL™ SURGE™ 1/4" Hex Hydraulic Driver										■	■					
M18 FUEL™ 1/4" Hex Impact Driver		■												■		■
M18™ 1/4" Hex Brushless Impact Driver			■			■										
M18™ Brushless 1/4" Hex 3-Speed Impact Driver				■												
M18™ 1/4" Hex Impact Driver*					■		■					■	■		■	
M18 FUEL™ 1/2" Mid-Torque Impact Wrench w/ Friction Ring																■
M18 FUEL™ SAWZALL® Reciprocating Saw														■		■
M18™ SAWZALL® Reciprocating Saw								■					■		■	
M18™ HACKZALL® One-Handed Reciprocating Saw												■				
M18 FUEL™ 6-1/2" Circular Saw														■		■
M18™ 6-1/2" Circular Saw															■	
M18™ Brushless 7-1/4" Circular Saw									■							
M18 FUEL™ 4-1/2" / 5" Grinder Paddle Switch, No-Lock																■
M18™ 4-1/2" Cut-Off / Grinder															■	
M18™ Work Light												■	■	■	■	■
Also Includes																
M18™ and M12™ Multi-Voltage Charger	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
M18™ REDLITHIUM™ CP1.5 Battery Pack					2		2									
M18™ REDLITHIUM™ CP2.0 Battery Pack			1			2					2					
M18™ REDLITHIUM™ XC3.0 Battery Pack												2	2		2	
M18™ REDLITHIUM™ XC4.0 Battery Pack			1	2					2							
M18™ REDLITHIUM™ XC5.0 Battery Pack	2	2						2		2				2		2
Carrying Case	■	■								■						
Contractor Bag			■	■	■	■	■	■	■		■	■	■	■	■	2

\*M18™ 1/4" Hex Impact Driver is the single, variable speed model





**EQUIPMENT REDEFINED  
TRADE FOCUSED  
SYSTEM WIDE**

**ALL MX FUEL™ BATTERIES FIT  
ALL MX FUEL™ EQUIPMENT**



**MX FUEL™**  
**14" Cut-Off Saw**  
MXF314-2XC



**MX FUEL™**  
**Handheld Core Drill**  
MXF301-2CP



**MX FUEL™**  
**ROCKET™ Tower**  
**Light/Charger**  
MXF041-1XC



**MX FUEL™**  
**Breaker**  
MXF368-1XC



**MX FUEL™**  
**Sewer Drum Machine**  
**w/ POWERREDZ™**  
MXF501-1CP



**MX FUEL™**  
**CARRY-ON™ 3600W/1800W**  
**Power Supply**  
MXF002-2XC



**MX FUEL™**  
**Backpack**  
**Concrete Vibrator**  
MXF371-2XC



**MX FUEL™**  
**Vibratory Screed**  
MXF381-2CP



# EQUIPMENT REDEFINED.

The MX FUEL™ Equipment System revolutionizes the light equipment market by delivering the performance, run-time and durability demanded by the trades without the hazards associated with emissions, noise, vibration and the frustrations of gas maintenance. This completely compatible system goes beyond the limitations of gasoline and power cord units, utilizing the industry's most advanced batteries, motors and electronics to deliver a best-in-class experience for users. This is Equipment Redefined.

## 1 REDLITHIUM™ BATTERY PACK

- Industry Leader in LITHIUM-ION Technology
- Patented Designs Protect Against Drops, Water and Harsh Environments
- Robust Electronics Optimize Performance for Every Equipment and Battery Combination



## 2 REDLINK PLUS™ INTELLIGENCE

- Most Advanced System of Equipment Electronics in the Industry
- Protects Equipment with Best-In-Class Thermal and Overload Monitoring
- Delivers In-Application Communication, Optimizing Equipment Performance



## 3 POWERSTATE™ BRUSHLESS MOTOR

- Engineered Uniquely for the Demands of Each Piece of Equipment
- Optimized for the Perfect Combination of Performance, Portability and Productivity
- Built with Maximum Copper Content and Top-Grade Rare Earth Magnets



**EQUIPMENT REDEFINED  
TRADE FOCUSED  
SYSTEM WIDE**

MX FUEL™

14" Cut-Off Saw Kit

NO  
GAS  
HEADACHES

FASTEST  
CUTS FROM  
START TO FINISH

6 FT IN  
CONCRETE,  
72 CUTS IN  
#5 REBAR  
PER CHARGE

MXF314-2XC

Specifications:

Blade Diameter	14"
Cut Depth	5"
Blade Arbor	1" / 20 mm
RPM	5,350
On-Board Water Delivery	Yes
Weight w/ Battery	32.1 lbs
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment, Battery & Charger

**Includes:** (2) MX FUEL™ REDLITHIUM™ XC406 Battery Packs, MX FUEL™ Charger, Wrench, Hex Key, Quick Connect, Contractor Bag

**Available Accessories:**  
(Not Included)

**49-94-1475**  
14" x 1/8" x 1" Cutting Wheel

**49-93-7540**  
14" Diamond  
Ultra Segmented Blade



**Additional Equipment:**  
(Not Included)

**3100**  
MX FUEL™  
14" Cut-Off Saw Cart

**2820-21WS**  
M18™ SWITCH TANK™  
4-Gallon Backpack  
Water Supply Kit

MX FUEL™

Breaker Kit

MOST  
PRODUCTIVE  
LOWEST  
VIBRATION

LIGHTEST  
IN CLASS

2 TONS  
PER  
CHARGE

MXF368-1XC

Specifications:

Chuck Size	1-1/8" Hex
Blows per Minute	1,300
Impact Energy (ft/lbs)	50
Vibration	4.9 m/s²
Soft Start	Yes
Weight w/ Battery	63.9 lbs
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment, Battery & Charger

**Includes:** (1) MX FUEL™ REDLITHIUM™ XC406 Battery Pack, MX FUEL™ Charger, Cart, (3) Chisels

**Available Accessories:**  
(Not Included)

**8960-20**  
8 Gallon  
Dust Extractor

**5321-DE**  
Dust Extraction  
Attachment

**48-62-4001**  
1-1/8" Hex 16"  
Moil Point

**48-62-4006**  
1-1/8" Hex 16"  
Narrow Chisel

MX FUEL™

Handheld  
Core Drill Kit w/ Stand

SAFER  
HANDHELD  
CORING

POWER TO CORE  
6" HOLES  
IN REINFORCED CONCRETE

EASIEST  
CORING  
ANYWHERE

MXF301-2CXS

Specifications:

Maximum Bit Capacity	6"
RPMs Low / High	790 / 1,550
Spindle Size	1-1/4" – 7
Wet / Dry Coring	Both
On-Board Water Delivery	Yes
Stand Included	Yes
Weight: Machine w/ CP Battery	21.6 lbs
Weight: Stand Only	29.0 lbs
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment, Battery & Charger

**Includes:** (1) MX FUEL™ REDLITHIUM™ XC406 Battery Pack, (1) MX FUEL™ REDLITHIUM™ CP203 Battery Pack, MX FUEL™ Charger, Compact Core Drill Stand, Trigger Lock, 5/8" – 11 Bit Adapter, Quick Connect, Hard Case with Wheels

MX FUEL™

Handheld  
Core Drill Kit

MXF301-2CP

Specifications:

Maximum Bit Capacity	6"
RPMs Low / High	790 / 1,550
Spindle Size	1-1/4" – 7
Wet / Dry Coring	Both
On-Board Water Delivery	Yes
Weight w/ Battery	21.6 lbs
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment, Battery & Charger

**Includes:** (2) MX FUEL™ REDLITHIUM™ CP203 Battery Packs, MX FUEL™ Charger, Trigger Lock, 5/8" – 11 Bit Adapter, Quick Connect, Hard Case with Wheels

**Available Accessories for MXF301-2CP & MXF301-2CXS:**  
(Not Included)

**2820-21WS**  
M18™ SWITCH TANK™  
4-Gallon Backpack  
Water Supply Kit

**8960-20**  
8 Gallon Dust Extractor

**5319-DE**  
Dry Coring  
Dust Extractor Attachment



**48-17-5030**  
3" Diamond  
Ultra Wet  
Core Bit

**48-17-0130**  
3" Diamond  
Ultra Dry  
Core Bit

Fastest Drilling,  
Maximum  
Run-Time

Fastest Drilling,  
Maximum  
Run-Time

MX FUEL™ CARRY-ON™ 3600W/1800W  
Power Supply Kit

POWER  
MORE  
ON DEMAND

PORTABLE  
POWER  
ANYWHERE

MORE  
EFFICIENT  
POWER

MXF002-2XC  
Specifications:

Peak Watts	3,600W
Running Watts	1,800W
Outlets	(2) 120V 15A Outlets
Inverter Output	Pure Sine Wave
Integrated Charger	Yes
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Ground Fault Isolated	Yes
Intended For	One 15 Amp Tool
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment and Battery

**Includes:** (2) MX FUEL™ REDLITHIUM™  
XC406 Battery Packs, Detachable Charger Cord

GROUND  
FAULT  
ISOLATED



MX FUEL™ ROCKET™ Tower  
Light/Charger Kit

MOST  
PORTABLE  
10' LIGHT  
INSIDE / OUTSIDE

27,000  
LUMENS OF  
TASK OR AREA LIGHTING

WITHSTANDS  
THE STORM

MXF041-1XC  
Specifications:

Max Lumens	27,000
Modes	High / Medium / Low
Collapsed Height	44"
Extended Height	10'
Width	20.8"
Depth	24.8"
Weight w/ Battery	110 lbs
Ingress Rating	Outdoor Use
Push Button Start	Yes
ONE-KEY™ Compatible	Customize. Track. Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment and Battery

**Includes:** (1) MX FUEL™ REDLITHIUM™  
XC406 Battery Pack



MX FUEL™ Sewer Drum Machine  
w/ POWERTREDZ™ Kit

POWERTREDZ™  
LIFT ASSIST

POWER  
TO CLEAR  
ROOTS AT 200'

MESS  
CONTAINED

MXF501-1CP  
Specifications:

Drain Line Capacity	3" – 8" up to 200'
Drum Capacity	100'
Cable Capacity	5/8" and 3/4"
Powered Cable Feed & Retract	Yes, CABLE DRIVE™
Cable Spin Speed	200 RPM
Height / Length	47" / 32.5"
Weight w/ Battery	125 lbs
Lift Assist	Yes, POWERTREDZ™
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment, Battery & Charger

**Includes:** (1) MX FUEL™ REDLITHIUM™ CP203 Battery Pack,  
MX FUEL™ Charger, 3/4" Anchor Cable



MX FUEL™ Sewer Drum  
Machine Accessories

Compatible with MXF501-1CP, MXF500-1CP

**Machine Accessories**  
47-53-5001 6-1/2" Guide Hose  
47-53-5002 Load Wheel

**5/8" Inner  
Core Cables**  
48-53-2325 – 25'  
48-53-2350 – 50'  
48-53-2310 – 100'

**3/4" Inner  
Core Cables**  
48-53-2425 – 25'  
48-53-2450 – 50'  
48-53-2410 – 100'  
**Leader Cables &  
Anchor Cable**  
48-53-2802 Leader Cable  
48-53-2902 Leader Cable  
48-53-2905 Anchor Cable

**Cable Head  
Attachments**  
48-53-2830 Straight Auger  
48-53-2831 Funnel Auger  
48-53-2835 Small Opening Tool  
48-53-2836 Medium Opening Tool  
48-53-2832 3" Root Cutters  
48-53-2833 4" Root Cutters  
48-53-2834 6" Root Cutters  
48-53-2837 3" Grease Cutters  
48-53-2838 4" Grease Cutters  
48-53-2829 Pin Key  
48-53-2839 Case  
48-53-2840 9 pc Cable Head  
Attachment Kit

Also Available:

MX FUEL™ Sewer Drum Machine Kit  
MXF500-1CP

Specifications:

Drain Line Capacity	3" – 8" up to 200'
Drum Capacity	100'
Cable Capacity	5/8" and 3/4"
Powered Cable Feed & Retract	Yes, CABLE DRIVE™
Cable Spin Speed	200 RPM
Height / Length	47" / 32.5"
Weight w/ Battery	110 lbs
Lift Assist	No
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment, Battery & Charger

**Includes:** (1) MX FUEL™ REDLITHIUM™ CP203 Battery Pack,  
MX FUEL™ Charger, 3/4" Anchor Cable



**MX FUEL™ Backpack Concrete Vibrator Kit**

**POWER**  
TO PUSH  
**2.5" HEAD**

**NO GAS HEADACHES**

**70 YDS<sup>3</sup> PER CHARGE.**  
1-1/2" HEAD, 7' WHIP

MXF371-2XC

**Specifications:**

Maximum Head Size	2-1/2"
Maximum Shaft Length	21 ft
Quick Connect	Yes
Weight w/ Battery	34.5 lbs
Push Button Start	Yes
Removable Harness	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Batteries
Wireless Remote Included	Yes
Compatible w/ Oztec	Yes
Warranty	2 Year Equipment, Battery & Charger

**Includes:** (2) MX FUEL™ REDLITHIUM™ XC406 Battery Packs, MX FUEL™ Charger, MX FUEL™ Concrete Vibrator Remote

**Available Accessories:**

(Not Included)

**48-37-5015**  
1-1/2" Head

**48-37-7007**  
7' Shaft

**48-37-5020**  
2" Head

**48-37-7014**  
14' Shaft

**MX FUEL™ Vibratory Screed Kit**

**POWER**  
TO PULL  
**16' BAR**

**NO GAS HEADACHES**

**2 HOURS PER CHARGE.**  
w/ 12' BAR

MXF381-2CP

**Specifications:**

VPM	4,000 – 9,000
Bar Range	4 – 16 ft
Adjustable Handlebars	Yes
Kickstand	Yes
Weight w/ Battery	37 lbs
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Compatible w/ MBW Bars	Yes
Warranty	2 Year Equipment, Battery & Charger

**Includes:** (2) MX FUEL™ REDLITHIUM™ CP203 Battery Packs, MX FUEL™ Charger, (1) 9/16 Wrench

**Available Accessories:**

(Not Included)

**48-38-2016** 16 ft Screed Bar  
**48-38-2014** 14 ft Screed Bar  
**48-38-2012** 12 ft Screed Bar  
**48-38-2010** 10 ft Screed Bar  
**48-38-2008** 8 ft Screed Bar  
**48-38-2006** 6 ft Screed Bar  
**48-38-2004** 4 ft Screed Bar

**MX FUEL™ Batteries and Charger**

**MX FUEL™ REDLITHIUM™ XC406 Battery**

MXFC406

**Specifications:**

Compatibility	Fits All MX FUEL™ Equipment
Charge Duration	90 min
Capacity	6.0 Ah
Fuel Gauge	Yes
REDLINK™ Intelligence	Yes
ONE-KEY™ Compatible	Yes
Warranty	2 Year

**MX FUEL™ REDLITHIUM™ CP203 Battery**

MXFCP203

**Specifications:**

Compatibility	Fits All MX FUEL™ Equipment
Charge Duration	45 min
Capacity	3.0 Ah
Fuel Gauge	Yes
REDLINK™ Intelligence	Yes
ONE-KEY™ Compatible	No
Warranty	2 Year

**MX FUEL™ REDLITHIUM™ XC406 Battery/Charger Expansion Kit**

MXFC-2XC

**Includes:** (2) MX FUEL™ REDLITHIUM™ XC406 Battery Packs, MX FUEL™ Charger

**MX FUEL™ Charger**

MXFC

**Specifications:**

Compatibility	Charges All MX FUEL™ Batteries
Charge Speed	Charges MX FUEL™ CP203 Battery in 45 min Charges MX FUEL™ XC406 Battery in 90 min
REDLINK™ Intelligence	Yes
On-Board Fan	Yes
Cell Voltage Monitoring	Yes
On-Board Indicator Light	Yes
Warranty	2 Year

**LEARN MORE**



**NEW**

**ONE-KEY™ BLUETOOTH TRACKING TAG**

**AVAILABLE IN**

**1 PC**  
48-21-2301

**2 PC**  
48-21-2302

**10 PC**  
48-21-2310

TRACKED BY  
**ONE-KEY**

**DOWNLOAD THE FREE APP NOW!**



Apple, the Apple logo and iBeacon are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Google Play and the Google Play logo are trademarks of Google Inc.

The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Milwaukee Tool is under license. Other trademarks and trade names are those of their respective owners.



**PORTABLE POWER TOOL**  
**(including cordless product – tool, battery pack(s) & battery charger and Work Lights – cordless flashlights)**  
LIMITED WARRANTY

Every MILWAUKEE® **power tool\*** (see exceptions below) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on an electric power tool which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **five (5) years\*\*** after the date of purchase unless otherwise noted. Return of the power tool to a MILWAUKEE *factory* Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

**Normal Wear:** Many power tools need periodic parts replacement and service to achieve best performance. This warranty does not cover repair when normal use has exhausted the life of a part including, but not limited to, chucks, brushes, cords, saw shoes, blade clamps, o-rings, seals, bumpers, driver blades, pistons, strikers, lifters, and bumper cover washers.

\*This **warranty** does not cover Air Nailers & Staplers; Airless Paint Sprayer; Cordless Battery Packs; Gasoline Driven Portable Power Generators; Hand Tools; Hoist – Electric, Lever & Hand Chain; M12™ Heated Gear; Reconditioned Product; and Test & Measurement Products. **There are separate and distinct warranties** available for these products.

\*\*The warranty period for **Job Site Radios, M12™ Power Port, M18™ Power Source, Jobsite Fan and Trade Titan™ Industrial Work Carts** is **one (1) year** from the date of purchase. The warranty period for the **M18 FUEL™ 1" D-Handle High Torque Impact Wrenches, Drain Cleaning Cables, AIRSNAKE™ Drain Cleaning Air Gun Accessories, REDLITHIUM™ USB Laser Levels, TRAPSSNAKE™ 25' Auger w/ CABLE DRIVE™** and **FORCE LOGIC™ Press Tool Accessories** is **two (2) years** from the date of purchase. The warranty period for the **M18™ Compact Heat Gun, 8 Gallon Dust Extractor, M18™ Framing Nailers, M18 FUEL™ 1/2" Ext. Anvil Controlled Torque Impact Wrench w/ ONE-KEY™, M18 FUEL™ 1" High Torque Impact Wrench w/ ONE-KEY™, M18 FUEL™ 2 Gal. Compact Quiet Compressor, M12™ Laser Levels, 165' Laser Detector, M12™ 23GA Pin Nailer, M18 FUEL™ ¼" Blind Rivet Tool w/ ONE-KEY™, M12 FUEL™ Low Speed Tire Buffer, M18 FUEL™ Random Orbital Polishers, and the M18™ Utility Fencing Stapler** is **three (3) years** from the date of purchase. The warranty period for the **LED** in the LED Work Light and the **LED Upgrade Bulb** for the Work Light is the lifetime of the product subject to the limitations above. If during normal use the LED or LED Bulb fails, the part will be replaced free of charge.

Warranty Registration is not necessary to obtain the applicable warranty on a MILWAUKEE power tool product. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **‘Service Center Search’** in the **Parts & Service** section of MILWAUKEE’s webside [www.milwaukeetool.com](http://www.milwaukeetool.com) or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest service facility for warranty and non-warranty service on a MILWAUKEE **electric power tool**.

**CORDLESS BATTERY PACK**  
LIMITED WARRANTY

Every MILWAUKEE® **battery pack** (sold with cordless product and/or as a replacement battery pack) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace a battery pack which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for the **stated warranty period** from date of purchase. Return of the battery pack to a MILWAUKEE *factory* Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. For the proper shipping procedure of battery packs, contact 1.800.SAWDUST (1.800.729.3878), or go to [www.milwaukeetool.com](http://www.milwaukeetool.com). A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

Battery Pack Cat. No.	Chemistry	Warranty Period (from date of purchase)
48-11-1812 48-11-1828 <i>(Serial number prefix “B41E” and later)</i> 48-11-1840 48-11-1850 48-11-1850R 48-11-1860 48-11-1865 48-11-1880 48-11-1890 48-11-2402 48-11-2440 48-11-2460 48-11-2830 <i>(Serial number prefix “C71”)</i>	LITHIUM-ION	Three (3) Years
48-11-0490 48-11-1815 48-11-1820 48-11-1835 48-11-2001 48-11-2401 48-11-2420 48-11-2430	LITHIUM-ION	Two (2) Years
48-11-1828 <i>(Serial number prefix “B41D” and earlier)</i> 48-11-1830 <i>(Serial number prefix “A95”)</i> 48-11-2830 <i>(Serial number prefix “A71”)</i>	LITHIUM-ION	Two (2) Years – plus, Three (3) Years Pro-Rata (prorated)*
48-11-0100 48-11-1024 48-11-1830 <i>(Serial number prefix “E95”)</i> 48-11-1970 48-11-2230	Nickel-Cadmium (Ni-Cd), Nickel-Metal-Hydride (Ni-MH), LITHIUM-ION	One (1) Year

\*The warranty period for MILWAUKEE M18™ 48-11-1828 (with the serial number prefix “B41D” and earlier), V18™ 48-11-1830 (with the serial number prefix “A95”), and V28™ 48-11-2830 (with the serial number prefix “A71”) is five (5) years / 2000 charges from the date of purchase, whichever first occurs. The first 1000 charges or 2 years of the warranty, whichever first occurs, are covered through free replacement of the defective battery. This means that for the earlier of the first 1000 charges or two (2) years from the date of purchase/first charge, a replacement battery will be provided to the customer for any defective battery free of charge. Thereafter, the remaining charges up to a total of 2000 or the remainder of the five (5) year period from the date of purchase, whichever first occurs, will be covered on a pro rata basis. This means that every customer gets an additional 1000 charges or three (3) years of pro rata warranty on the these battery packs, depending upon the amount of use. MILWAUKEE M18™ 48-11-1828 (with the serial number prefix “B41E” and later), V18™ 48-11-2830 (with the serial number prefix “E95”), and M28™ 48-11-2830 (with the serial number prefix “C71”) have different warranty periods, as listed.

Warranty Registration is not necessary to obtain the applicable warranty on a MILWAUKEE battery pack. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **‘Service Center Search’** in the **Parts & Service** section of MILWAUKEE’s website [www.milwaukeetool.com](http://www.milwaukeetool.com) or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest *service* facility for warranty and non-warranty service on a MILWAUKEE **battery pack**.

**HEATED GEAR**  
LIMITED WARRANTY

Every MILWAUKEE® **Heated Gear product** (including its battery holder/controller) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on a Heated Gear product which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **one (1) year\*** after the date of purchase. Return of a Heated Gear product to a MILWAUKEE *factory* Service Center location, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE personnel, misuse, alterations, abuse, normal wear and tear, or accidents.

\*This warranty does not cover a M12™ LITHIUM-ION Battery Pack, a M12™ Charger, or a REDLITHIUM™ USB battery; **there are separate and distinct warranties** available for these products.

Warranty Registration is not necessary to obtain the applicable warranty on MILWAUKEE Heated Gear products. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE..

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **‘Service Center Search’** in the **Parts & Service** section of MILWAUKEE’s website [www.milwaukeetool.com](http://www.milwaukeetool.com) or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest MILWAUKEE *factory* Service Center location.

**OUTDOOR POWER EQUIPMENT**  
LIMITED WARRANTY

Every MILWAUKEE® **outdoor power equipment product\*** (see exceptions below) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on an outdoor power equipment product which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **three (3) years\*\*** after the date of purchase unless otherwise noted. Return of the outdoor power equipment to a MILWAUKEE *factory* Service Center location or participating MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

**Normal Wear:** Many outdoor power equipment products need periodic parts replacement and service to achieve best performance. This warranty does not cover repair when normal use has exhausted the life of a part including, but not limited to mower blades, trimmer head, trimmer head spool, cutting lines, blades, chains, blower tubes, brushes, o-rings, and seals.

\*This **warranty** does not cover Cordless Battery Packs or Reconditioned Product. **There are separate and distinct warrantities** available for these products

\*\*The warranty period for SWITCH TANK™ tank assemblies, hoses, handles, and wands are **one (1) year** from the date of purchase.

MILWAUKEE does **not** cover freight or labor charges associated with the inspection and testing of **outdoor power equipment products** which are found by MILWAUKEE **not** to be a valid warranty claim. A valid warranty claim **must be substantiated** by the discovery of defective material or workmanship by MILWAUKEE.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **‘Service Center Search’** in the **Parts & Service** section of MILWAUKEE’s website [www.milwaukeetool.com](http://www.milwaukeetool.com) or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest *service* facility for warranty and non-warranty service on a MILWAUKEE **electric power tool**.

**REDLITHIUM USB**  
LIMITED WARRANTY

Every MILWAUKEE® **REDLITHIUM USB battery and charger\*** is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace repair a REDLITHIUM USB battery or charger which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **two (2) years** after the date of purchase unless otherwise noted. Return of the REDLITHIUM USB battery or charger to a MILWAUKEE *factory* Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. For the proper shipping procedure of battery packs, contact 1.800.SAWDUST (1.800.729.3878), or go to [www.milwaukeetool.com](http://www.milwaukeetool.com). A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

**Normal Wear:** This warranty does not cover repair or replacement when normal use has exhausted the life of a part including, but not limited to charging cables, and wall plugs.

\*This **warranty** does not cover any cordless product sold with the REDLITHIUM USB battery and/or charger. **There are separate and distinct warrantities** available for these products

Warranty Registration is not necessary to obtain the applicable warranty on MILWAUKEE Heated Gear products. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **‘Find a Service Center’** search in the **Parts & Service** section of MILWAUKEE’s website [www.milwaukeetool.com](http://www.milwaukeetool.com) or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest MILWAUKEE *factory* Service Center location.

**PERSONAL LIGHTING**

*(A) 2010R Milwaukee® Rechargeable 250L Penlight w/ Laser, 2011R Milwaukee® Rechargeable 500L Everyday Carry Flashlight w/ Magnet, and 2012R Milwaukee® Rechargeable Magnetic Headlamp and Task Light*  
2 YEAR LIMITED WARRANTY

The **rechargeable personal lighting products** referenced above are warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on the above Rechargeable Personal Lighting Products which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **two (2) years** after the date of purchase.

*(B) All other MILWAUKEE® Personal Lighting Products*  
LIMITED LIFETIME WARRANTY

All other MILWAUKEE **personal lighting products\*** (see exceptions below) are warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on a personal lighting product which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for the **lifetime** of such personal lighting products.

**Normal Wear:** This warranty does not cover repair or replacement when normal use has exhausted the life of a part including, but not limited to clips, straps, charging cables, wall plugs, and rubber gaskets. This warranty does cover the **LED** in the personal lighting products, subject to the limitations herein.

\*This warranty does not cover Cordless Battery Packs or Chargers. **There are separate and distinct warrantities** available for these products.

Return of all personal lighting products to a MILWAUKEE *factory* Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. The above warrantities do not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, accidents, or caused by alkaline batteries.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THE ABOVE WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTIES AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THESE WARRANTIES GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **‘Find a Service Center’** search in the **Parts & Service** section of MILWAUKEE’s website [www.milwaukeetool.com](http://www.milwaukeetool.com) or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest MILWAUKEE *factory* Service Center location.

**MX FUEL™ PRODUCT, BATTERY PACKS, AND CHARGERS**  
LIMITED WARRANTY

Every MILWAUKEE® **MX FUEL™ product, battery pack, and charger** is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace a MX FUEL™ product, battery pack, or charger which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **two (2) years** after the date of purchase. Return of the MX FUEL™ product, battery pack, or charger to a MILWAUKEE *factory* Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. For the proper shipping procedure of battery packs, contact 1.800.SAWDUST (1.800.729.3878), or go to [www.milwaukeetool.com](http://www.milwaukeetool.com). A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

**Normal Wear:** Many MX FUEL™ products need periodic parts replacement and service to achieve best performance. This warranty does not cover repair when normal use has exhausted the life of a part including, but not limited to, assist & drive belts, pulleys, blade flanges, vacuum gaskets, tool free handles, set pins, skis, drive couplers, rubber boots, auto feed, stabilize blocks, wheels, carrier wheels, cords, o-rings, seals, bumpers, driver blades, pistons, strikers, lifters, tool holder, and bumper cover washers.

Warranty Registration is not necessary to obtain the applicable warranty on a MX FUEL product, battery pack, or charger

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **‘Service Center Search’** in the **Parts & Service** section of MILWAUKEE’s website [www.milwaukeetool.com](http://www.milwaukeetool.com) or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest *service* facility for warranty and non-warranty service on a MILWAUKEE **MX FUEL™ product, battery pack or charger**.

# LIGHTNING MAX REPAIR

MILWAUKEE® understands the unpredictability of the jobsite and the need for fast, reliable repairs and replacements. Through our Lightning Max Repair Program we are committed to providing you the best service so you can minimize downtime and get the job done.

- SPEED:** Repair of your tool in 7 – 10 days
- PAY LESS, NOT MORE:** Guaranteed to never pay more than the quoted Lightning Max Repair price
- RELIABILITY:** All repairs are serviced by experienced, certified factory technicians
- QUALITY:** Only genuine MILWAUKEE® parts used

## WHERE TO GO FOR LIGHTNING MAX REPAIRS

### eSERVICE

Solution for quick, convenient repairs, best for smaller tool quantities.

- FedEx shipping to MILWAUKEE® repair facility
- Your tool returned directly to you – no need to pick it up
- Go to [www.milwaukeetool.com/eService](http://www.milwaukeetool.com/eService)

### FACTORY SERVICE CENTERS

Factory Service Centers also carry the widest variety of MILWAUKEE® Tools and Accessories for all your needs.  
**1-800-SAWDUST (1-800-729-3878)**

- Anaheim**  
1130 N Magnolia  
Anaheim, CA 92801
- Atlanta**  
6155 Jimmy Carter Blvd  
Suite F2  
Norcross, GA 30071
- Boston**  
375 University Avenue  
Westwood, MA 02090
- Chicago**  
6310 Gross Point Road  
Niles, IL 60714
- Cleveland**  
8200 Sweet Valley Drive  
Valley View, OH 44125
- Dallas**  
1625 W Mockingbird Ln  
Unit 205  
Dallas, TX 75235
- Denver**  
2500 W 8th Avenue, Unit E  
Denver, CO 80204
- Houston**  
3566 West T.C. Jester Blvd  
Houston, TX 77018
- Las Vegas**  
5580 S Decatur Blvd  
Unit 110  
Las Vegas, NV 89118

- Miami**  
3311 NW 82nd Avenue  
Miami, FL 33122
- Minneapolis/St. Paul**  
9705 Valley View Road  
Eden Prairie, MN 55344
- Milwaukee**  
13145 W Lisbon Road  
Brookfield, WI 53005
- New York City**  
3068 Whitestone Expressway  
Flushing, NY 11354
- Philadelphia**  
711 West Chester Pike  
Havertown, PA 19064
- San Antonio**  
14329 San Pedro Avenue, Suite D  
San Antonio, TX 78232
- San Diego**  
7849 – 7851 Clairemont Mesa Blvd.  
San Diego, CA 92111
- San Francisco/Oakland**  
2341 Lincoln Avenue  
Hayward, CA 94545
- Seattle**  
5963 Corson Avenue South  
Suite 104  
Seattle, WA 98108

- Washington D.C.**  
11900 Baltimore Ave  
Suite B  
Beltsville, MD 20705

- CANADA**  
**1-800-268-4015**  
**Edmonton**  
14506 – 115th Avenue NW  
Edmonton AB T5M 3B9
- Halifax**  
Unit 102 50 Akerley Blvd  
Dartmouth NS B3B 1R8
- Saskatoon**  
Unit 630 3530 Millar Ave  
Saskatoon SK S7P 0B3
- Vancouver**  
9000 Bill Fox Way, Unit 103A  
Burnaby BC V5J 5J3
- Vaughan**  
140 Fernstaff Court, Unit 4  
Vaughan ON L4K 3L8
- Winnipeg**  
675 Berry St, Unit H  
Winnipeg MB R3H 1A7

