



DOUBLE SIDED ENTRY

Type IPB-D/Type IPBB-D (continued)

CLEAR PART NO.	BLACK PART NO.	NUMBER OF CONDUCTORS	CONDUCTOR RANGE	APPROXIMATE DIMENSIONS (IN.)			HEX SIZE
				L	W	H	
IPB-NA250-2D	IPBB-NA250-2D	2	250 kcmil - 10 Sol.	2.15	2.63	2.13	5/16
IPB-NA250-3D	IPBB-NA250-3D	3		3.15	2.63	2.13	
IPB-NA250-4D	IPBB-NA250-4D	4		4.15	2.63	2.13	
IPB-NA250-5D	IPBB-NA250-5D	5		5.15	2.63	2.13	
IPB-NA250-6D	IPBB-NA250-6D	6		6.15	2.63	2.13	
IPB-NA250-8D	IPBB-NA250-8D	8		8.15	2.63	2.13	
IPB-NA250-10D	IPBB-NA250-10D	10		10.15	2.63	2.13	
IPB-NA250-12D	IPBB-NA250-12D	12		12.15	2.63	2.13	
IPB-NA250-14D	IPBB-NA250-14D	14		14.15	2.63	2.13	
IPB-NA350-2D	IPBB-NA350-2D	2	350 kcmil - 10 Sol.	2.4	3	2.5	5/16
IPB-NA350-3D	IPBB-NA350-3D	3		3.53	3	2.5	
IPB-NA350-4D	IPBB-NA350-4D	4		4.65	3	2.5	
IPB-NA350-5D	IPBB-NA350-5D	5		5.78	3	2.5	
IPB-NA350-6D	IPBB-NA350-6D	6		6.9	3	2.5	
IPB-NA350-8D	IPBB-NA350-8D	8		9.15	3	2.5	
IPB-NA350-10D	IPBB-NA350-10D	10		11.4	3	2.5	
IPB-NA350-12D	IPBB-NA350-12D	12		13.65	3	2.5	
IPB-NA350-14D	IPBB-NA350-14D	14		15.9	3	2.5	
IPB-NA600-2D	IPBB-NA600-2D	2	600 kcmil - 4 Str.	2.8	3	2.75	3/8
IPB-NA600-3D	IPBB-NA600-3D	3		4.13	3	2.75	
IPB-NA600-4D	IPBB-NA600-4D	4		5.45	3	2.75	
IPB-NA600-5D	IPBB-NA600-5D	5		6.78	3	2.75	
IPB-NA600-6D	IPBB-NA600-6D	6		8.1	3	2.75	
IPB-NA600-8D	IPBB-NA600-8D	8		10.75	3	2.75	
IPB-NA600-10D	IPBB-NA600-10D	10		13.4	3	2.75	
IPB-NA600-12D	IPBB-NA600-12D	12		16.05	3	2.75	
IPB-NA600-14D	IPBB-NA600-14D	14		18.7	3	2.75	
IPB-NA750-2D	IPBB-NA750-2D	2	750 kcmil - 2 Str.	3.02	3.38	3	3/8
IPB-NA750-3D	IPBB-NA750-3D	3		4.46	3.38	3	
IPB-NA750-4D	IPBB-NA750-4D	4		5.89	3.38	3	
IPB-NA750-5D	IPBB-NA750-5D	5		7.33	3.38	3	
IPB-NA750-6D	IPBB-NA750-6D	6		8.76	3.38	3	
IPB-NA750-8D	IPBB-NA750-8D	8		11.63	3.38	3	
IPB-NA750-10D	IPBB-NA750-10D	10		14.5	3.38	3	
IPB-NA750-12D	IPBB-NA750-12D	12		17.37	3.38	3	
IPB-NA750-14D	IPBB-NA750-14D	14		20.24	3.38	3	