

## **PERFORMAX TORCH** For use with MAP-Pro

A high intensity trigger start torch with a 360-degree swivel burn tube, and adjustable flame control. This torch comes with a continuous flame lock, allowing finger free use and is pressure regulated for consistent performance when inverted. The Max-Power flame delivers fast heat transfer, making this torch ideal for use with MAP-Pro<sup>™</sup> in multiple lower demand applications including brazing up to 1" diameter, soldering and heating.

- MAX POWER FLAME
- 360 DEGREE SWIVEL BURN TUBE
- INSTANT ON-OFF IGNITION
- CONTINUOUS FLAME LOCK
- ADJUSTABLE FLAME
- PRESSURE REGULATED FOR CONSISTENT PERFORMANCE WHEN INVERTED
- DURABLE ALUMINUM ALLOY BODY WITH ERGONOMIC DESIGN FOR EASY HANDLING
- FOR USE WITH MAP-PRO<sup>™</sup>



## PERFORMAX TORCH



## For use with MAP-Pro

## Specifications

| Item                  | PerforMax Torch  |
|-----------------------|--|
| Product Number        | 1811185  |
| Application           | Brazing on up to 1" diameter pipes, Soldering, Heating, Heat treating  |
| Barcode               | 9320688425546  |
| Fuel Type             | Designed for use with MAP Pro (sold separately)<br>Suitable for use with Propane.                            |
| Flame Type            | Max-Power.<br>A fast-spinning concentrated flame, for increased heat output.                                 |
| Connection            | CGA 600  |
| Ignition Type         | Trigger start  |
| Dimensions            | 14" Long (tip to hose)   |
| Net Weight            | 1.2lbs (556g)  |
| Max flame temperature | ~3730°F (2054°C) – In air flame temperature  |
| Approx. Run Time      | 1.5hrs per 14.1oz (400g) cylinder.   |
|                       | *When used with Ambro Controls Map-Pro cylinder (1811121).<br>Based on continuous use with fully open valve. |



858 779 0377

AMBRO@BROMIC.COM

AMBROCONTROLS.COM